







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE	
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A	
SPECIFIC DESCRIPTION OF THE ALTERATION.	
	ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY

		CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN	
		STA. 15300+00 TO STA. 15306+56 EROSION AND	
		SEDIMENT CONTROL PLAN	
 	 		1

KIEWIT PROJECT NO. CHA PROJECT NO. DRAWING NO.

C-411

AS NOTED DATE

0 12/16/2022 FINAL EM&CP SUBMISSION DB APP DRAWN BY: JJE DESIGNED BY: JTM APPROVED BY: JPR REV. NO. DATE SUBMITTAL / REVISION DESCRIPTION

DESIGN SEGMENT 3 PACKAGE 1C WORK ZONE TRAFFIC CONTROL MAIN STAGES

LANE CLOSURE WITH ALTERNATING ONE WAY TRAFFIC

TEMPORARY SIGN

15277+45

15280+75

15281+25

15295+90

15304+15

15281+25

15295+90

15304+15

15306+55

28

29

30

31



DRUM

TEMPORARY CONCRETE BARRIER (TCB)

■ FLAGGER

TYPE III BARRICADE

TEMPORARY TRAFFIC FLOW ARROW

ABBREVIATIONS

FLASHING ARROW SIGN UNIT

FEDERAL HIGHWAY ADMINISTRATION

MINIMUM

MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES

NEW YORK STATE

NEW YORK STATE DEPARTMENT OF TRANSPORTATION

STATION

- 1. ALL TRAFFIC CONTROL AND WORK AREA PROTECTION DEVICES SHALL BE FABRICATED AND INSTALLED IN ACCORDANCE WITH THE FEDERAL HIGHWAY ADMINISTRATION (FHWA) MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD) FOR STREETS AND HIGHWAYS, LATEST EDITION, EXCEPT AS NOTED.
- 2. ALL TEMPORARY TRAFFIC CONTROL AND WORK AREA PROTECTION DEVICES SHALL BE FURNISHED AND INSTALLED BY THE CONTRACTOR UNLESS OTHERWISE NOTED ON THE CONTRACT DRAWINGS AND APPROVED BY THE ENGINEER PRIOR TO COMMENCING WORK.
- 3. ALL MAINTENANCE AND PROTECTION OF TRAFFIC WORK SHALL CONFORM TO THE CONTRACT DRAWINGS. MAINTENANCE AND PROTECTION OF TRAFFIC SCHEMES SHOWN ON THE CONTRACT DRAWINGS SHALL NOT BE CHANGED BY THE CONTRACTOR WITHOUT THE WRITTEN PERMISSION OF THE ENGINEER.
- 4. THE TEMPORARY MAINTENANCE OF TRAFFIC AND WORK AREA PROTECTION DEVICE LOCATIONS SHOWN ON THE CONTRACT DRAWINGS ARE SCHEMATIC EXCEPT AS NOTED. LOCATION OF TRAFFIC CONTROL DEVICES MAY BE MODIFIED TO MEET FIELD CONDITIONS AS APPROVED BY THE ENGINEER.
- 5. ALL CLOSURES SHALL BE COORDINATED WITH THE ENGINEER. A SCHEDULE OF WORK SHALL BE SUBMITTED AT LEAST TWO WEEKS IN ADVANCE FOR APPROVAL BY THE ENGINEER.
- 6. THERE MAY BE ONGOING CONSTRUCTION CONTRACTS WITHIN THE VICINITY OF THE WORK AREA. DO NOT MOVE, MODIFY, OR RELOCATE ANY ITEM ASSOCIATED WITH THESE CONTRACTS WITHOUT PROPER APPROVAL OF AND COORDINATION WITH THE ENGINEER.
- 7. PERFORM WORK IN SUCH A MANNER AND SEQUENCE AS TO INTERFERE AS LITTLE AS POSSIBLE WITH THE PASSAGE OF VEHICLES, PEDESTRIANS, AND OTHER KINDS OF PUBLIC TRAFFIC.
- 8. ALL TEMPORARY MAINTENANCE OF TRAFFIC AND WORK AREA PROTECTION SIGN SUPPORTS AND MOUNTINGS SHALL BE IN CONFORMANCE WITH NYSDOT STANDARD SHEETS AND STANDARD SPECIFICATIONS.
- 9. ALL CONSTRUCTION SIGNS SHALL BE COVERED WITH THICK PLASTIC WHEN THE WORK THEY ARE INTENDED FOR IS NOT IN PROGRESS.
- 10. ALL TRAFFIC CONTROL DEVICES SHALL BE INSTALLED PRIOR TO THE COMMENCEMENT OF THE WORK TO WHICH THEY APPLY. AND SHALL BE MAINTAINED BY THE CONTRACTOR THEREAFTER. THE DEVICES SHALL REMAIN IN PLACE AS LONG AS THEY ARE APPLICABLE.
- 11. TRAFFIC CONTROL DEVICES SHALL NOT BE PLACED AT ANY LOCATIONS WHERE THEY MAY OBSCURE OR INTERFERE WITH THE MOTORIST'S VIEW OF APPROACHING, MERGING, OR INTERSECTING TRAFFIC; OBSTRUCT OTHER TEMPORARY OR PERMANENT TRAFFIC CONTROL DEVICES WHICH ARE STILL APPLICABLE TO ROADWAY CONDITIONS: MISLEAD OR MISDIRECT MOTORISTS, OR ARE BLOCKED BY OTHER TEMPORARY OR PERMANENT OBJECTS.
- 12. ALL EXISTING ROADWAY ITEMS SUCH AS GUIDE RAILS. PAVEMENT MARKINGS, CURBS, SIGNALS AND SIGNS DAMAGED BY THE CONTRACTOR SHALL BE RESTORED BY THE CONTRACTOR TO THE SATISFACTION OF THE ENGINEER AT NO ADDITIONAL COST.
- 13. TRAFFIC LANES AND OTHER AREAS CLOSED BY THE CONTRACTOR DURING PERMITTED WORK HOURS SHALL BE CLEARED OF ALL MATERIAL, EQUIPMENT, AND DEBRIS, AND SAFELY REOPENED TO TRAFFIC BY THE END OF THE WORK PERIOD UNLESS OTHERWISE INDICATED ON THE CONTRACT DRAWINGS.
- 14. IF THE CONTRACTOR REQUIRES A LANE CLOSURE TO PERFORM OPERATIONS, THEY MAY DO SO WITH THE APPROVAL OF THE ENGINEER. ANY LANE CLOSURES WILL BE SHORT TERM AND IN ACCORDANCE WITH NYS STANDARD SHEETS UNLESS OTHERWISE SHOWN IN CONTRACT PLANS.
- 15. NO WORK ACTIVITY OR STORAGE OF EQUIPMENT, VEHICLES, OR MATERIAL SHOULD OCCUR WITHIN A BUFFER SPACE.
- 16. CHANNELIZING DEVICE SPACING (CENTER TO CENTER) SHALL NOT EXCEED 20' IN THE ACTIVE WORK SPACE.
- 17. ALL OPEN TRENCH EXCAVATIONS SHALL BE BACKFILLED OR COVERED BY A STEEL PLATE (HS-20 LOAD RATED) AT THE END OF EACH WORK DAY, OR AS DIRECTED BY THE ENGINEER.
- 18. PRIOR TO COMMENCING ANY WORK, THE CONTRACTOR SHALL COORDINATE WITH CP RAILROAD FOR RAILROAD FLAGGING FOR ALL WORK IN THE VICINITY OF ANY RAILROAD GRADE CROSSING AND WHENEVER WITHIN THE RAILROAD ROW.
- 19. ALL ADDITIONAL TEMPORARY SIGNAGE, NOT COVERED IN FHWA MUTCD, SHALL COMPLY WITH NYS SUPPLEMENT TO MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES.

- 20. DURING NON-WORK HOURS. LEAVE DRUMS AND TCB IN PLACE. OR AS DIRECTED AT THE ENGINEER.
- 21. DURING WINTER MORATORIUM, COVER EXCAVATIONS WITH TEMPORARY ASPHALT AND OPEN ALL LANES TO TRAFFIC.
- 22. THE WZTC DETAILS CONTAINED IN THE CONTRACT PLANS SUPPLEMENT THE CURRENT NYSDOT STANDARD SHEETS. REFERENCE SHALL BE MADE TO THE APPLICABLE NYSDOT STANDARD SHEETS FOR ALL NOTES AND TABLES. THE LATEST REVISIONS OF THE STANDARD SHEETS MAINTAINED BY NYSDOT. WHICH ARE CURRENT ON THE DATE OF ADVERTISEMENT FOR BIDS, SHALL BE CONSIDERED TO BE IN EFFECT. ALL PAY ITEMS AND WORK CONTAINED IN THE CONTRACT AND ANY ADDITIONAL PAY ITEMS AND WORK ENCOUNTERED DURING THE COURSE OF THE CONTRACT SHALL BE SUBJECT TO THE APPLICABLE STANDARD SHEET(S) UNLESS OTHERWISE SPECIFIED IN THE CONTRACT DOCUMENTS.
- 23. MAINTAIN SAFE AND ADEQUATE ACCESS FOR INTERSECTING ROADWAYS, HOMES, AND BUSINESSES, AT ALL TIMES, TO THE SATISFACTION OF THE ENGINEER.
- 24. ACCESS TO RESIDENTIAL AND COMMERCIAL DRIVEWAYS SHALL BE MAINTAINED AT ALL TIMES. UNLESS OTHER AGREEMENTS SUITABLE TO THE PROPERTY OWNERS CAN BE MADE, PROPERTY OWNERS WHOSE DRIVEWAYS WILL BE MADE INACCESSIBLE SHALL BE NOTIFIED BY THE CONTRACTOR AT LEAST 24 HOURS PRIOR TO RESTRICTING USE OF THE DRIVEWAY. THE CONTRACTOR SHALL MAINTAIN ACCESS TO COMMERCIAL DRIVEWAYS AT ALL TIMES WHEN A FACILITY IS IN USE. FOR MULTIPLE ACCESS PROPERTIES. ONLY ONE DRIVEWAY MAY BE CLOSED AT ANY ONE TIME. ACCESS SHALL BE RESTORED TO ALL DRIVEWAYS AS SOON AS POSSIBLE, OR AS DIRECTED BY THE ENGINEER.
- 25. THE CONTRACTOR'S ATTENTION IS DIRECTED TO THE FACT THAT THE FOLLOWING HOLIDAY WORK RESTRICTIONS ARE APPLICABLE TO THIS PROJECT. DURING THESE HOLIDAY PERIODS, THE CONTRACTOR WILL NOT BE ALLOWED TO PERFORM ANY WORK THAT WILL BE DISRUPTIVE TO TRAFFIC, INCLUDING BUT NOT LIMITED TO LANE CLOSURES. LANE CLOSURES WILL NOT BE PERMITTED DURING THE FOLLOWING STATE RECOGNIZED HOLIDAYS:
 - 1) CHRISTMAS DAY SUNDAY, DECEMBER 25, 2022
 - 2) NEW YEAR'S DAY SUNDAY, JANUARY 1, 2023
 - 3) MEMORIAL DAY - MONDAY, MAY 29, 2023
 - 4) INDEPENDENCE DAY TUESDAY, JULY 4, 2023 5) LABOR DAY - MONDAY, SEPTEMBER 4, 2023
 - 6) THANKSGIVING DAY THURSDAY, NOVEMBER 23, 2023 7) CHRISTMAS DAY - MONDAY, DECEMBER 25, 2023
 - 8) NEW YEAR'S DAY - MONDAY, JANUARY 1, 2024
 - 9) MEMORIAL DAY - MONDAY, MAY 27, 2024 10) INDEPENDENCE DAY - THURSDAY, JULY 4, 2024
 - MONDAY, SEPTEMBER 2, 2024 11) LABOR DAY 12) THANKSGIVING DAY - THURSDAY, NOVEMBER 28, 2024
- 13) CHRISTMAS DAY WEDNESDAY, DECEMBER 25, 2024
- 14) NEW YEAR'S DAY WEDNESDAY, JANUARY 1, 2025 15) MEMORIAL DAY - MONDAY, MAY 26, 2025
- 16) INDEPENDENCE DAY FRIDAY, JULY 4, 2025 17) LABOR DAY - MONDAY, SEPTEMBER 1, 2025
- 18) THANKSGIVING DAY THURSDAY, NOVEMBER 27, 2025 19) CHRISTMAS DAY - THURSDAY, DECEMBER 25, 2025
- 26. LANE CLOSURES SHALL BE SUSPENDED AS FOLLOWS:
 - BEGINNING 6AM, FRIDAY DECEMBER 23, 2022 AND ENDING 6AM, MONDAY DECEMBER 26, 2022 - BEGINNING 6AM, FRIDAY DECEMBER 30, 2022 AND ENDING 6AM, TUESDAY JANUARY 3, 2023
 - BEGINNING 6AM, FRIDAY MAY 26, 2023 AND ENDING 6AM, TUESDAY MAY 30, 2023 - BEGINNING 6AM, SATURDAY JULY 1, 2023 AND ENDING 6AM, WEDNESDAY JULY 5, 2023
 - BEGINNING 6AM, FRIDAY SEPTEMBER 1, 2023 AND ENDING 6AM, TUESDAY SEPTEMBER 5, 2023 - BEGINNING 6AM. WEDNESDAY NOVEMBER 22. 2023 AND ENDING 6AM. MONDAY NOVEMBER 27. 2023 - BEGINNING 6AM. FRIDAY DECEMBER 22, 2023 AND ENDING 6AM, TUESDAY DECEMBER 26, 2023
 - BEGINNING 6AM, FRIDAY DECEMBER 29, 2023 AND ENDING 6AM, TUESDAY JANUARY 2, 2024 - BEGINNING 6AM. FRIDAY MAY 24. 2024 AND ENDING 6AM. TUESDAY MAY 28. 2024
 - BEGINNING 6AM, WEDNESDAY JULY 3, 2024 AND ENDING 6AM, MONDAY JULY 8, 2024 - BEGINNING 6AM. FRIDAY AUGUST 30. 2024 AND ENDING 6AM. TUESDAY SEPTEMBER 3. 2024
 - BEGINNING 6AM, WEDNESDAY NOVEMBER 27, 2024 AND ENDING 6AM, MONDAY DECEMBER 2, 2024
 - BEGINNING 6AM, TUESDAY DECEMBER 24, 2024 AND ENDING 6AM, MONDAY DECEMBER 30, 2024
 - BEGINNING 6AM, TUESDAY DECEMBER 30, 2024 AND ENDING 6AM, FRIDAY JANUARY 3, 2025 - BEGINNING 6AM, FRIDAY MAY 23, 2025 AND ENDING 6AM, TUESDAY MAY 27, 2025 - BEGINNING 6AM, THURSDAY JULY 3, 2025 AND ENDING 6AM, MONDAY JULY 7, 2025
 - BEGINNING 6AM, FRIDAY AUGUST 29, 2025 AND ENDING 6AM, TUESDAY SEPTEMBER 2, 2025 - BEGINNING 6AM, WEDNESDAY NOVEMBER 26, 2025 AND ENDING 6AM, MONDAY DECEMBER 1, 2025 - BEGINNING 6AM, WEDNESDAY DECEMBER 24, 2025 AND ENDING 6AM, MONDAY DECEMBER 29, 2025
- 27. DURING WINTER STORM EVENTS, NO WORK WITHIN THE ROAD RIGHT-OF-WAY IS PERMITTED TO ALLOW FOR SNOW REMOVAL
- 28. ANY EARTHWORK DONE BETWEEN NOVEMBER 1ST AND APRIL 1ST

MUST CONFORM TO NYSDOT STANDARD SPECIFICATION SECTION 203-1.01 P.

AND PLOWING ACTIVITIES.





CP RAIL R.O.W.

CP RAIL/RYDER RD

CP RAIL R.O.W.

CP RAIL R.O.W.

CP RAIL R.O.W.



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED THE ALTERING ENGINEER ARCHITECT LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THFIR SIGNATURE. THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

SPLICE VAULT INTSALLATION

TRENCHING & CONDUIT INSTALLATION

TRENCHING & CONDUIT INSTALLATION

HORIZONTAL DIRECTIONAL DRILLING INSTALLATION

TRENCHING & CONDUIT INSTALLATION

C-502

No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	
0	12/16/2022	FINAL EM&CP SUBMISSION	JS	МН	\perp
					7

CHAMPLAIN HUDSON POWER EXPRESS **SEGMENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN** WORK ZONE TRAFFIC CONTROL NOTES

LEGEND AND ABBREVIATIONS


21162 CHA PROJECT NO. 066076 DRAWING NO.


KIEWIT PROJECT NO.

C-501

12/16/2022

AS SHOWN DRAWN BY: JAH | DESIGNED BY: JPS | APPROVED BY: MDH | REV. NO.





FILE NAME = V:\Projects\ANY\K6\066076.000\09_Design\Drawings\Hwu\Segment 3\PIC\








IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

					JOLGINILINI 3 (PACKAGE 16) WHITEHALL TO FORT AN
					,
					WORK ZONE TRAFFIC CONTROL DETAILS
					SHEET 3 OF 3
0	12/16/2022	FINAL EM&CP SUBMISSION	JS	МН	
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	SCALE AS SHOWN
NO.	DAIL	SUBMITTAL/ REVISION DESCRIPTION	DB	AFF	DRAWN BY: JAH DESIGNED BY: JPS APPROVED BY: MDH REV. NO.

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN


KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

C-504



INSTALLATION AND REMOVAL. 4. SEE EROSION CONTROL PLANS FOR LOCATIONS OF TREE PROTECTION AREAS.

TREE PROTECTION NOT TO SCALE



- 1. TIE FABRIC TO WIRE FENCE IN ACCORDANCE WITH
- 2. IF EXTRA STRENGTH FABRIC (GREATER THAN 50#/INCH) IS USED, WIRE CAN BE DELETED IF POST SPACING IS REDUCED TO 6' O.C.
- 3. AT THE ENDS OF THE FENCING THE FIRST 20' SHALL BE TURNED UP THE SLOPE 2'.
- 4. POSTS SHOULD BE INCLINED TOWARD THE DIRECTION FLOW CAME
- 5. OVERLAP FABRIC A MINIMUM OF 6" AND FOLDED AT JOINTS. ATTACH FILTER FABRIC TO STAKES ALLOWING EXTENSION INTO TRENCH AS SHOWN; SECURE TO STAKES AS NOTED.
- 6. THE MAXIMUM AREA OF RUNOFF PER 100LF. OF FENCE SHALL NOT EXCEED 0.25 ACRES.
- MAINTENANCE SHALL BE PERFORMED AS NECESSARY. THE FENCING SHALL BE CHECKED AFTER EVERY STORM TO ENSURE THEIR PROPER FUNCTIONING.
- WHEN FENCE IS NO LONGER NEEDED, THE ACCUMULATED SILT, THE POSTS AND FABRIC SHALL BE REMOVED AND TRENCH BACK FILLED WITH TOPSOIL AND SEEDED.
- 9. FENCING SHOULD BE PLACED AS SHOWN ON THE DRAWING OR IF NOT SHOWN, 10' BEYOND THE TOE OF THE SLOPE AND AT A SPACING IN ACCORDANCE WITH THE TABLE.
- 10. EXCAVATE TRENCH AS PER DETAIL AND SET POSTS AT 10' O.C.
- 11. BACKFILL WITH COMPACTED, EXCAVATED SOIL FROM TRENCH.

-NORTH AMERICAN GREEN S75 OR APPROVED EQUAL ON SUBGRADE, TEMP. SEED MIXTURE FILTER SOCK, SIZED TO SUIT CONDITIONS. -HARDWOOD POST 10' O.C. WATER FLOW INLET SIDE FILTER COMPOST MATERIAL

1. ALL MATERIAL TO MEET MANUFACTURER SPECIFICATIONS. 2. ALL FILTER SOCKS SHALL BE 12" DIAMETER OR LARGER. 3. THE CONTRACTOR SHALL MAINTAIN THE COMPOST FILTER BERM IN A FUNCTIONAL CONDITION AT ALL TIMES AND IT SHALL BE

AS PER SPECIFICATIONS.

- ROUTINELY INSPECTED. 4. WHERE THE BERM REQUIRES REPAIR, IT WILL BE ROUTINELY REPAIRED.
- 5. THE CONTRACTOR SHALL REMOVE SEDIMENTS COLLECTED AT THE BASE OF THE BERM WHEN THEY REACH 1/3 OF THE EXPOSED HEIGHT OF THE BERM, OR AS DIRECTED BY THE
- 6. THE COMPOST FILTER BERM WILL BE REMOVED ON SITE WHEN NO LONGER REQUIRED, AS DETERMINED BY THE OWNERS.

CHANNEL PLACEMENT

SOCK

FILTER

SOCK

FILTER

SOCK

MAINTENANCE NOTES:

TOP OF CHANNEL/BANK

FILTER SOCK SHALL BE PLACED PERPENDICULAR TO THE FLOW


ACROSS THE ENTIRE WIDTH OF

THE CHANNEL

BOTTOM OF CHANNEL

- 1. TRAFFIC SHALL NOT BE PERMITTED TO CROSS FILTER 2. ACCUMULATED SEDIMENT SHALL BE REMOVED WHEN
- IT REACHES 3 OF THE EXPOSED HEIGHT OF THE PRACTICE AND DISPOSED OF IN ACCORDANCE WITH THE SWPPP. 3. SOCKS SHALL BE INSPECTED WEEKLY AND AFTER EACH RUNOFF EVENT. DAMAGED SOCKS SHALL BE
- REPAIRED IN THE MANNER REQUIRED BY THE MANUFACTURER OR REPLACED WITHIN 24 HOURS OF INSPECTION NOTIFICATION. BIODEGRADABLE FILTER SOCKS SHALL BE REPLACED AFTER 6 MONTHS: PHOTO-DEGRADABLE FILTER
- SOCKS AFTER 1 YEAR. POLY-PROPYLENE SOCKS SHALL BE REPLACED ACCORDING TO THE MANUFACTURER'S RECOMMENDATIONS.


5. UPON STABILIZATION OF THE AREA CONTRIBUTORY TO THE SOCK, STAKES SHALL BE REMOVED. THE SOCK SHALL BE REMOVED. FOR REMOVAL THE MESH CAN BE CUT AND COMPOST SPREAD AS AN ADDITIONAL MULCH TO ACT AS A SOIL SUPPLEMENT.




AT GRADE PLACEMENT

COMPOST FILTER SOCK DETAIL SCALE: N.T.S.

7. INSTALL PERPENDICULAR TO FLOW.






TYPICAL CULVERT OUTFALL RIP RAP

TYPICAL OUTFALL ON SLOPE

EXISTING OR PROPOSED FINISHED GRADE ┌ 1'-0" MIN. 4"-TOPSOIL, SEED SIDE SLOPES AND BOTTOM

TYPICAL GRASS DRAINAGE SWALE



SCALE: N.T.S.

3 SILT FENCE







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY, IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ACTION ACTION ACTION ACTION ACTION AND ACTION ACTION AND ACTION ACTION AND ACTION ACTION ACTION AND ACTION A


					CHAMPLAIN HUDSON POWER EX SEGMENT 3 (PACKAGE 1C) WHITEHALL TO
					EROSION AND SEDIMENT CONTROL DI
					-
)	12/16/2022	FINAL EM&CP SUBMISSION	JTM	JPR	
ο.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: JJE DESIGNED BY: JTM APPROVED BY: JPR REV. NO.

AMPLAIN HUDSON POWER EXPRESS IENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN ROSION AND SEDIMENT CONTROL DETAILS

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. DRAWING NO.

C-601

12/16/2022



6' LONG 13 GAUGE RUST PROOF -STEEL FENCE POST WITH STABILIZING ANCHOR PLATES -CONSTRUCTION FLAT ORIENTED OR DIAMOND MESH BARRIER FENCE CONSTRUCTION FENCE BY RESINET OR EQUAL WARNING SIGN (SEE ADJACENT DETAIL) (SIGNS SPACED AT 48' ON CENTER±) EXISTING GRADE ELEVATION

1. CONSTRUCTION BARRIER FENCE SHALL BE INSTALLED IN THE LOCATIONS SHOWN ON THE PLANS PRIOR TO BEGINNING ANY WORK ADJACENT TO

2. THE CONTRACTOR SHALL INSTALL AT THE BEGINNING OF THE CONTRACT, AND MAINTAIN THROUGHOUT ITS DURATION.

3. SET BOTTOM OF CONSTRUCTION BARRIER FENCE FLUSH WITH EXISTING

4. CONSTRUCTION BARRIER FENCE SHALL HAVE A MINIMUM TENSILE STRENGTH OF 2000 PSI.

WORK AREA AREA TO BE PROTECTED -CONSTRUCTION BARRIER FENCE INSTALLED AT R.O.W. (SEE DETAIL)-6' LONG 13 GAUGE RUST PROOF -STEEL FENCE POST WITH STABILIZING ANCHOR PLATES SILT SOXX PROTECTED -WHITE LETTERING ON RED BACKGROUND. FASTEN TO FENCE POST AREA 1.3'

KEEP OUT

WARNING SIGN DETAIL

STAPLE OR STAKE PER-MANUFACTURER'S RECOMMENDATIONS NORTH AMERICAN GREEN -ECB, MIRAFI MIRAMAT OR APPROVED EQUAL TOE TO BE BACKFILLED WITH COMPACTED EARTH

EROSION CONTROL BLANKETS TO BE INSTALLED ON SLOPES 3:1 OR GREATER (TYP.)

3 EROSION CONTROL BANK STABILIZATION DETAIL SCALE: N.T.S.

50' MINIMUM FROM WETLANDS/WATERBODIES PUMP — **DISCHARGE** STRAP


SPOUT - WATER SEDIMENT_ DEWATERING | FILTERED — 2' WIDE x 1' HIGH #2 STONE BERM (TYP) — #2 STONE BERM AGGREGATE OR STRAW ---SIDE VIEW UNDERLAY (FOR ADDED FLOW)

NOTE: THE SEDIMENT DEWATERING BAG WILL BE MANUFACTURED IN THE U.S.A. FROM A NONWOVEN POLYPROPYLENE FABRIC THAT MEETS OR EXCEEDS THE FOLLOWING SPECIFICATIONS:


SEDIMENT DEWATERING BAG SPECIFICATIONS

Mechanical Properties	Test Method	Units	MARV
Grab Tensile Strength	ASTM D 4632	kN (lbs)	0.9 (205) x 0.9 (205)
Grab Tensile Elongation	ASTM D 4632	%	50 x 50
Puncture Strength	ASTM D 4833	kN (lbs)	0.58 (130)
Mullen Burst Strength	ASTM D 3786	kPa (psi)	2618 (380)
Trapezoid Tear Strength	ASTM D 4533	kN (lbs)	0.36 (80) X 0.36 (80)
UV Resistence	ASTM D 4355	%	70
Apparent Opening Size	ASTM D 4751	Mm (US Std Sieve)	0.180 (80)
Flow Rate	ASTM D 4491	1/min/m² (gal/min/ft²)	3866 (95)
Permittivity	ASTM D 4491	Sec ⁻¹	1.2

SEDIMENT DEWATERING BAG



- 1. STONE SIZE-USE AASHTO M43 SIZE 3 COARSE AGGREGATE, OR RECLAIMED OR RECYCLED CONCRETE EQUIVALENT.
- 2. LENGTH NOT LESS THAN 50 FEET (EXCEPT ON A SINGLE RESIDENCE LOT WHERE A 30 FOOT MINIMUM LENGTH WOULD
- 3. THICKNESS NOT LESS THAN 12".
- 4. WIDTH TWELVE (12) FOOT MINIMUM, BUT NOT LESS THAN THE FULL WIDTH AT POINTS WHERE INGRESS OR EGRESS OCCURS. TWENTY-FOUR (24) FOOT IF SINGLE ACCESS TO SITE.
- 5. WOVEN GEOTEXTILE FABRIC WILL BE PLACED OVER THE ENTIRE AREA PRIOR TO PLACING OF STONE.
- 6. EXISTING ROAD SIDE DRAINAGE SHALL BE MAINTAINED.
- 7. SURFACE WATER ALL SURFACE WATER FLOWING OR DIVERTED TOWARD CONSTRUCTION ENTRANCES SHALL BE PIPED BENEATH THE ENTRANCE. IF PIPING IS IMPRACTICAL, A MOUNTABLE BERM WITH 5:1 SLOPES WILL BE PERMITTED.
- 8. MAINTENANCE-THE ACCESS SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHTS-OF-WAY. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH ADDITIONAL STONE AS CONDITIONS DEMAND AND REPAIR AND/OR CLEANOUT OF ANY MEASURES USED TO TRAP SEDIMENT. ALL SEDIMENT OR STONE SPILLED, DROPPED, WASHED, OR TRACKED ONTO PUBLIC RIGHTS-OF-WAY MUST BE REMOVED IMMEDIATELY.
- 9. WHEN WASHING IS REQUIRED, IT SHALL BE DONE ON A AREA STABILIZED WITH STONE AND WHICH DRAINS INTO AN APPROVED SEDIMENT TRAPPING DEVICE.
- 10. PERIODIC INSPECTION AND NEEDED MAINTENANCE SHALL BE PROVIDED AFTER EACH RAIN.



A CONTAINMENT VESSEL AND PROPERLY DISPOSED OF OFF SITE. 3. DISPOSAL OF THE HARDENED MATERIAL SHALL BE OFF-SITE IN A CONSTRUCTION/DEMOLITION LANDFILL.

MAINTENANCE NOTES:

FILTER STRIP.

4. THE PLASTIC LINER SHALL BE REPLACED WITH EACH CLEANING OF THE WASHOUT FACILITY. 5. INSPECT THE PROJECT SITE FREQUENTLY TO ENSURE THAT NO CONCRETE DISCHARGES ARE

1. ALL CONCRETE WASHOUT FACILITIES SHALL BE

INSPECTED DAILY. DAMAGED OR LEAKING

FACILITATES SHALL BE DEACTIVATED AND

A STABILIZED AREA SUCH AS A GRASS

REMOVED WHEN 75% OF THE STORAGE

REPAIRED OR REPLACED IMMEDIATELY. EXCESS

RAINWATER THAT HAS ACCUMULATED OVER

HARDENED CONCRETE SHALL BE PUMPED TO

ACCUMULATED HARDENED MATERIAL SHALL BE

CAPACITY OF THE STRUCTURE IS FILLED. ANY

EXCESS WASH WATER SHALL BE PUMPED INTO

TAKING PLACE IN NON-DESIGNATED AREAS. 6. LOCATION(S) TO BE DETERMINED IN THE FIELD

BY THE OWNER'S REPRESENTATIVE 7. CONCRETE WASHOUTS SHALL NOT BE LOCATED WITHIN 200' OF ANY KNOWN WELL.

TYPICAL SECTION CONCRETE WASHOUT AREA SCALE: N.T.S.

— 6" MIN DEPTH

AGGREGATE ALL AROUND POLYETHYLENE

SHEETING

JTM JPR

STABILIZED CONSTRUCTION ACCESS

PER PLAN OR 50' MIN.

PROFILE

PLAN VIEW

20'

EXISTING

PAVEMEN'

WOVEN GEOTEXTILE

EXISTING GROUND

12' MIN.

Champlain Hudson Power Express





IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY, IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ACTION ACTION ACTION ACTION ACTION AND ACTION ACTION AND ACTION ACTION AND ACTION ACTION ACTION AND ACTION A



CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN

---WOOD STAKE (TYPICAL)


KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

12/16/2022

C-602

12/16/2022 FINAL EM&CP SUBMISSION DATE SUBMITTAL / REVISION DESCRIPTION

DB APP DRAWN BY: JJE DESIGNED BY: JTM APPROVED BY: JPR REV. NO.



- TIMBER MATS SHOULD BE INSTALLED IN WETLANDS AND OTHER AREAS IF NECESSARY TO PREVENT RUTTING.
- BASED ON ACTUAL SITE CONDITIONS, MULTIPLE LAYERS OF TIMBER MATS MAY BE REQUIRED. TIMBER MAT SURFACE SHOULD BE LEVEL TO PREVENT EQUIPMENT AND VEHICLES FROM
- SLIDING OFF DURING MUDDY OR ICING CONDITIONS, AND PREVENT TIMBERS FROM BREAKING. 4. SEDIMENT TRACKED ONTO TIMBER MATTING SHOULD BE REMOVED AS NECESSARY TO PREVENT SEDIMENT FROM ENTERING WETLAND DURING RAIN EVENTS. SEDIMENT SHOULD BE
- REMOVED TO A STABILIZED SOIL STOCKPILE OR OTHER APPROVED LOCATION. 5. PERIMETER EROSION AND SEDIMENT CONTROLS ARE REQUIRED TO BE INSTALLED PRIOR TO
- PLACING TIMBER MATTING. UNLESS PERMITTED FROM REMOVAL, STUMPS WITHIN THE WETLAND SHOULD REMAIN. THIS
- MAY REQUIRE ADDITIONAL TIMBERS TO BRIDGE ABOVE. 7. UPON REMOVAL OF TIMBER MATTING ALL SPLINTERED WOOD SHOULD BE REMOVED. IF
- EXPOSED SOILS ARE PRESENT STRAW MULCH SHOULD BE APPLIED.

NOTE: GEOTEXTILE FABRIC TO BE INSTALLED UNDER MATTING (TYP)


APPROXIMATE WETLAND BOUNDARY TIMBER MAT - WATER BAR (IF NECESSARY) PLAN VIEW 4' 12" SECTION A-A' APPROXIMATE WETLAND -EXISTING GRADE - TRANSITION TO TIMBER MATS AS NECESSARY

1. TIMBER MATS SHOULD BE INSTALLED IN WETLANDS AND OTHER AREAS IF NECESSARY TO PREVENT RUTTING.

SECTION B-B'

- BASED ON ACTUAL SITE CONDITIONS, MULTIPLE LAYERS OF TIMBER MATS MAY BE REQUIRED. TIMBER MAT SURFACE SHOULD BE LEVEL TO PREVENT EQUIPMENT AND VEHICLES FROM SLIDING OFF DURING MUDDY OR ICING CONDITIONS, AND PREVENT TIMBERS FROM BREAKING.
- 4. SEDIMENT TRACKED ONTO TIMBER MATTING SHOULD BE REMOVED AS NECESSARY TO PREVENT SEDIMENT FROM ENTERING WETLAND DURING RAIN EVENTS. SEDIMENT SHOULD BE REMOVED TO A STABILIZED SOIL STOCKPILE OR OTHER APPROVED LOCATION.
- 5. PERIMETER EROSION AND SEDIMENT CONTROLS ARE REQUIRED TO BE INSTALLED PRIOR TO PLACING TIMBER MATTING.
- UNLESS PERMITTED FROM REMOVAL, STUMPS WITHIN THE WETLAND SHOULD REMAIN. THIS MAY REQUIRE ADDITIONAL TIMBERS TO BRIDGE ABOVE.
- 7. UPON REMOVAL OF TIMBER MATTING ALL SPLINTERED WOOD SHOULD BE REMOVED. IF EXPOSED SOILS ARE PRESENT STRAW MULCH SHOULD BE APPLIED.

NOTE: GEOTEXTILE FABRIC TO BE INSTALLED UNDER MATTING (TYP)



TIMBER MAT SECTIONS USED FOR SUPPORTS IN CHANNEL TIMBER MATS 4% MAXIMUM 4% MAXIMUM GEOTEXTILE FABRIC (MIRAFIT EXISTING GRADE 500X OR APPROVED EQUAL) -MAX -DIVERSION SWALE OR WATERBAR ADDITIONAL MATS FOR STREAM BANK PROTECTION AS NEEDED-SECTION A-A'

NOTES:

- 1. IN-STREAM EXCAVATION SHOULD BE COMPLETED IN ACCORDANCE WITH "TEMPORARY ACCESS WATERWAY CROSSING" ON PAGE 2.32 OF THE 2016 NYSDEC STANDARDS AND SPECIFICATIONS FOR EROSION AND SEDIMENT CONTROL (OR NEWEST VERSION) AND THE CERTIFICATE.
- THE CONSTRUCTION OF ANY CROSSING SHOULD NOT CAUSE A SIGNIFICANT WATER LEVEL DIFFERENCE BETWEEN THE UPSTREAM AND DOWNSTREAM WATER SURFACE ELEVATIONS. IN-STREAM WORK WILL BE PROHIBITED WITHIN COLD WATER TROUT FISHERIES FROM OCTOBER 1 TO MAY 31.
- 3. ALL FILL MATERIALS ASSOCIATED WITH THE ROADWAY APPROACH SHOULD BE LIMITED TO A MAXIMUM HEIGHT OF 2 FEET ABOVE THE EXISTING FLOOD PLAIN ELEVATION.
- 4. A WATER DIVERTING STRUCTURE SUCH AS A SWALE OR WATER BAR SHOULD BE CONSTRUCTED (ACROSS THE ROADWAY ON BOTH ROADWAY APPROACHES) 50 FEET (MAXIMUM) ON EITHER SIDE OF THE WATERWAY CROSSING. THIS WILL PREVENT ROADWAY SURFACE RUNOFF FROM DIRECTLY ENTERING THE WATERWAY. THE 50 FEET MEASURED IS MEASURED FROM THE TOP OF THE WATERWAY BANK. IF THE ROADWAY APPROACH IS CONSTRUCTED WITH A REVERSE GRADE AWAY FROM THE WATERWAY, A SEPARATE DIVERTING STRUCTURE IS NOT REQUIRED.
- 5. ALL CROSSINGS SHOULD HAVE ONE TRAFFIC LANE. THE MINIMUM WIDTH SHOULD BE 12 FEET WITH A MAXIMUM WIDTH OF 20 FEET. 6. ANCHORS: TIMBER MATS SHOULD BE SECURELY ANCHORED AT ONLY ONE END, USING STEEL CABLE OR CHAIN. ANCHORING AT ONLY ONE END WILL PREVENT CHANNEL OBSTRUCTION IN THE EVENT THAT FLOODWATERS FLOAT THE BRIDGE. ACCEPTABLE ANCHORS ARE LARGE TREES, LARGE BOULDERS, OR DRIVEN STEEL ANCHORS. ANCHORING SHOULD BE SUFFICIENT TO PREVENT THE TIMBER MATS

FROM FLOATING DOWNSTREAM AND POSSIBLY CAUSING AN

OBSTRUCTION TO THE FLOW.

TIMBER MATTING SCALE: N.T.S.







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ACTION ACTION ACTION ACTION ACTION AND ACTION ACTION AND ACTION ACTION AND ACTION ACTION ACTION AND ACTION A


JTM JPR 12/16/2022 FINAL EM&CP SUBMISSION DB APP DRAWN BY: JJE DESIGNED BY: JTM APPROVED BY: JPR REV. NO. DATE SUBMITTAL / REVISION DESCRIPTION


CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN WETLAND CROSSING DETAILS


KIEWIT PROJECT NO. 21162 CHA PROJECT NO. DRAWING NO.

C-611

AS NOTED DATE 12/16/2022








DUCTBANK IN ROADWAY


1. SLOPING, BENCHING, OR SHORING SHALL BE IN ACCORDANCE WITH OSHA EXCAVATION STANDARDS, 29 CFR PART 1926, SUBPART P. AT LOCATIONS WHERE THE TRENCH IS NOT SHORED, SLOPING AND/OR BENCHING WILL DEPEND ON TYPE OF SOILS ENCOUNTERED ON SITE. SLOPE FROM EDGE OF ROADWAY TO BOTTOM OF EXCAVATIONS MAY BE FLATTER THAN 2:1 (H: V) FOR AASHTO HS-20 LOADING. THE CONTRACTOR SHALL BE

2. SEE DETAIL 4 ON DETAIL SHEET C-631 FOR PAVEMENT TRANSITION DETAIL.

4. SEE PLAN AND PROFILE SHEETS FOR CONDUIT € TO € AND DUCTBANK SIZE TRENCH WIDTH (NOTE ABOVE PROFILE VIEW).

1 TYPICAL TRENCHING DETAILS
NOT TO SCALE











IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED	
PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT	
OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN	
ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS	
ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE	
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT	
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY	
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A	
SPECIFIC DESCRIPTION OF THE ALTERATION.	

	CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN TRENCHING DETAILS

DB APP DRAWN BY: JJE DESIGNED BY: JTM APPROVED BY: JPR REV. NO.


JTM JPR


12/16/2022 FINAL EM&CP SUBMISSION

DATE SUBMITTAL / REVISION DESCRIPTION


KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

C-621






EXISTING, MINOR REFURBISHMENT



EXISTING, MAJOR REFURBISHMENT









IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY
ARE ACTING UNDER THE DIRECTION OF A LICENSED
PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT
OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN
ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS
ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMEN
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A
SPECIFIC DESCRIPTION OF THE ALTERATION.

	CHAMPLAIN HUDSON POWER EXPRESS
	SEGMENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN
	TYPICAL ACCECC DOAD CDOCC CECTIONIC
	TYPICAL ACCESS ROAD CROSS SECTIONS

DB APP DRAWN BY: JJE DESIGNED BY: JTM APPROVED BY: JPR REV. NO.


JTM JPR

12/16/2022 FINAL EM&CP SUBMISSION


DATE SUBMITTAL / REVISION DESCRIPTION

KIEWIT PROJECT NO.
21162
CHA PROJECT NO.
066076
DRAWING NO.

C-622
AS NOTED DATE 12/16/



TYPE 4 REFURBISH ACCESS NEXT TO RAIL. BUILD TEMP ACCESS AT TOE OF SLOPE



TYPE 5 BUILD TEMP ACCESS AT TOE OF SLOPE







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED	
OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN	
ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE	
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A	
SPECIFIC DESCRIPTION OF THE ALTERATION.	
	ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A

					_
					ceil S
0	12/16/2022	FINAL EM&CP SUBMISSION	JTM	JPR	
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DF

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN TYPICAL ACCESS ROAD CROSS SECTIONS

KIEWIT PROJECT NO. CHA PROJECT NO. DRAWING NO. C-623

DRAWN BY: JJE DESIGNED BY: JTM APPROVED BY: JPR REV. NO.

1. ABOVE SECTION IS THE MINIMUM FOR INSTALLATION. MATCH EXISTING SECTION IF EXISTING THICKNESS IS GREATER

ALL MATERIALS TO MEET NYSDOT STANDARD SPECIFICATIONS.

APPLY STRAIGHT TACK COAT BETWEEN PAVEMENT SECTIONS NYSDOT ITEM NO.407.0103 4. PRIVATE COMMERCIAL DRIVEWAYS TO UTILIZE COMMERCIAL DRIVEWAY SPECIFICATIONS AS SHOWN ON THE NYSDOT STANDARD SHEETS.

ASPHALT CONCRETE PAVEMENT DETAIL (PRIVATE DRIVEWAY) SCALE: N.T.S.

2" ASPHALT CONCRETE TOP COURSE (NYSDOT ITEM NO. 404.096201) -2-1/2" ASPHALT CONCRETE BINDER COURSE (NYSDOT ITEM NO. 404.198901) -3" ASPHALT CONCRETE BASE COURSE (NYSDOT ITEM NO. 404.378901) -12" SUBBASE MATERIAL, MATCH EXISTING THICKNESS NYSDOT (ITEM NO. 304.12) COMPACTED SUBGRADE

1. ABOVE SECTION IS THE MINIMUM FOR INSTALLATION. MATCH EXISTING SECTION IF EXISTING THICKNESS IS GREATER

2. ALL MATERIALS TO MEET NYSDOT STANDARD SPECIFICATIONS 3. APPLY STRAIGHT TACK COAT TO BETWEEN PAVEMENT SECTIONS NYSDOT ITEM NO.407.0103


ASPHALT CONCRETE PAVEMENT (WITHIN COUNTY OR TOWN ROADWAYS)

SCALE: N.T.S.

COLD MILL EXISTING PAVEMENT TOP COURSE, TACK COAT AND INSTALL NEW TOP COURSE -- SAW CUT FULL DEPTH TOP COURSE PER PAVEMENT DETAIL ___EXISTING PAVEMENT EXISTING SUBBASE _|||_|| COLD MILL EXISTING PAVEMENT 24" MIN. BEYOND THE TRENCH WALL

1. ALL MATERIALS TO MEET NYSDOT STANDARD SPECIFICATIONS

3 PAVEMENT TRANSITION DETAIL



1. ALL MATERIALS TO MEET NYSDOT STANDARD SPECIFICATIONS

4 WING WEDGE CURB DETAIL SCALE: N.T.S.

-SLOPE AS INDICATED ON PLAN -LAYER THICKNESS PER TABLE - COMPACTED SUBGRADE - STABILIZATION FABRIC OR GEOGRID

TEMPORARY ACCESS ROAD SECTION BX1200 RD580I GEOTEXTILE CBR 180N GEOTEXTILE GEOGRID² 24 INCH RIP RAP³ 24 INCH RIP RAP + 4 INCH 0.5 --AGGREGATE + 6 INCH AGGREGATE⁴ 1.0 20 INCH AGGREGATE 12 INCH AGGREGATE 9 INCH AGGREGATE 1.5 15 INCH AGGREGATE 9 INCH AGGREGATE --2.0 12 INCH AGGREGATE 6 INCH AGGREGATE ___ 3.0+ 6 INCH AGGREGATE 9 INCH AGGREGATE ___

'ESTIMATE CBR IN THE FIELD USING A DYNAMIC CONE PENETROMETER.


² SEPARATOR GEOTEXTILE FABRIC SUCH AS MIRAFI 140N SHALL BE INCLUDED BENEATH GEOGRID LAYER ON COHESIVE SUBGRADE

³ RIP RAP TO BE NYSDOT LIGHT STONE FILL

⁴ A LAYER OF #57 STONE MAY BE REQUIRED ON TOP OF GEOTEXTILE TO PREVENT DAMAGING OR PUNCHING OF THE FABRIC. ⁵ GEOGRID AND GEOTEXTILES SHALL BE INSTALLED PER MANUFACTURERS SPECIFICATION INCLUDING OVERLAP AND EDGE DETAILS


ACCESS ROAD SECTIONS PER KIEWIT GEOTECHNICAL

TEMPORARY ACCESS ROAD SCALE: N.T.S.




NOTE: CURB JOINTS TO BE POINTED WITH

GRANITE CURB DETAIL




NOTE: SEE ADJACENT GRANITE CURB DETAIL

GRANITE CURB TERMINATION DETAIL



GRAVEL PAVEMENT



NOTES:

1. WHERE IDENTIFIED ON PLANS, CULVERT REPLACEMENTS AND/OR REPAIR TO BE COMPLETED IN ACCORDANCE WITH NYSDOT STANDARD SHEETS (NYSDOT STANDARD SHEET GROUP 603 CULVERTS AND STORM DRAINS AND NYSDOT BRIDGE DETAIL SHEETS BD-CB1 THRU BD-CB13)

CULVERT REPLACEMENT SCALE: N.T.S.

12/16/2022 FINAL EM&CP SUBMISSION

DATE SUBMITTAL / REVISION DESCRIPTION







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THE ARE ACTING UNDER THE DIRECTION OF A LICENSED THE DIRECTION OF A LICENSED THE DIRECT LANDSCAPE ARE ARE ARE ARE ARE ARE ARE ARE ARE AR
PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHIT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF
ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCA
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUM AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED E
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND SPECIFIC DESCRIPTION OF THE ALTERATION.

N POWER EXPRESS) WHITEHALL TO FORT ANN DRATION DETAILS


DB APP DRAWN BY: JJE DESIGNED BY: JTM APPROVED BY: JPR REV. NO.


JTM JPR


KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

C-631

AS NOTED DATE 12/16/2022







Power Express



CP RAIL CANADIAN MAINLINE MP: 76.44



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY
ARE ACTING UNDER THE DIRECTION OF A LICENSED
PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT
OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN
ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS
ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A
SPECIFIC DESCRIPTION OF THE ALTERATION.
l l

0	12/16/2022	FINAL EM&CP SUBMISSION	MCS	JEO	CHAMPLAIN HUDSON POWER EX SEGMENT 3 (PACKAGE 1C) WHITEHALL TO RAIL CROSS SECTION DETAILS HD
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	SCALE SCALE
140.	DAIL	SUBMITTAL/ REVISION DESCRIPTION			DRAWN BY: JAS DESIGNED BY: JAS APPROVED BY: JEO REV. NO.

HUDSON POWER EXPRESS CKAGE 1C) WHITEHALL TO FORT ANN ROSS SECTION DETAILS HDD 3

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. DRAWING NO.

BORING LOG STRIP LEGEND

2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

Legend

Bedrock

Boulder Fat CLAY

SILTY Fat CLAY

Lean CLAY

SILTY CLAY

Concrete

Fill CLAYEY GRAVEL

SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL Poorly Graded Gravel with CLAY

Poorly Graded GRAVEL with SILT

Well Graded GRAVEL

Well Graded GRAVEL with CLAY

Well Graded GRAVEL with SILT

ORGANIC Fat CLAY

ORGANIC Lean CLAY

ORGANIC SOIL

PEAT

Rock

Sandstone

CLAYEY SAND

SILT, CLAYEY SAND

Shale

SILTY SAND

Poorly Graded SAND

Poorly Graded SAND with CLAY

Poorly Graded SAND with SILT

Well graded SAND

Well Graded SAND with CLAY Well Graded SAND with SILT

Topsoil

Gravel or Conglomerate 1

Subgraywacke

Schist

Schist

Gneiss

Gneiss

Granite 1

Void

Water

Undefined

Water Table during drilling

Water Table after drilling

nterbedded Sandstone and Shale

Recovery %/RQD % = 95%/90% - 11000psi =UCS

Blow Counts per 6" = 10-10-10

ASPHALT Bedrock

Boulder

CH

CH-MH

CL-ML CONCRETE

Fill

GC-GM

GP-GC

GP-GM

OL/OH

Rock

Sandstone

2C-2M

SHALE

SILTSTONE

SP

SP-SC

SP-SM

SW

SM-SC

SW-SM

Topsoil

USGS 601

USGS 654

USGS 670

USGS 702

USGS 705

USGS 705

USGS 708

USGS 708

USGS 718

Void


Weathered Rock

▼ Water Table


□ Delayed Water Table

C-641

AS NOTED DATE 12/16/2022



120



Power Express

6.6'

15.0′



HDD #3 CONDUIT 2 EXIT PIT CUT SECTION; STA. 15093+16

FO = 223.3

APPROXIMATE EXISTING GROUND -

220

FO Elev. = UNKNOWN

0.2%

---- APPROXIMATE

HDD EXIT

EXIT PIT

_ PROPOSED 5'X10'X5'

1V 1.5H

APPROXIMATE DEPTH

CP RAIL CANADIAN MAINLINE MP: 76.44

AT INV: 75.6'-



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

0	12/16/2022	FINAL EM&CP SUBMISSION	MCS	JEO	CHAMPLAIN HUDSON POWER EX SEGMENT 3 (PACKAGE 1C) WHITEHALL TO RAIL CROSS SECTION DETAILS HD
No.	DATE	CURNITAL / DEVICION DESCRIPTION	DB	ADD	SCALE
INO.	DAIE	SUBMITTAL / REVISION DESCRIPTION	םט	APP	DRAWN BY: JAS DESIGNED BY: JAS APPROVED BY: JEO REV. NO.

CHAMPLAIN HUDSON POWER EXPRESS EGMENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN RAIL CROSS SECTION DETAILS HDD 3

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

BORING LOG STRIP LEGEND

2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

Legend

Bedrock

Boulder

Fat CLAY

SILTY Fat CLAY

Lean CLAY

SILTY CLAY

Concrete

Fill CLAYEY GRAVEL

SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL

Poorly Graded Gravel with CLAY

Poorly Graded GRAVEL with SILT

Well Graded GRAVEL

Well Graded GRAVEL with CLAY

Well Graded GRAVEL with SILT

DRGANIC Fat CLAY

ORGANIC Lean CLAY

ORGANIC SOIL

PEAT

Rock

Sandstone

CLAYEY SAND

SILT, CLAYEY SAND

Shale

Siltstone

SILTY SAND

Poorly Graded SAND

Poorly Graded SAND with CLAY

Poorly Graded SAND with SILT

Well graded SAND

Well Graded SAND with CLAY

Well Graded SAND with SILT

Gravel or Conglomerate 1

Subgraywacke

Schist

Schist

Gneiss

Gneiss

Granite 1

Void

Water

Undefined

Water Table during drilling

Water Table after drilling

nterbedded Sandstone and Shale

Recovery %/RQD % = 95%/90% — 11000psi =UCS

Blow Counts per 6" = 10-10-10

ASPHALT Bedrock

Boulder

CH

CH-MH

CL-ML CONCRETE

Fill

GC-GM

GP-GC

GP-GM

GW-GM

OL/OH

Rock

Sandstone

2C-2M

SHALE

SILTSTONE

SP

SP-SC

SP-SM

SW

SM-SC

SM-SM

Topsoil

USGS 601 USGS 654

USGS 670

USGS 702

USGS 705

USGS 705

USGS 708

USGS 708 USGS 718


Void

Weathered Rock


Delayed Water Table

▼ Water Table

C-641.1



HDD #4 CONDUIT 1 EXIT PIT CUT SECTION; STA. 15145+25 CP RAIL CANADIAN MAINLINE MP: 75.46



HDD #4 CONDUIT 1 ENTRY PIT CUT SECTION; STA. 15138+89
CP RAIL CANADIAN MAINLINE MP: 75.58







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY
ARE ACTING UNDER THE DIRECTION OF A LICENSED
PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT
OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN
ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS
ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A
SPECIFIC DESCRIPTION OF THE ALTERATION.

	CHAMPLAIN HUDSON POWER EXPRESS
	SEGMENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN
	RAIL CROSS SECTION DETAILS HDD 4

MCS JEO

12/16/2022 FINAL EM&CP SUBMISSION

DATE SUBMITTAL / REVISION DESCRIPTION

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

AS NOTED DATE

Gneiss

Gneiss

Granite 1

Void

Water

Undefined

Water Table during drilling

Water Table after drilling

PEAT Rock Rock Sandstone Sandstone CLAYEY SAND SILT, CLAYEY SAND SC-SMSHALE Shale SILTSTONE Siltstone SILTY SAND Poorly Graded SAND SP-SC Poorly Graded SAND with CLAY SP-SM Poorly Graded SAND with SILT SW Well graded SAND SW-SC Well Graded SAND with CLAY Well Graded SAND with SILT SW-SMTopsoil Gravel or Conglomerate 1 USGS 601 USGS 654 Subgraywacke Interbedded Sandstone and Shale USGS 702 USGS 705 Schist

USGS 708

USGS 708

USGS 718

Void

Delayed Water Table

▼ Water Table

Scale in feet

DB APP DRAWN BY: ES DESIGNED BY: ES APPROVED BY: JEO REV. NO.

BORING LOG STRIP LEGEND

2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

Legend

Bedrock

Boulder

Fat CLAY

SILTY Fat CLAY

Lean CLAY SILTY CLAY

Concrete

Fill

CLAYEY GRAVEL

SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL Poorly Graded Gravel with CLAY

Poorly Graded GRAVEL with SILT

Well Graded GRAVEL

Well Graded GRAVEL with CLAY

Well Graded GRAVEL with SILT

Limestone

ORGANIC Fat CLAY

ORGANIC Lean CLAY

ORGANIC SOIL

Recovery %/RQD % = 95%/90% 11000psi =UCS

Blow Counts per 6" = 10-10-10

ASPHALT

Bedrock

Boulder

CH-MH

CL-ML CONCRETE

GC-GM


GP-GC GP-GM

GW


GW-GM

OL/OH

C-642



HDD #4 CONDUIT 2 EXIT PIT CUT SECTION; STA. 15144+81 CP RAIL CANADIAN MAINLINE MP: 75.47



HDD #4 CONDUIT 2 ENTRY PIT CUT SECTION; STA. 15138+64
CP RAIL CANADIAN MAINLINE MP: 75.58

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN RAIL CROSS SECTION DETAILS HDD 4

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. DRAWING NO.

BORING LOG STRIP LEGEND

2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

Legend

Bedrock

Boulder Fat CLAY

SILTY Fat CLAY

Lean CLAY

SILTY CLAY

Concrete

Fill

CLAYEY GRAVEL

SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL Poorly Graded Gravel with CLAY

Poorly Graded GRAVEL with SILT

Well Graded GRAVEL

Well Graded GRAVEL with CLAY

Well Graded GRAVEL with SILT

Limestone

ORGANIC Fat CLAY

ORGANIC Lean CLAY

ORGANIC SOIL

PEAT

Rock

Sandstone

CLAYEY SAND

SILT, CLAYEY SAND

Shale

Siltstone

SILTY SAND Poorly Graded SAND

Poorly Graded SAND with CLAY

Poorly Graded SAND with SILT

Well graded SAND

Well Graded SAND with CLAY Well Graded SAND with SILT

Gravel or Conglomerate 1

Subgraywacke Interbedded Sandstone and Shale

Schist

Gneiss

Gneiss

Granite 1 Void Water

Undefined

Water Table during drilling

Water Table after drilling

AS NOTED DATE

Recovery %/RQD % = 95%/90% 11000psi =UCS

Blow Counts per 6" = 10-10-10

ASPHALT

Bedrock

Boulder

CH-MH

CL-ML CONCRETE

GC-GM

GP-GC GP-GM

GW

GW-GM

OL/OH

Rock

Sandstone

SC-SM

SHALE

SILTSTONE

SP-SC

SP-SM

SW

SW-SC

SW-SM

USGS 601 USGS 654

USGS 702 USGS 705 USGS 705

USGS 708

USGS 708

USGS 718

Delayed Water Table

▼ Water Table

C-642.1

12/16/2022


Power Express





IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY
ARE ACTING UNDER THE DIRECTION OF A LICENSED
PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITEC
OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN
ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS
ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMEN
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A
SPECIFIC DESCRIPTION OF THE ALTERATION.

					SI
0	12/16/2022	FINAL EM&CP SUBMISSION	MCS	JEO	
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRA



WORKZONE OFFSET = 28.7 WORKZONE Elev. = 120.3BORING K-114.6 LOW OFFSET = 27.1ELEVATION: 121.8 LOW Elev. = 120.7 130 CP RAIL OFFSET = 13.6 BORING B114.4-1 ELEVATION: 123.0 CP RAIL Elev. = 123.6 CP RAIL OFFSET = 0.0_ CP RAIL Elev. = 123.7 EXISTING GROUND — PROPOSED
ACCESS ROAD
120 120 T OFFSET FO = 20.5FO Elev. = UNKNOWN 2-1-1-1 0.1% 2-4-1-2 F0 F0 2-3-5 – APPROXIMATE HDD ENTRY 4-5-7 PROPOSED 5'X10'X5' 2-3-3-6 1-2-4-6

1 HDD #4A CONDUIT 1 ENTRY PIT CUT SECTION; STA. 15164+48
CP RAIL CANADIAN MAINLINE MP: 75.09

L APPROXIMATE DEPTH AT INV: 89.9'

BORING LOG STRIP LEGEND

B101

B101

Recovery %/RQD % = 95%/90%

2D strip logs shown at 10x exaggeration
3D strip logs have no exaggeration

Legend

		Legeno
	ASPHALT	Asphalt
	Bedrock	Bedrock
🔷 .	Boulder	Boulder
	СН	Fat CLAY
/ // //	CH-MH	SILTY Fat CLAY
777	CL	Lean CLAY
711	CL-ML	SILTY CLAY
/ /	CONCRETE	Concrete
	Fill	Fill
52.7.3	GC	CLAYEY GRAVEL
	GC-GM	SILTY CLAYEY GRAVEL
	GM	
		SILTY GRAVEL Poorly Graded GRAVEL
50	GP GP	
O C	GP-GC	Poorly Graded Gravel with CLAY
	GP-GM	Poorly Graded GRAVEL with SILT
	GW	Well Graded GRAVEL
	GW-GC	Well Graded GRAVEL with CLAY
	GW-GM	Well Graded GRAVEL with SILT
	Limestone	Limestone
	MH	Elastic SILT
	ML	SILT
	DΗ	ORGANIC Fat CLAY
	DL	ORGANIC Lean CLAY
888	OL/OH	ORGANIC SOIL
\\\/	PT	PEAT
	Rock	Rock
	Sandstone	Sandstone
· /: :	SC	CLAYEY SAND
· :	SC-SM	SILT, CLAYEY SAND
* 71*	SHALE	Shale
\times	SILTSTONE	Siltstone
	SM	SILTY SAND
	SP	Poorly Graded SAND
,.	SP-SC	Poorly Graded SAND with CLAY
	SP-SM	Poorly Graded SAND with SILT
	SW	Well graded SAND
, 4	SW-SC	Well Graded SAND with CLAY
- /	SW-SM	Well Graded SAND with SILT
	Topsoil	Topsoil
XX	USGS 601	Gravel or Conglomerate 1
	USGS 654	Subgraywacke
	USGS 670	Interbedded Sandstone and Shale
7777	USGS 702	Quartzite
	USGS 705	Schist
	USGS 705	Schist
	USGS 708	Gneiss
	USGS 708	Gneiss
- \ \	USGS 718	Granite 1
	Void	Void
	Water	Water
$\parallel \cdot - \cdot \cdot - \mid$	Weathered Rock	Undefined
▼	Water Table Delayed Water	Water Table during drilling







	ı
IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY	
ARE ACTING UNDER THE DIRECTION OF A LICENSED	ı
PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT	ı
OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN	ı
ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS	ı
ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE	ı
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT	ı
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY	ı
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A	ı
SPECIFIC DESCRIPTION OF THE ALTERATION.	

	CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN RAIL CROSS SECTION DETAILS HDD 4A

10 Scale in feet


KIEWIT PROJECT NO.
21162
CHA PROJECT NO.
066076
DRAWING NO.

C-643
AS NOTED DATE 12/16


12/16/2022 FINAL EM&CP SUBMISSION MCS JEO

DATE SUBMITTAL / REVISION DESCRIPTION

DB APP DRAWN BY: ES DESIGNED BY: ES APPROVED BY: JEO REV. NO.



2 HDD #4A CONDUIT 2 EXIT PIT CUT SECTION; STA. 15170+43 CP RAIL CANADIAN MAINLINE MP: 74.99



HDD #4A CONDUIT 2 ENTRY PIT CUT SECTION; STA. 15163+19
CP RAIL CANADIAN MAINLINE MP: 75.12

 □ Delayed Water Table Water Table after drilling CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN RAIL CROSS SECTION DETAILS HDD 4A

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. DRAWING NO.

BORING LOG STRIP LEGEND

2D strip logs shown at 10x exaggeration

3D strip logs have no exaggeration

Legend

Bedrock

Boulder

Fat CLAY

SILTY Fat CLAY

Lean CLAY

SILTY CLAY

Concrete

Fill

CLAYEY GRAVEL

SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL Poorly Graded Gravel with CLAY

Poorly Graded GRAVEL with SILT Well Graded GRAVEL

Well Graded GRAVEL with CLAY

Well Graded GRAVEL with SILT

ORGANIC Fat CLAY ORGANIC Lean CLAY

ORGANIC SOIL

PEAT

Rock

Sandstone

CLAYEY SAND

SILT, CLAYEY SAND

SILTY SAND

Poorly Graded SAND

Poorly Graded SAND with CLAY

Poorly Graded SAND with SILT

Well graded SAND

Well Graded SAND with CLAY Well Graded SAND with SILT

Gravel or Conglomerate 1

Subgraywacke

Schist

Schist

Gneiss

Gneiss

Granite 1 Void

Water

Undefined

Water Table during drilling

AS NOTED DATE

nterbedded Sandstone and Shale

Recovery %/RQD % = 95%/90% 11000psi =UCS

Blow Counts per 6" = 10-10-10

ASPHALT

Bedrock

Boulder

CH

CH-MH

CL-ML CONCRETE

Fill

GC-GM

GP-GC GP-GM

OL/OH

Rock

Sandstone

2C-2M

SHALE

SILTSTONE

SP-SC

SP-SM

SW

SM-SC

SW-SMTopsoil

USGS 601

USGS 654

USGS 702

USGS 705

USGS 705

USGS 708

USGS 708

USGS 718

Void

Weathered Rock

▼ Water Table

C-643.1


Power Express






IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY
ARE ACTING UNDER THE DIRECTION OF A LICENSED
PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITEC
OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN
ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS
ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMEN
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A
SPECIFIC DESCRIPTION OF THE ALTERATION.

					DEGINENT 3 (LACIMOL TO) WITH LITALL TO
					RAIL CROSS SECTION DETAILS HDI
					IVAIL CINOSS SECTION DETAILS TIDI
0	12/16/2022	FINAL EM&CP SUBMISSION	MCS	JEO	
No.	DATE	CURNITAL / DEVICION DESCRIPTION	DB	ADD	SCALE
INO.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: ES DESIGNED BY: ES APPROVED BY: JEO REV. NO.



2 HDD #5 CONDUIT 1 EXIT PIT CUT SECTION; STA. 15182+35
CP RAIL CANADIAN MAINLINE MP: 74.76



1 HDD #5 CONDUIT 1 ENTRY PIT CUT SECTION; STA. 15175+25
CP RAIL CANADIAN MAINLINE MP: 74.89

Blow Counts per 6" = 10-10-10

Recovery %/RQD % = 95%/90%

2D strip logs shown at 10x exaggeration
3D strip logs have no exaggeration

		Legend
	ASPHALT	Asphalt
	Bedrock	Bedrock
🔷 .	Boulder	Boulder
	СН	Fat CLAY
////	CH-MH	SILTY Fat CLAY
////	CL	Lean CLAY
////	CL-ML	SILTY CLAY
/ /1 1	CONCRETE	Concrete
\times	Fill	Fill
7573	GC	CLAYEY GRAVEL
	GC-GM	SILTY CLAYEY GRAVEL
	GM	SILTY GRAVEL
7500	GP	Poorly Graded GRAVEL
	GP-GC	Poorly Graded Gravel with CLAY
	GP-GM	Poorly Graded GRAVEL with SILT
	GW	•
		Well Graded GRAVEL
	GW-GC	Well Graded GRAVEL with CLAY
	GW-GM	Well Graded GRAVEL with SILT
	Limestone	Limestone
	MH	Elastic SILT
	ML	SILT
<i>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</i>	ΩН	ORGANIC Fat CLAY
2	OL.	ORGANIC Lean CLAY
<i>(((</i>	OL/OH	ORGANIC SOIL
<u>\(\frac{\frac{7}{2}}{2}\)</u>	PT	PEAT
	Rock	Rock
	Sandstone	Sandstone
· /. ·/	SC	CLAYEY SAND
	2C-2M	SILT, CLAYEY SAND
	SHALE	Shale
\times	SILTSTONE	Siltstone
	SM	SILTY SAND
	SP	Poorly Graded SAND
-	SP-SC	Poorly Graded SAND with CLAY
	SP-SM	Poorly Graded SAND with SILT
4	WZ	Well graded SAND
<u> </u>	SM-SC	Well Graded SAND with CLAY
	SW-SM	Well Graded SAND with SILT
$\times\!\!\times\!\!\times$	Topsoil	Topsoil
(* *)	USGS 601	Gravel or Conglomerate 1
	USGS 654	Subgraywacke
	USGS 670	Interbedded Sandstone and Shale
	USGS 702	Quartzite
1111	USGS 705	Schist
	USGS 705	Schist
	USGS 708	Gneiss
11/1	USGS 708	Gneiss
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	USGS 718	Granite 1
	Vold	Void
	Water	Water
	w a cei	
	Wenthanad Pack	Hadafinad
<u> </u>	Weathered Rock Water Table	Undefined Water Table during drilling







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY
ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT
OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN
ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS
ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

12/16/2022 FINAL EM&CP SUBMISSION

DATE SUBMITTAL / REVISION DESCRIPTION


		CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN	
		RAIL CROSS SECTION DETAILS HDD 5	
			l

KIEWIT PROJECT NO.
21162
CHA PROJECT NO.
066076
DRAWING NO.

C-644


MCS JEO

DB APP DRAWN BY: CJL DESIGNED BY: CJL APPROVED BY: JEO REV. NO. C



HDD #5 CONDUIT 2 EXIT PIT CUT SECTION; STA. 15182+25

CP RAIL CANADIAN MAINLINE MP: 74.76



1 HDD #5 CONDUIT 2 ENTRY PIT CUT SECTION; STA. 15174+79
CP RAIL CANADIAN MAINLINE MP: 74.89

USGS 708
USGS 718
Void
Water

USGS 718

Void

Water

Weathered Rock

Delayed Water
Table

CHAMPLAIN HUDSON POWER EXPRESS
SEGMENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN
RAIL CROSS SECTION DETAILS HDD 5

KIEWIT PROJECT NO.

21162
CHA PROJECT NO.

066076
DRAWING NO.

BORING LOG STRIP LEGEND

2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

Legend

Bedrock

Boulder

Fat CLAY

SILTY Fat CLAY

Lean CLAY

SILTY CLAY

Concrete

Fill CLAYEY GRAVEL

SILTY CLAYEY GRAVEL

SILTY GRAVEL

Poorly Graded GRAVEL

Poorly Graded Gravel with CLAY

Poorly Graded GRAVEL with SILT

Well Graded GRAVEL

Well Graded GRAVEL with CLAY

Well Graded GRAVEL with SILT

ORGANIC Fat CLAY

ORGANIC Lean CLAY

ORGANIC SOIL

PEAT

Rock

Sandstone

CLAYEY SAND SILT, CLAYEY SAND

Shale

SILTY SAND

Poorly Graded SAND

Poorly Graded SAND with CLAY

Poorly Graded SAND with SILT

Well graded SAND

Well Graded SAND with CLAY

Well Graded SAND with SILT

Gravel or Conglomerate 1

Subgraywacke
nterbedded Sandstone and Shale

Schist

Schist

Gneiss

Gneiss

Granite 1

Void

Water

Undefined

Water Table during drilling

Recovery %/RQD % = 95%/90% 11000psi =UCS

Blow Counts per 6" = 10-10-10

ASPHALT

Bedrock

Boulder

CH

CH-MH

CL-ML CONCRETE

Fill

GC-GM

GP-GC

GP-GM

GW-GM

OL/OH

Rock

Sandstone

SC-SM SHALE

SILTSTONE

SP-SC

SP-SM

SW

SM-SC

SW-SM Topsoil

USGS 601 USGS 654

USGS 702

USGS 705

USGS 705

USGS 708

C-644.1

CHPE


Champlain Hudson
Power Express






IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THE
ARE ACTING UNDER THE DIRECTION OF A LICENSED
PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITE
OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF A
ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL
ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAF
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUME
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED B
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND
SPECIFIC DESCRIPTION OF THE ALTERATION.

0	12/16/2022	FINAL EM&CP SUBMISSION	MCS	JEO	
No	DATE	SURMITTAL / PEVISION DESCRIPTION	DB	ΔPP	DDAVAAL



2 HDD #6 CONDUIT 1 EXIT PIT CUT SECTION; STA. 15231+53
CP RAIL CANADIAN MAINLINE MP: 73.83



1 HDD #6 CONDUIT 1 ENTRY PIT CUT SECTION; STA. 15217+14
CP RAIL CANADIAN MAINLINE MP: 74.10

Void

Water

Value

Va

Water Table during drilling

Water Table after drilling

KIEWIT PROJECT NO.

21162

CHA PROJECT NO.

066076

DRAWING NO.

BORING LOG STRIP LEGEND

2D strip logs shown at 10x exaggeration

3D strip logs have no exaggeration

Legend

Bedrock

Boulder

Fat CLAY
SILTY Fat CLAY

Lean CLAY

SILTY CLAY

Concrete

Fill CLAYEY GRAVEL

SILTY CLAYEY GRAVEL

SILTY GRAVEL

Poorly Graded GRAVEL

Poorly Graded Gravel with CLAY

Poorly Graded GRAVEL with SILT

Well Graded GRAVEL

Well Graded GRAVEL with CLAY

Well Graded GRAVEL with SILT

Limestone

ORGANIC Fat CLAY

ORGANIC Lean CLAY

ORGANIC SOIL

PEAT

Rock

Sandstone

CLAYEY SAND

SILT, CLAYEY SAND

Shale

SILTY SAND

Poorly Graded SAND

Poorly Graded SAND with CLAY

Poorly Graded SAND with SILT

Well graded SAND

Well Graded SAND with CLAY

Well Graded SAND with SILT

Topsoil
Gravel or Conglomerate 1

Subgraywacke
Interbedded Sandstone and Shale

Schist

Schist

Gneiss Gneiss

Granite 1

Void

Water

Undefined

Recovery %/RQD % = 95%/90% 11000psi =UCS

Blow Counts per 6" = 10-10-10

ASPHALT Bedrock

Boulder

СН

CH-MH

CL-ML

CONCRETE

Fill

GC-GM

GP-GC

GP-GM

GW-GM

OL/OH

Rock

Sandstone

2C-2M

SHALE

SILTSTONE

SP-SC

SP-SM

SW

SM-SC

SW-SM JiozaoT

USGS 601

USGS 654

USGS 702

USGS 705

USGS 705

USGS 708

USGS 708

USGS 718

C-645

CHPE

Champlain Hudson
Power Express





IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY
ARE ACTING UNDER THE DIRECTION OF A LICENSED
PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT
OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN
ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS
ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMEN
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A
SPECIFIC DESCRIPTION OF THE ALTERATION.

					SEGMENT 3 (PACKAGE 1C) WHITEHALL TO FORT ANN						
					RAIL CROSS SECTION DETAILS HDD 6						
							C				
)	12/16/2022	FINAL EM&CP SUBMISSION	MCS	JEO							
Ο.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: CJL DESIGNED BY: CJL APPROVED BY: JEO REV. NO. C	DATE					