APPENDIX C.14 CASE 10-T-0139 SITE PLANS AND CONSTRUCTION DRAWINGS ENERGY PACKAGE - CONVERTER AND SERVICE BUILDING ASTORIA HVDC CONVERTER STATION - SEGMENT 22



ASTORIA HVDC CONVERTER STATION

CONVERTER AND SERVICE BUILDING ENERGY PACKAGE

SCOPE OF WORK

THE ENERGY SCOPE OF WORK FOR THE ASTORIA CONVERTER STATION INCLUDES THE AREAS BELOW:

- 1. CONVERTER BUILDING
- 2. SERVICE BUILDING3. HVAC ROOM


ENERGY SHEET LIST						
NUMBER NAME						
EN-000.00	OVERALL SITE PLAN					
EN-001.00	ENERGY COMPLIANCE ARCHITECTURAL-1					
EN-002.00	ENERGY COMPLIANCE ARCHITECTURE-2					
EN-003.00	ENERGY COMPLIANCE ARCHITECTURE-3					
EN-004.00	ENERGY COMPLIANCE MECHANICAL-1					
EN-005.00	ENERGY COMPLIANCE MECHANICAL-2					
EN-006.00	ENERGY COMPLIANCE MECHANICAL-3					
EN-007.00	ENERGY COMPLIANCE MECHANICAL-4					
EN-008.00	ENERGY COMPLIANCE ELECTRICAL-1					

FLOOD ZONE DESIGN CERTIFICATION:


THE EXISTING PROPERTY IS IN THE SPECIAL FLOOD HAZARD AREA (SFHA), ZONE AE PER EFFECTIVE 2015 FLOOD INSURANCE RATE MAP(FIRM). THIS IS TO CONFIRM THAT THE PROPOSED INSTALLATION IS IN COMPLIANCE WITH THE REQUIREMENTS SET FORTH IN APPENDIX Q OF THE NYC BUILDING CODE.

NYC ENERGY CODE COMPLIANCE:

STATEMENT: TO THE BEST OF MY KNOWLEDGE, BELIEF AND PROFESSIONAL JUDGEMENT, THESE PLANS AND SPECIFICATIONS ARE IN COMPLIANCE WITH THE NEW YORK CITY ENERGY CONSERVATION CODE. PROPOSED WORK MEETS THE GUIDELINES AND INSTRUCTIONS OUTLINED IN THE 2020 NYC ECC CHAPTER 4.



ISSUED FOR PERMIT





370 7th Avenue SUITE 1604 New York, NY 10001



25 Mohawk Avenue Sparta, NJ 07871

CONFIDENTI

THESE DRAWINGS ARE CONFIDENTIAL IN NATURE. ANY MISUSE OR UNAUTHORIZED DISTRIBUTION OF THE DRAWINGS CONTAINED HEREIN WILL BE A VIOLATION OF THIS CONFIDENTIALITY REQUIREMENT AND SUBJECT THE VIOLATOR TO LIABILITY. REVIEW OF THESE MATERIALS BY RECEIPT SHALL CONSTITUTE ACCEPTANCE OF THESE TERMS AND THE TERMS OF ANY UNDERLYING CONFIDENTIALITY AGREEMENT WE MAY HAVE EXCLUDED IN OBTAINING THIS INFORMATION FROM A THIRD PARTY. IF THE RECIPIENT IS NOT IN AGREEMENT WITH THE OBLIGATION OF

E	FINAL SUBMISSION	RAC	ZH	12/12/2022
	INTERIM SUBMISSION	RAC	ZH	09/13/2022
RI	V DESCRIPTION	DRW BY	CHK BY	DATE





PROJECT



Astoria HVDC Converter Station


31-45 20th Avenue, Astoria, Queens NY 11105 Block #850 - Lot #310 - BIN #4624437

COVER SHEET

DATE 12/12/22
PROJECT NO 105121
DRAWING BY Author
CHECKED BY Designer
DRAWING NO

T-000.00

Autodesk Docs://CHPE Astoria/CHA-KIE-111-ZZ-M3-A-001.rvt



Project Information

Construction Site:

2020 New York City Energy Conservation Code, Appendix CA (modified 90.1-2016) Energy Code: Project Title: CHPE Astoria HVDC Converter Station Location: New York, New York

Transmission Developers Inc.

Designer/Contractor:

Kiewit

Climate Zone: Project Type: New Construction

EnergyPlus 8.1.0.009 (EPW: USA_NY_New.York-LaGuardia.AP.725030_TMY3.epw) Performance Sim. Specs:

Owner/Agent:

Additional Efficiency Package(s) Credits: 1.0 Required 1.0 Proposed High Performance HVAC, 1.0 credit

Building Area	Floor Area
1-Converter Halls (Warehouse) : Nonresidential	75900
2-Service Bldg (Office) : Nonresidential	5700

Envelope Assemblies

Assembly	Gross Area or Perimeter	Cavity R-Value	Cont. R-Value	Proposed U-Factor	Budget U- Factor₁₀
Roof 1: Insulation Entirely Above Deck, [Bidg. Use 1 - Converter Halls]	32394		35.0	0.028	0.030
Roof 2: Other Metal Building Roof, [Bldg. Use 2 - Service Bldg] (b)	1740	***	***	0.031	0.035
NORTHEAST Exterior Wall 1: Other Metal Building Wall, [Bldg. Use 1 - Converter Halls] (b)	14994			0.038	0.048
A104D: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
A104E: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	217	***	***	0.430	0.370
A104G: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
A104H: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
A104l: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
A104F: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
Exterior Wall 5: Other Metal Building Wall, [Bldg. Use 2 - Service Bldg] (b)	1901	***	***	0.038	0.048
B103: Insulated Metal, Swinging, [Bldg. Use 2 - Service Bldg]	35	***	***	0.360	0.370
B102A: Insulated Metal, Swinging, [Bldg. Use 2 - Service Bldg]	35	***	***	0.360	0.370
B101: Insulated Metal, Swinging, [Bldg. Use 2 - Service Bldg]	35			0.360	0.370
SOUTHEAST Exterior Wall 2: Other Metal Building Wall, [Bldg. Use 1 - Converter Halls] (b)	15291			0.038	0.048
A103D: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
A103E: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21		***	0.430	0.370
A102D: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
A105A: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	42	***	***	0.430	0.370
A104K: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21		***	0.430	0.370
Project Title: CHPE Astoria HVDC Converter Station				Report da	te: 12/07/

Section # & Req.ID	Plan Review	Complies?	Comments/Assumptions
[PR12] ¹	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the additional energy efficiency package options.	Complies Does Not Not Observable Not Applicable	Exception: Requirement does not apply.

efficiency package options. Additional Comments/Assumptions:

Data filename: C:\Users\acarlson\Desktop\Astoria COMcheck.cck

	Gross Area or	Cavity R-Value	Cont. R-Value	Proposed U-Factor	Budget U- Factor _{ii}
	Perimeter				
A104J: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
Exterior Wall 6: Other Metal Building Wall, [Bldg. Use 2 - Service Bldg] (b)	5345		***	0.038	0.048
B115A: Insulated Metal, Swinging, [Bldg. Use 2 - Service Bldg]	144	***	***	0.360	0.370
B108: Insulated Metal, Swinging, [Bldg. Use 2 - Service Bldg]	35	***	***	0.360	0.370
B104: Insulated Metal, Swinging, [Bldg. Use 2 - Service Bldg]	35	***		0.360	0.370
B203: Insulated Metal, Swinging, [Bldg. Use 2 - Service Bldg]	56	***	***	0.360	0.370
SOUTHWEST Exterior Wall 3: Other Metal Building Wall, [Bldg. Use 1 - Converter Halls] (b)	14994			0.038	0.048
A103G: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
A103A: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21			0.430	0.370
Exterior Wall 7: Other Metal Building Wall, [Bldg. Use 2 - Service Bldg] (b)	1901			0.038	0.048
B114: Insulated Metal, Swinging, [Bldg. Use 2 - Service Bldg]	21		***	0.360	0.370
NORTHWEST					
Exterior Wall 4: Other Metal Building Wall, [Bldg. Use 1 - Converter Halls] (b)	21319			0.038	0.048
A103B: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	132	***	***	0.430	0.370
A103C: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
A101A: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
A101B: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
A101C: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
A101D: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	132	***	***	0.430	0.370
A104A: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
A104B: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
A104C: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
A101E: Insulated Metal, Swinging, [Bldg. Use 1 - Converter Halls]	21	***	***	0.430	0.370
(b) 'Other' components require supporting documentation for propose Envelope PASSES: Design 1% better than code Envelope Compliance Statement Compliance Statement: The proposed envelope design represe specifications, and other calculations submitted with this permit	ented in this docu t application. The Code, Appendix	proposed CA (modifie	envelope sy ed 90.1-201	stems have t 6) requirement	oeen nts in
designed to meet the 2020 New York City Energy Conservation					
designed to meet the 2020 New York City Energy Conservation				Date	
designed to meet the 2020 New York City Energy Conservation COMcheck Version 4.1.5.5 and to comply with any applicable m				Date	

Section # & Req.ID	Footing / Foundation Inspection	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumptions
4.2.4 [FO1] ²	Installed below-grade wall insulation type and R-value consistent with insulation specifications reported in plans and COMcheck reports.	R	R	Complies Does Not Not Observable Not Applicable	See the Envelope Assemblies table for values.
4.2.4 [FO3] ²	Installed slab-on-grade insulation type and R-value consistent with insulation specifications reported in plans and COMcheck reports.	R Unheated Heated	R Unheated Heated	Complies Does Not Not Observable Not Applicable	See the Envelope Assemblies table for values.
5.5.3.5 [FO5] ²	Slab edge insulation depth/length.	ft	ft	Complies Does Not Not Observable Not Applicable	See the Envelope Assemblies table for values.
5.8.1.7 [FO6] ¹	Exterior insulation protected against damage, sunlight, moisture, wind, landscaping and equipment maintenance activities.			Complies Does Not Not Observable Not Applicable	Requirement will be met.
5.8.1.7.3 [FO7] ¹	Insulation in contact with the ground has <=0.3% water absorption rate per ASTM C272.			Complies Does Not Not Observable	Requirement will be met.

□Not Observable
□Not Applicable

Additional Comments/Assumptions:

Project Title: CHPE Astoria HVDC Converter Station

Data filename: C:\Users\acarlson\Desktop\Astoria COMcheck.cck

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: CHPE Astoria HVDC Converter Station Data filename: C:\Users\acarlson\Desktop\Astoria COMcheck.cck Report date: 12/07/22

COMcheck Software Version 4.1.5.5

Energy Code: 2020 New York City Energy Conservation Code, Appendix CA

Requirements: 98.0% were addressed directly in the COMcheck software Text in the "Comments/Assumptions" column is provided by the user in the COMcheck Requirements screen. For each requirement, the user certifies that a code requirement will be met and how that is documented, or that an exception is being claimed. Where compliance is itemized in a separate table, a reference to that table is provided.

Section # & Req.ID	Plan Review	Complies?	Comments/Assumptions
4.2.2, 5.4.3.1.1, 5.7 [PR1] ¹	Plans and/or specifications provide all information with which compliance can be determined for the building envelope and document where exceptions to the standard are claimed.	Complies Does Not Not Observable Not Applicable	Requirement will be met.
4.2.2, 8.4.1.1, 8.4.1.2, 8.7 [PR6] ²	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the electrical systems and equipment and document where exceptions are claimed. Feeder connectors sized in accordance with approved plans and branch circuits sized for maximum drop of 3%.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
5.5.4.2.3 [PR7] ²	In buildings > 2,500 ft2, any enclosed spaces directly under a roof with ceiling heights > 15 ft. and used as an office, lobby, atrium, concourse, corridor, storage (including nonrefrigerated warehouse), gymnasium, fitness/exercise area, playing area, gymnasium seating area, convention exhibit/event space, courtroom, automotive service, fire station engine room, manufacturing corridor/transition and bay areas, retail, library reading and stack areas, distribution/sorting area, transportation baggage and seating areas, or workshop, the following requirements apply: The daylight zone under skylights is >= half the floor area and (a) the skylight area to daylight zone is >= 3 percent with a skylight VT >= 0.40 or (b) the minimum skylight effective aperture >= 1 percent. The skylights have a measured haze value > 90 percent.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
8.4.5 [PR11] ¹	Electrical meters for tenant spaces in covered buildings. Each covered tenant space in a new building shall be equipped with a separate meter or sub-meter to measure the electrical consumption of such space when let or sublet. See section details and Section 28-311.2 of the Administrative Code. As new covered tenant spaces are created, they shall be equipped with meters or sub-meters as provided in this section		Exception: Requirement does not apply.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: CHPE Astoria HVDC Converter Station

Data filename: C:\Users\acarlson\Desktop\Astoria COMcheck.cck

Report date: 12/07/22 Page 3 of 12 ISSUED FOR PERMIT

370 7th Avenue **SUITE 1604** New York, NY 10001



25 Mohawk Avenue **Sparta, NJ 07871**

CONFIDENTIAL

THESE DRAWINGS ARE CONFIDENTIAL IN NATURE. ANY MISUSE OR UNAUTHORIZED DISTRIBUTION OF THE DRAWINGS CONTAINED HEREIN WILL BE A VOLATION OF THIS CONFIDENTIALITY REQUIREMENT AND SUBJECT THE VIOLATOR TO LIABILITY. REVIEW OF THESE MATERIALS BY RECEIPT SHALL CONSTITUTE ACCEPTANCE OF THESE TERMS AND THE TERMS OF ANY UNDERLYING CONFIDENTIALITY AGREEMENT WE MAY HAVE EXCLUDED IN OBTAINING THIS INFORMATION FROM A THIRD PARTY. IF THE RECIPIENT IS NOT IN AGREEMENT WITH THE OBLIGATION OF CONFIDENTIALITY THEN THE DRAWINGS SHALL BE RETURNED TO THE ORIGINATOR.

0	FINAL SUBMISSION	RAC	ZH	12/12/2022

DESCRIPTION



@Hitachi Energy 901 Main Campus Drive Raleigh, North Carolina 27606

DRW BY CHK BY DATE



Astoria HVDC Converter Station

31-45 20th Avenue, Astoria, Queens NY 11105 Block #850 - Lot #310 - BIN #4624437

ENERGY COMPLIANCE ARCHITECTURAL-1

DATE	12/12/22
PROJECT NO	105121
DRAWING BY	Author
CHECKED BY	Designer
DRAWING NO	

EN-001.00

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: CHPE Astoria HVDC Converter Station Data filename: C:\Users\acarlson\Desktop\Astoria COMcheck.cck Report date: 12/07/22 Page 4 of 12

Page 1 of 12

Page 5 of 12

Report date: 12/07/22

Page 2 of 12

Section # & Req.ID	Framing / Rough-In Inspection	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumption
5.4.3.2 [FR1] ³	Factory-built and site-assembled fenestration and doors are labeled or certified as meeting air leakage requirements.			Complies Does Not Not Observable Not Applicable	Requirement will be met.
5.4.3.4 [FR4] ³	Vestibules are installed where building entrances separate conditioned space from the exterior, and meet exterior envelope requirements. Doors have self-closing devices, and are >= 7 ft apart (>= 16 ft apart for adjoinging floor area >= 40000 sq.ft.). Vestibule floor area <= 7 50 sq.ft. or 2 percent of the adjoining conditioned floor area.			Complies Does Not Not Observable Not Applicable	2
5.5.4.3a [FR8] ¹	Vertical fenestration U-Factor.	U	U	Complies Does Not Not Observable Not Applicable	See the Envelope Assemblies table for values.
5.5.4.3b [FR9] ¹	Skylight fenestration U-Factor.	U	U	Complies Does Not Not Observable Not Applicable	See the Envelope Assemblies table for values.
5.5.4.4.1 [FR10] ¹	Vertical fenestration SHGC value.	SHGC:	SHGC:	Complies Does Not Not Observable Not Applicable	See the Envelope Assemblies table for values.
5.5.4.4.2 [FR11] ¹	Skylight SHGC value.	SHGC:	SHGC:	Complies Does Not Not Observable Not Applicable	See the Envelope Assemblies table for values.
5.8.2.1, 5.8.2.3, 5.8.2.4, 5.8.2.5 [FR12] ²	Fenestration products rated (U- factor, SHGC, and VT) in accordance with NFRC or energy code defaults are used.			Complies Does Not Not Observable Not Applicable	Requirement will be met.
5.8.2.2 [FR13] ¹	Fenestration and door products are labeled, or a signed and dated certificate listing the U- factor, SHGC, VT, and air leakage rate has been provided by the manufacturer.			Complies Does Not Not Observable Not Applicable	Requirement will be met.
5.5.3.6 [FR14] ²	U-factor of opaque doors associated with the building thermal envelope meets requirements.	U Swinging Nonswinging	U Swinging Nonswinging	Complies Does Not Not Observable Not Applicable	See the Envelope Assemblies table for values.
5.4.3.1 [FR15] ¹	Continuous air barrier is wrapped, sealed, caulked, gasketed, and/or taped in an approved manner, except in semiheated spaces.			Complies Does Not Not Observable Not Applicable	Requirement will be met.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: CHPE Astoria HVDC Converter Station Report date: 12/07/22 Page 6 of 12 Data filename: C:\Users\acarlson\Desktop\Astoria COMcheck.cck

Section # & Req.ID	Insulation Inspection	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumptions
4.2.4 [IN2] ¹	Installed roof insulation type and R-value consistent with insulation specifications reported in plans and COMcheck reports. For some ceiling systems, verification may need to occur during Framing Inspection.	R Above deck Metal Attic	R Above deck Metal Attic	Complies Does Not Not Observable Not Applicable	See the Envelope Assemblies table for values.
5.8.1.2, 5.8.1.3 [IN3] ¹	Roof insulation installed per manufacturer's instructions. Blown or poured loose-fill insulation is installed only where the ceiling slope is <= 3:12.			Complies Does Not Not Observable Not Applicable	Requirement will be met.
4.2.4 [IN6] ¹	Installed above-grade wall insulation type and R-value consistent with insulation specifications reported in plans and COMcheck reports.	R Mass Metal Steel Wood	R Mass Metal Steel Wood	Complies Does Not Not Observable Not Applicable	See the Envelope Assemblies table for values.
5.8.1.2 [IN7] ¹	Above-grade wall insulation installed per manufacturer's instructions.			Complies Does Not Not Observable Not Applicable	Requirement will be met.
4.2.4 [IN8] ²	Installed floor insulation type and R-value consistent with insulation specifications reported in plans and COMcheck reports.	R Mass Steel Wood	R Mass Steel Wood	Complies Does Not Not Observable Not Applicable	See the Envelope Assemblies table for values.
5.8.1.1 [IN10] ²	Building envelope insulation is labeled with R-value or insulation certificate has been provided listing R-value and other relevant data.			Complies Does Not Not Observable Not Applicable	Requirement will be met.
5.8.1.9 [IN18] ²	Building envelope insulation extends over the full area of the component at the proposed rated R or U value.			Complies Does Not Not Observable Not Applicable	Requirement will be met.
5.8.1.4 [IN11] ²	Eaves are baffled to deflect air to above the insulation.			Complies Does Not Not Observable Not Applicable	Requirement will be met.
5.8.1.5 [IN12] ²	Insulation is installed in substantial contact with the inside surface separating conditioned space from unconditional space.			Complies Does Not Not Observable Not Applicable	Requirement will be met.
5.8.1.6 [IN13] ²	Recessed equipment installed in building envelope assemblies does not compress the adjacent insulation.			Complies Does Not Not Observable Not Applicable	Requirement will be met.
5.8.1.7.1 [IN15] ²	Attics and mechanical rooms have insulation protected where adjacent to attic or equipment access.			Complies Does Not Not Observable Not Applicable	Requirement will be met.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Report date: 12/07/22

Page 9 of 12

Project Title: CHPE Astoria HVDC Converter Station

Data filename: C:\Users\acarlson\Desktop\Astoria COMcheck.cck

Section # & Req.ID	Framing / Rough-In Inspection	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumptions
5.4.3.1.3 [FR16] ¹	Whole-building pressurization conducted by an independent third party. Measured air leakage rate of the building envelope <= 0.40 cfm/ft2, with this air leakage rate normalized by the sum of the above and below-grade building envelope areas of the conditioned and semiheated space. R-2 buildings may alternatively show compliance through testing in accordance with Section R402.4.1.3 of the New York City Energy Conservation Code. See department rules and code section for conditional exceptions.			Complies Does Not Not Observable Not Applicable	Requirement will be met.
5.4.4 [PR10] ¹	Applications for construction document approval includes thermal bridge documentation inlcuding: 1) Clear field thermal bridges, 2) Point thermal bridges, 3) Linear thermal bridges. See section language for details.			Complies Does Not Not Observable Not Applicable	

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3) Project Title: CHPE Astoria HVDC Converter Station Report date: 12/07/22 Page 7 of 12 Data filename: C:\Users\acarlson\Desktop\Astoria COMcheck.cck

Section # & Req.ID	Insulation Inspection	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumptions
5.8.1.7.2 [IN16] ²	Foundation vents do not interfere with insulation.			Complies Does Not Not Observable Not Applicable	Requirement will be met.
5.8.1.8 [IN17] ³	Insulation intended to meet the roof insulation requirements cannot be installed on top of a suspended ceiling. Mark this requirement compliant if insulation is installed accordingly.			Complies Does Not Not Observable Not Applicable	Requirement will be met.
5.5.3.7 [IN19] ³	Balconies and parapets that interrupt the building thermal envelope comply with one of the following: 1. Insulated with continuous insulation R-value >= thermal resistance equivalent to the continuous insulation component required in the adjacent wall assembly. Where more than one wall assembly is interrupted by an adjacent balcony, the higher thermal resistance shall be followed. 2. Incorporate >= R-3 thermal break where the structural element penetrates the building thermal envelope.			Complies Does Not Not Observable Not Applicable	Exception: Requirement does not apply.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: CHPE Astoria HVDC Converter Station Data filename: C:\Users\acarlson\Desktop\Astoria COMcheck.cck

Report date: 12/07/22 Page 10 of 12

Section # & Req.ID	Rough-In Electrical Inspection	Complies?	Comments/Assumptions
8.4.2 [EL10] ²	At least 50% of all 125 volt 15- and 20-Amp receptacles are controlled by an automatic control device.	Complies Does Not Not Observable Not Applicable	Exception: Receptacles intended for 24 hour operation of equipment.
8.4.3 [EL11] ²	New buildings have electrical energy use measurement devices installed. Where tenant spaces exist, each tenant is monitored separately. In buildings with a digital control system the energy use is transmitted to to control system and displayed graphically.	Complies Does Not Not Observable Not Applicable	Exception: Requirement does not apply.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: CHPE Astoria HVDC Converter Station

Data filename: C:\Users\acarlson\Desktop\Astoria COMcheck.cck

Report date: 12/07/22 Page 8 of 12 ISSUED FOR PERMIT



SUITE 1604 New York, NY 10001



25 Mohawk Avenue **Sparta, NJ 07871**

CONFIDENTIAL

THESE DRAWINGS ARE CONFIDENTIAL IN NATURE. ANY MISUSE OR UNAUTHORIZED DISTRIBUTION OF THE DRAWINGS CONTAINED HEREIN WILL BE A VIOLATION OF THIS CONFIDENTIALITY REQUIREMENT AND SUBJECT THE VIOLATOR TO LIABILITY. REVIEW OF THESE MATERIALS BY RECEIPT SHALL CONSTITUTE ACCEPTANCE OF THESE TERMS AND THE TERMS OF ANY UNDERLYING CONFIDENTIALITY AGREEMENT WE MAY HAVE EXCLUDED IN OBTAINING THIS INFORMATION FROM A THIRD PARTY. IF THE RECIPIENT IS NOT IN AGREEMENT WITH THE OBLIGATION OF CONFIDENTIALITY THEN THE DRAWINGS SHALL BE RETURNED TO THE ORIGINATOR.

0	FINAL SUBMISSION	RAC	ZH	12/12/2022
REV	DESCRIPTION	DRW BY	CHK BY	DATE



901 Main Campus Drive Raleigh, North Carolina 27606



Astoria HVDC Converter Station

31-45 20th Avenue, Astoria, Queens NY 11105 Block #850 - Lot #310 - BIN #4624437

ENERGY COMPLIANCE ARCHITECTURE-2

I	
DATE	12/12/22
PROJECT NO	105121
DRAWING BY	Author
CHECKED BY	Designer
DRAWING NO	

EN-002.00

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
5.4.3.3 [FI1] ¹	Weatherseals installed on all loading dock cargo doors in Climate Zones 4-	Complies Does Not	Exception: Requirement does not apply.
	8.	□Not Observable □Not Applicable	
5.7.5 [FI58] ¹	Air barrier commissioning. Registered or approved agent provides evidence of air barrier commissioning including: 1) Construction documents that include documentation of the continuous air barrier components included in the design and a field inspection checklist that includes all requirements necessary for maintaining air barrier continuity and durability in accordance with Section 5.4.3.1; 2) Reports from field inspections during project construction showing compliance with continuous air barrier requirements. Air barrier continuity shall be determined by testing or inspecting each type of unique air barrier joint or seam in the building envelope for continuity and defects; 3) A final commissioning report indicating compliance with the continuous air barrier requirements shall be provided to the building owner and, upon request, to the code official.	□Not Applicable	Requirement will be met.

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: CHPE Astoria HVDC Converter Station Report Title: C:\Users\acarlson\Desktop\Astoria COMcheck.cck

Report date: 12/07/22 Page 11 of 12 Project Title: CHPE Astoria HVDC Converter Station

Data filename: C:\Users\acarlson\Desktop\Astoria COMcheck.cck

Report date: 12/07/22 Page 12 of 12 ISSUED FOR PERMIT



370 7th Avenue SUITE 1604 New York, NY 10001



25 Mohawk Avenue Sparta, NJ 07871

CONFIDENTIAL

THESE DRAWINGS ARE CONFIDENTIAL IN NATURE. ANY MISUSE OR UNAUTHORIZED DISTRIBUTION OF THE DRAWINGS CONTAINED HEREIN WILL BE A VIOLATION OF THIS CONFIDENTIALITY REQUIREMENT AND SUBJECT THE VIOLATOR TO LIABILITY. REVIEW OF THESE MATERIALS BY RECEIPT SHALL CONSTITUTE ACCEPTANCE OF THESE TERMS AND THE TERMS OF ANY UNDERLYING CONFIDENTIALITY AGREEMENT WE MAY HAVE EXCLUDED IN OBTAINING THIS INFORMATION FROM A THIRD PARTY. IF THE RECIPIENT IS NOT IN AGREEMENT WITH THE OBLIGATION OF CONFIDENTIALITY THEN THE DRAWINGS SHALL BE RETURNED TO THE ORIGINATOR.

0	FINAL SUBMISSION	RAC	ZH	12/12/2022
חבי	DESCRIPTION	DDW BV	CHK BY	DATE



Hitachi Energy901 Main Campus Drive Raleigh, North Carolina 27606



Astoria HVDC Converter Station

31-45 20th Avenue, Astoria, Queens NY 11105 Block #850 - Lot #310 - BIN #4624437

ENERGY COMPLIANCE ARCHITECTURE-3

1	
DATE	12/12/22
PROJECT NO	105121
DRAWING BY	Author
CHECKED BY	Designer
DRAWING NO	
	00000

EN-003.00

CADD FILE NO
Autodesk Docs://CHPE
Astoria/CHA-KIE-111-ZZ-M3-A-001.rvt

↑ COM*check* Software Version 4.1.5.5

Mechanical Compliance Certificate

Project Information

Project Type:

2020 New York City Energy Conservation Code, Appendix CA (modified 90.1-2016) Energy Code: Astoria HVDC Converter Station Project Title:

New York, New York Location: Climate Zone: 4a

Construction Site: Owner/Agent: Designer/Contractor: 31-45m20th Avenue

New Construction

Astoria, NY 11105 Additional Efficiency Package(s) Credits: 1.0 Required 1.0 Proposed High Performance HVAC, 1.0 credit

Mechanical Systems List Quantity System Type & Description

1 ACCU-111-01 A/B (Service) (Single Zone): VRF Condensing Unit, Air Cooled Heat Pump Heating Mode: Capacity = 18 kBtu/h, Proposed Efficiency = 10.00 HSPF, Required Efficiency = 8.47 HSPF

Cooling Mode: Capacity = 18 kBtu/h, Proposed Efficiency = 20.00 SEER, Required Efficiency: 14.30 SEER Fan System: None 1 ACCU-111-02 (Service) (Single Zone):

VRF Condensing Unit, Air Cooled w/ Heat Recovery Heat Pump

Heating Mode: Capacity = 135 kBtu/h, Proposed Efficiency = 4.00 COP, Required Efficiency = 3.63 COP Cooling Mode: Capacity = 120 kBtu/h, Proposed Efficiency = 20.70 EER, Required Efficiency: 11.88 EER + 15.8 IEER Fan System: None

1 ACCU-111-03 (Service) (Single Zone): VRF Condensing Unit, Air Cooled w/ Heat Recovery Heat Pump Heating Mode: Capacity = 108 kBtu/h, Proposed Efficiency = 4.30 COP, Required Efficiency = 3.63 COP Cooling Mode: Capacity = 86 kBtu/h, Proposed Efficiency = 17.50 EER, Required Efficiency: 11.88 EER + 15.8 IEER Fan System: None

1 ACCU-111-04 (Service) (Single Zone): VRF Condensing Unit, Air Cooled w/ Heat Recovery Heat Pump Heating Mode: Capacity = 19 kBtu/h, Proposed Efficiency = 10.00 HSPF, Required Efficiency = 8.47 HSPF Cooling Mode: Capacity = 18 kBtu/h,

Proposed Efficiency = 20.00 SEER, Required Efficiency: 14.30 SEER Fan System: None 1 AC-111-01A/B (Service) (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 18 kBtu/h No minimum efficiency requirement applies Fan System: AC-111-01A/B | Service -- Compliance (Motor nameplate HP method) : Passes

11101 Supply, Constant Volume, 459 CFM, 0.1 motor nameplate hp, 0.0 fan efficiency grade

Report date: 12/07/22 Project Title: Astoria HVDC Converter Station Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck Page 1 of 19

Project Title: Astoria HVDC Converter Station Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck

Quantity System Type & Description

1 AC-111-02 and 03 (Service) (Single Zone):

1 AC-111-16 (Service) (Single Zone):

efficiency grade

Pressure Drop Credits:

IWH-111-01,02, 03 (Service):

Mechanical Compliance Statement

Cooling: 2 each - VRF Zone Fan Unit, Capacity = 28 kBtu/h

Cooling: 12 each - VRF Zone Fan Unit, Capacity = 12 kBtu/h

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 19 kBtu/h

Heating: 2 each - Central Furnace, Electric, Capacity = 757 kBtu/h

Particulate filtration credit: MERV 13 through 15, 15.6863 credit

Energy recover device, other than Coil Runaround Loop, 14.6754 credit

Exhaust filters, scrubbers, or other exhaust treatment, 17.4292 credit

Alexander Zabolotsky, PE- Lead Mechanical Engineer
Name - Title

Signature

Return and/or exhaust airflow control devices, 8.7146 credit

Fully ducted return and/or exhaust air systems, 8.7146 credit

Particulate filtration credit: MERV 9 through 12, 8.7146 credit

Electric Instantaneous Water Heater, Capacity: 0 gallons

No minimum efficiency requirement applies

Fan System: AC-111-02 and 03 | Service -- Compliance (Motor nameplate HP method) : Passes

AC1110203 Supply, Constant Volume, 855 CFM, 0.1 motor nameplate hp, 0.0 fan efficiency grade

Fan System: AC-111-04 through 15 | Service -- Compliance (Motor nameplate HP method): Passes

AC1110415 Supply, Constant Volume, 307 CFM, 0.1 motor nameplate hp, 0.0 fan efficiency grade

AC11116 Supply, Constant Volume, 459 CFM, 0.1 motor nameplate hp, 0.0 fan efficiency grade

AHU081010203 Supply, Single-Zone VAV, 32000 CFM, 90.0 motor nameplate hp, 67.6 design brake hp (70.0 max. BHP), 80.0 fan

Compliance Statement: The proposed mechanical design represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed mechanical systems have been designed to meet the 2020 New York City Energy Conservation Code, Appendix CA (modified 90.1-2016) requirements in COMcheck Version 4.1.5.5 and to comply with any applicable mandatory requirements listed in the Inspection Checklist.

Fan System: AC-111-16 | Service -- Compliance (Motor nameplate HP method) : Passes

Fan System: AHU-081-01, 02, 03 | Valve Hall -- Compliance (Brake HP method) : Passes

No minimum efficiency requirement applies

AC-111-04 through 15 (Service) (Single Zone):

No minimum efficiency requirement applies

No minimum efficiency requirement applies

AHU-081-01/02/03 (Valve Hall) (Single Zone):

No minimum efficiency requirement applies

Report date: 12/07/22 Page 2 of 19

Footing / Foundation Inspection Comments/Assumptions & Req.ID 6.4.3.7 Freeze protection and snow/ice **Exception:** Requirement does not apply. **J**Complies [FO9]³ melting system sensors for future \square Does Not connection to controls. ☐Not Observable

☐Not Applicable **Additional Comments/Assumptions:**

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: Astoria HVDC Converter Station Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck

COMcheck Software Version 4.1.5.5

Inspection Checklist

Energy Code: 2020 New York City Energy Conservation Code, Appendix CA Requirements: 100.0% were addressed directly in the COMcheck software

Text in the "Comments/Assumptions" column is provided by the user in the COMcheck Requirements screen. For each requirement, the user certifies that a code requirement will be met and how that is documented, or that an exception is being claimed. Where compliance is itemized in a separate table, a reference to that table is provided. Section

# & Req.ID	Plan Review	Complies?	Comments/Assumptions
4.2.2, 6.4.4.2.1, 6.7.2 [PR2] ¹	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the mechanical systems and equipment and document where exceptions to the standard are claimed. Load calculations per acceptable engineering standards and handbooks.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
4.2.2, 7.7.1, 10.4.2 [PR3] ¹	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the service water heating systems and equipment and document where exceptions to the standard are claimed. Hot water system sized per manufacturer's sizing guide.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
4.2.2, 8.4.1.1, 8.4.1.2, 8.7 [PR6] ²	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the electrical systems and equipment and document where exceptions are claimed. Feeder connectors sized in accordance with approved plans and branch circuits sized for maximum drop of 3%.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
6.7.2.4 [PR5] ¹	Detailed instructions for HVAC systems commissioning included on the plans or specifications for projects >=50,000 ft2.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
8.4.5 [PR11] ¹	Electrical meters for tenant spaces in covered buildings. Each covered tenant space in a new building shall be equipped with a separate meter or sub-meter to measure the electrical consumption of such space when let or sublet. See section details and Section 28-311.2 of the Administrative Code. As new covered tenant spaces are created, they shall be equipped with meters or sub-meters as provided in this section	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
I1 [PR12] ¹	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the additional energy efficiency package options.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: Astoria HVDC Converter Station Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck Report date: 12/07/22 Page 3 of 19 ISSUED FOR PERMIT

370 7th Avenue **SUITE 1604** New York, NY 10001



25 Mohawk Avenue **Sparta, NJ 07871**

CONFIDENTIAL

THESE DRAWINGS ARE CONFIDENTIAL IN NATURE. ANY MISUSE OR UNAUTHORIZED DISTRIBUTION OF THE DRAWINGS CONTAINED HEREIN WILL BE A VIOLATION OF THIS CONFIDENTIALITY REQUIREMENT AND SUBJECT THE VIOLATOR TO LIABILITY. REVIEW OF THESE MATERIALS BY RECEIPT SHALL CONSTITUTE ACCEPTANCE OF THESE TERMS AND THE TERMS OF ANY UNDERLYING CONFIDENTIALITY AGREEMENT WE MAY HAVE EXCLUDED IN OBTAINING THIS INFORMATION FROM A THIRD PARTY. IF THE RECIPIENT IS NOT IN AGREEMENT WITH THE OBLIGATION OF CONFIDENTIALITY THEN THE DRAWINGS SHALL BE RETURNED TO THE ORIGINATOR.

ſ					
[
[
ĺ	В	FINAL SUBMISSION	RAC	ZH	12/12/2022
- [Α	INTERIM SUBMISSION	RAC	ZH	09/13/2022
ſ	RFV	DESCRIPTION	DRW BY	CHK BY	DATE



@Hitachi Energy 901 Main Campus Drive Raleigh, North Carolina 27606

PROJECT



Astoria HVDC Converter Station

31-45 20th Avenue, Astoria, Queens NY 11105 Block #850 - Lot #310 - BIN #4624437

ENERGY COMPLIANCE MECHANICAL-1

> PROJECT NO CHECKED BY

DRAWING NO

CADD FILE NO
Autodesk Docs://CHPE
Astoria/CHA-KIE-111-ZZ-M3-A-001.rvt

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: Astoria HVDC Converter Station Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck

Report date: 12/07/22 Page 4 of 19

Report date: 12/07/22

Page 5 of 19

Section # & Req.ID	Mechanical Rough-In Inspection	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumptions
6.4.1.4, 6.4.1.5 [ME1] ²	HVAC equipment efficiency verified. Non-NAECA HVAC equipment labeled as meeting 90.1.	Efficiency:	Efficiency:	□Complies □Does Not □Not Observable	See the Mechanical Systems list for values.
6.4.3.4.1 [ME3] ³	Stair and elevator shaft vents have motorized dampers that automatically close.			□Not Applicable □Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
6.4.3.4.2, 6.4.3.4.3 [ME4] ³	Outdoor air and exhaust systems have motorized dampers that automatically shut when not in use and meet maximum leakage rates. Check gravity dampers where allowed.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
6.4.3.4.5 [ME39] ³	Enclosed parking garage ventilation has automatic contaminant detection and capacity to stage or modulate fans to 50% or less of design capacity.			□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
6.4.3.4.4 [ME5] ³	Ventilation fans >0.75 hp have automatic controls to shut off fan when not required.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
6.4.3.8 [ME6] ¹	Demand control ventilation provided for spaces >500 ft2 and >25 people/1000 ft2 occupant density and served by systems with air side economizer, auto modulating outside air damper control, or design airflow >3,000 cfm.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
6.5.3.2.1 [ME40] ²	DX cooling systems >= 75 kBtu/h (>= 65 kBtu/h effective 1/2016) and chilled-water and evaporative cooling fan motor hp >= ¼ designed to vary supply fan airflow as a function of load and comply with operational requirements.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
6.4.4.1.1 [ME7] ³	Insulation exposed to weather protected from damage. Insulation outside of the conditioned space and associated with cooling systems is vapor retardant.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
6.4.4.1.2 [ME8] ²	HVAC ducts and plenums insulated per Table 6.8.2. Where ducts or plenums are installed in or under a slab, verification may need to occur during Foundation Inspection.	R	R	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
6.4.4.1.3 [ME9] ²	HVAC piping insulation thickness. Where piping is installed in or under a slab, verification may need to occur during Foundation Inspection.	in.	in.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: Astoria HVDC Converter Station

Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck

Report date: 12/07/22 Page 6 of 19

Section # & Req.ID	Mechanical Rough-In Inspection	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumption
6.5.3.6 [ME72] ²	Motors for fans >= 1/12 hp and < 1 hp are electronically-commutated motors or have a minimum motor efficiency of 70%. These motors are also speed adjustable for either balancing or remote control.			□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
6.5.3.4 [ME108] ²	Parallel-flow fan-powered VAV air terminals have automatic controls to a) turn off the terminal fan except when space heating is required or if required for ventilation; b) turn on the terminal fan as the first stage of heating before the heating coil is activated; and c) during heating for warmup or setback temperature control, either operate the terminal fan and heating coil without primary air or reverse the terminal damper logic and provide heating from the central air handler through primary air.			□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
6.5.3.4 [ME108] ²	Parallel-flow fan-powered VAV air terminals have automatic controls to a) turn off the terminal fan except when space heating is required or if required for ventilation; b) turn on the terminal fan as the first stage of heating before the heating coil is activated; and c) during heating for warmup or setback temperature control, either operate the terminal fan and heating coil without primary air or reverse the terminal damper logic and provide heating from the central air handler through primary air.			□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
6.5.3.4 [ME108] ²	Parallel-flow fan-powered VAV air terminals have automatic controls to a) turn off the terminal fan except when space heating is required or if required for ventilation; b) turn on the terminal fan as the first stage of heating before the heating coil is activated; and c) during heating for warmup or setback temperature control, either operate the terminal fan and heating coil without primary air or reverse the terminal damper			□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: Astoria HVDC Converter Station

Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck

or reverse the terminal damper logic and provide heating from the central air handler through

primary air.

Report date: 12/07/22

Page 9 of 19

Section # & Req.ID	Mechanical Rough-In Inspection	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumptions
6.4.4.1.4 [ME41] ³	Thermally ineffective panel surfaces of sensible heating panels have insulation >= R-3.5.			□Complies □Does Not	Exception: Requirement does not apply.
	panels have insulation 1			□Not Observable □Not Applicable	
6.4.4.2.1 [ME10] ²	Ducts and plenums having pressure class ratings are Seal			□Complies □Does Not	Requirement will be met.
	Class A construction.			□Not Observable □Not Applicable	
6.8.1-15, 6.8.1-16	Electrically operated DX-DOAS units meet requirements per			□Complies □Does Not	Exception: Requirement does not apply.
[ME110] ²	Tables 6.8.1-15 or 6.8.1-16.			□Not Observable □Not Applicable	
6.4.4.2.2 [ME11] ³	Ductwork operating >3 in. water column requires air leakage			□Complies □Does Not	Exception: Requirement does not apply.
(MEII)	testing.			□Not Observable □Not Applicable	does not apply.
6.4.4.2.2 [ME11] ³	Ductwork operating >3 in. water column requires air leakage			□Complies □Does Not	Exception: Requirement does not apply.
	testing.			□Not Observable □Not Applicable	
6.4.4.2.2 [ME11] ³	Ductwork operating >3 in. water column requires air leakage			□Complies □Does Not	Exception: Requirement does not apply.
	testing.			□Not Observable □Not Applicable	
6.4.4.2.2 [ME11] ³	Ductwork operating >3 in. water column requires air leakage			□Complies □Does Not	Exception: Requirement does not apply.
	testing.			□Not Observable □Not Applicable	
6.4.4.2.2 [ME11] ³	Ductwork operating >3 in. water column requires air leakage			□Complies □Does Not	Exception: Requirement does not apply.
	testing.			□Not Observable □Not Applicable	
6.4.4.2.2 [ME11] ³	Ductwork operating >3 in. water column requires air leakage			□Complies □Does Not	Exception: Requirement does not apply.
	testing.			□Not Observable □Not Applicable	
6.4.4.2.2 [ME11] ³	Ductwork operating >3 in. water column requires air leakage			□Complies □Does Not	Exception: Requirement does not apply.
	testing.			□Not Observable □Not Applicable	
6.4.4.2.2 [ME11] ³	Ductwork operating >3 in. water column requires air leakage			□Complies □Does Not	Exception: Requirement does not apply.
	testing.			□Not Observable □Not Applicable	
6.4.4.2.2 [ME11] ³	Ductwork operating >3 in. water column requires air leakage			□Complies □Does Not	Requirement will be met.
	testing.				

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: Astoria HVDC Converter Station

Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck

Report date: 12/07/22 Page 7 of 19

□Not Observable
□Not Applicable

Section # & Req.ID	Mechanical Rough-In Inspection	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumptions
6.5.3.4 [ME108] ²	Parallel-flow fan-powered VAV air terminals have automatic controls to a) turn off the terminal fan except when space heating is required or if required for ventilation; b) turn on the terminal fan as the first stage of heating before the heating coil is activated; and c) during heating for warmup or setback temperature control, either operate the terminal fan and heating coil without primary air or reverse the terminal damper logic and provide heating from the central air handler through primary air.			□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
6.5.3.4 [ME108] ²	Parallel-flow fan-powered VAV air terminals have automatic controls to a) turn off the terminal fan except when space heating is required or if required for ventilation; b) turn on the terminal fan as the first stage of heating before the heating coil is activated; and c) during heating for warmup or setback temperature control, either operate the terminal fan and heating coil without primary air or reverse the terminal damper logic and provide heating from the central air handler through primary air.			□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
6.5.3.7 [ME109] ²	Required minimum outdoor air rate is the larger of minimum outdoor air rate or minimum exhaust air rate required by Standard 62.1, Standard 170, or applicable codes or accreditation standards. Outdoor air ventilation systems shall comply with one of the following: a) design minimum system outdoor air provided < 135% of the required minimum outdoor air rate, b) dampers, ductwork, and controls allow the system to supply <= the required minimum outdoor air rate with a single set-point adjustment., or c) system includes exhaust air energy recovery complying with Section 6.5.6.1.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: Astoria HVDC Converter Station

Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck

Report date: 12/07/22 Page 10 of 19

Section #	Mechanical Rough-In Inspection	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumptions
& Req.ID 6.5.2.3	Dehumidification controls	value	value	Complies	Exception: Use of a
[ME19] ³	provided to prevent reheating, recooling, mixing of hot and cold airstreams or concurrent heating and cooling of the same airstream.			□Does Not □Not Observable □Not Applicable	desiccant systems.
6.5.2.4.1 [ME68] ³	Humidifiers with airstream mounted preheating jackets have preheat auto-shutoff value set to activate when humidification is not required.			☐Complies ☐Does Not ☐Not Observable ☐Not Applicable	Exception: Requirement does not apply.
6.5.2.4.2 [ME69] ³	Humidification system dispersion tube hot surfaces in the airstreams of ducts or airhandling units insulated >= R-0.5.			☐Complies ☐Does Not ☐Not Observable ☐Not Applicable	Exception: Requirement does not apply.
6.5.2.5 [ME70] ³	Preheat coils controlled to stop heat output whenever mechanical cooling, including economizer operation, is active.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
6.5.2.6 [ME106] ³	Units that provide ventilation air to multiple zones and operate in conjunction with zone heating and cooling systems are prevented from using heating or heat recovery to warm supply air above 60°F when representative building loads or outdoor air temperature indicate that most zones demand cooling.			□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
6.5.3.1.3 [ME74] ²	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation <= 15% of maximum total efficiency of the fan.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
6.5.3.6 [ME72] ²	Motors for fans >= 1/12 hp and < 1 hp are electronically-commutated motors or have a minimum motor efficiency of 70%. These motors are also speed adjustable for either balancing or remote control.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
6.5.3.6 [ME72] ²	Motors for fans >= 1/12 hp and < 1 hp are electronically-commutated motors or have a minimum motor efficiency of 70%. These motors are also speed adjustable for either balancing or remote control.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
6.5.3.6 [ME72] ²	Motors for fans >= 1/12 hp and < 1 hp are electronically-commutated motors or have a minimum motor efficiency of 70%. These motors are also speed adjustable for either balancing or remote control.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
6.5.3.6 [ME72] ²	Motors for fans >= 1/12 hp and < 1 hp are electronically-commutated motors or have a minimum motor efficiency of 70%. These motors are also speed adjustable for either balancing or remote control.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)


Project Title: Astoria HVDC Converter Station Report

Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck

Report date: 12/07/22 Page 8 of 19 ISSUED FOR PERMIT

Engineering and Land Surveying, P.C.

370 7th Avenue SUITE 1604 New York, NY 10001



25 Mohawk Avenue Sparta, NJ 07871

CONFIDENTIAL

THESE DRAWINGS ARE CONFIDENTIAL IN NATURE. ANY MISUSE OR UNAUTHORIZED DISTRIBUTION OF THE DRAWINGS CONTAINED HEREIN WILL BE A VIOLATION OF THIS CONFIDENTIALITY REQUIREMENT AND SUBJECT THE VIOLATOR TO LIABILITY. REVIEW OF THESE MATERIALS BY RECEIPT SHALL CONSTITUTE ACCEPTANCE OF THESE TERMS AND THE TERMS OF ANY UNDERLYING CONFIDENTIALITY AGREEMENT WE MAY HAVE EXCLUDED IN OBTAINING THIS INFORMATION FROM A THIRD PARTY. IF THE RECIPIENT IS NOT IN AGREEMENT WITH THE OBLIGATION OF CONFIDENTIALITY THEN THE DRAWINGS SHALL BE RETURNED TO THE ORIGINATOR.

	В	FINAL SUBMISSION	RAC	ZH	12/12/2022
	Α	INTERIM SUBMISSION	RAC	ZH	09/13/2022
Γ	RFV	DESCRIPTION	DRW BY	CHK BY	DATE



Hitachi Energy901 Main Campus Drive Raleigh, North Carolina 27606

PROJEC



Astoria HVDC Converter Station

31-45 20th Avenue, Astoria, Queens NY 11105 Block #850 - Lot #310 - BIN #4624437

ENERGY COMPLIANCE MECHANICAL-2

 DATE
 12/12/22

 PROJECT NO
 105121

 DRAWING BY
 Author

 CHECKED BY
 Designer

 DRAWING NO

EN-005.00

CADD FILE NO
Autodesk Docs://CHPE
Astoria/CHA-KIE-111-ZZ-M3-A-001.rvt

Section # & Req.ID	Mechanical Rough-In Inspection	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumptions
6.5.3.7 [ME109] ²	Required minimum outdoor air rate is the larger of minimum outdoor air rate or minimum exhaust air rate required by Standard 62.1, Standard 170, or applicable codes or accreditation standards. Outdoor air ventilation systems shall comply with one of the following: a) design minimum system outdoor air provided < 135% of the required minimum outdoor air rate, b) dampers, ductwork, and controls allow the system to supply <= the required minimum outdoor air rate with a single set-point adjustment., or c) system includes exhaust air energy recovery complying with Section 6.5.6.1.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
6.5.3.7 [ME109] ²	Required minimum outdoor air rate is the larger of minimum outdoor air rate or minimum exhaust air rate required by Standard 62.1, Standard 170, or applicable codes or accreditation standards. Outdoor air ventilation systems shall comply with one of the following: a) design minimum system outdoor air provided < 135% of the required minimum outdoor air rate, b) dampers, ductwork, and controls allow the system to supply <= the required minimum outdoor air rate with a single set-point adjustment., or c) system includes exhaust air energy recovery complying with Section 6.5.6.1.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
6.5.3.7 [ME109] ²	Required minimum outdoor air rate is the larger of minimum outdoor air rate or minimum exhaust air rate required by Standard 62.1, Standard 170, or applicable codes or accreditation standards. Outdoor air ventilation systems shall comply with one of the following: a) design minimum system outdoor air provided < 135% of the required minimum outdoor air rate, b) dampers, ductwork, and controls allow the system to supply <= the required minimum outdoor air rate with a single set-point adjustment., or c) system includes exhaust air energy recovery complying with Section 6.5.6.1.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3) Report date: 12/07/22

Project Title: Astoria HVDC Converter Station Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck

Page 11 of 19

Section # & Req.ID	Mechanical Rough-In Inspection	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumptions
6.4.3.9 [ME63] ²	Heating for vestibules and air curtains with integral heating include automatic controls that shut off the heating system when outdoor air temperatures > 45F. Vestibule heating and cooling systems controlled by a thermostat in the vestibule with heating setpoint <= 60F and cooling setpoint >= 80F.			□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
6.5.10 [ME73] ³	Doors separating conditioned space from the outdoors have controls that disable/reset heating and cooling system when open.			□Complies □Does Not □Not Observable □Not Applicable	Exception: Building entrances have automatic closing devices.
6.7.2.3.2. 1 [ME53] ³	Mechanical systems, Renewable Systems, and SWH Commissioning: Air outlets and zone terminal devices have means for air balancing. See section details.			□Complies □Does Not □Not Observable □Not Applicable	Exception: Fans with fan motors of 1 hp (0.74 kW) or less.

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3) Project Title: Astoria HVDC Converter Station Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck Page 14 of 19

6.5.3.7 [ME109] ²	Required minimum outdoor air rate is the larger of minimum outdoor air rate or minimum exhaust air rate required by Standard 62.1, Standard 170, or applicable codes or accreditation standards. Outdoor air ventilation systems shall comply with one of the following: a) design minimum system outdoor air provided < 135% of the required minimum outdoor air rate, b) dampers, ductwork, and controls allow the system to supply <= the required minimum outdoor air rate with a single set-point adjustment., or c) system includes exhaust air energy recovery complying with Section 6.5.6.1.		□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
6.5.3.3 [ME42] ³	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint reset controls.		□Complies □Does Not □Not Observable	Exception: Requirement does not apply. See the Mechanical Systems list
6.5.3.3 [ME42] ³	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint		□Not Applicable □Complies □Does Not	Exception: Requirement does not apply.
	reset controls.		□Not Observable □Not Applicable	See the Mechanical Systems list for values.
6.5.3.3 [ME42] ³	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint		□Complies □Does Not	Exception: Requirement does not apply.
	reset controls.		□Not Observable □Not Applicable	See the Mechanical Systems list for values.
6.5.3.3 [ME42] ³	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint		□Complies □Does Not	Exception: Requirement does not apply.
	reset controls.		□Not Observable □Not Applicable	See the Mechanical Systems list for values.
6.5.3.3 [ME42] ³	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint		☐Complies ☐Does Not ☐Not Observable	Exception: Requirement does not apply.
	reset controls.		□Not Applicable	See the Mechanical Systems list for values.
6.5.3.3 [ME42] ³	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint		□Complies □Does Not	Exception: Requirement does not apply.
	reset controls.		□Not Observable □Not Applicable	See the Mechanical Systems list for values.
6.5.3.3 [ME42] ³	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint		□Complies □Does Not	Exception: Requirement does not apply.
	reset controls.		□Not Observable □Not Applicable	See the Mechanical Systems list for values.
6.5.3.3 [ME42] ³	Multiple zone VAV systems with DDC of individual zone boxes have static pressure setpoint		□Complies □Does Not	Exception: Requirement does not apply.
	reset controls.		□Not Observable □Not Applicable	See the Mechanical Systems list for values.
6.5.3.3 [ME42] ³	Multiple zone VAV systems with DDC of individual zone boxes		□Complies □Does Not	Exception: Requirement does not apply.
	have static pressure setpoint reset controls.		□Not Observable □Not Applicable	See the Mechanical Systems list for values.
	1 High Impact (Tier	1) 2 Medium Impact (Tier 2)	3 Low Impact (T	ier 3)
Project Title		·	- I - I - I - I - I - I - I - I - I - I	Report date: 12/07/22
-		y\Downloads\Astoria COMcheck.cck		Page 12 of 19

Mechanical Rough-In Plans Verified Field Verified

Inspection

6.5.3.7 Required minimum outdoor air

& Req.ID

Complies? Comments/Assumptions

Section # & Req.ID	Rough-In Electrical Inspection	Complies?	Comments/Assumptions
[EL10] ² 20-Amp receptacles are controlled by an automatic control device.		□Complies □Does Not	Exception: Requirement does not apply.
		□Not Observable □Not Applicable	
8.4.3 [EL11] ²	New buildings have electrical energy use measurement devices installed. Where tenant spaces exist, each tenant is monitored separately. In buildings with a digital control system the energy use is transmitted to to control system and displayed	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
10.4.1 [EL9] ²	graphically. Electric motors meet requirements where applicable.	□Complies □Does Not	Requirement will be met.
		□Not Observable □Not Applicable	

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: Astoria HVDC Converter Station Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck Page 15 of 19

Section # & Req.ID	Mechanical Rough-In Inspection	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumptions
6.5.4.2 [ME25] ³	HVAC pumping systems with >= 3 control values designed for variable fluid flow (see section			☐Complies ☐Does Not ☐Not Observable	Exception: Requirement does not apply.
	details).			□Not Observable □Not Applicable	
6.5.6.1 [ME56] ¹	Exhaust air energy recovery on systems meeting Tables 6.5.6.1-1, and 6.5.6.1-2.			□Complies □Does Not	Requirement will be met.
	1, and 0.3.0.1-2.			□Not Observable □Not Applicable	
6.5.7.1 [ME100] ²	Conditioned supply air to space with mechanical exhaust <= the greater of criteria of supply flow,			☐Complies ☐Does Not	Requirement will be met.
	required ventilation rate, exhaust flow minu the available transffer air (see section details).			□Not Observable □Not Applicable	
6.5.7.1 [ME100] ²	Conditioned supply air to space with mechanical exhaust <= the greater of criteria of supply flow,			☐Complies ☐Does Not	Requirement will be met.
	required ventilation rate, exhaust flow minu the available transffer air (see section details).			□Not Observable □Not Applicable	
6.5.7.1 [ME100] ²	Conditioned supply air to space with mechanical exhaust <= the greater of criteria of supply flow,			□Complies □Does Not	Requirement will be met.
	required ventilation rate, exhaust flow minu the available transffer air (see section details).			□Not Observable □Not Applicable	
6.5.7.1 [ME100] ²	Conditioned supply air to space with mechanical exhaust <= the			□Complies □Does Not	Requirement will be met.
	greater of criteria of supply flow, required ventilation rate, exhaust flow minu the available transffer air (see section details).			□Not Observable □Not Applicable	
6.5.7.1 [ME100] ²	Conditioned supply air to space with mechanical exhaust <= the			□Complies □Does Not	Requirement will be met.
	greater of criteria of supply flow, required ventilation rate, exhaust flow minu the available transffer air (see section details).			□Not Observable □Not Applicable	
6.5.7.2.1 [ME32] ²	Kitchen hoods >5,000 cfm have make up air >=50% of exhaust			□Complies □Does Not	Exception: Requirement does not apply.
	air volume.			□Not Observable □Not Applicable	
6.5.7.2.4 [ME49] ³	Approved field test used to evaluate design air flow rates and demonstrate proper capture			☐Complies ☐Does Not	Exception: Requirement does not apply.
	and containment of kitchen exhaust systems.			□Not Observable □Not Applicable	
6.5.8.1 [ME34] ²	Unenclosed spaces that are heated use only radiant heat.			□Complies □Does Not	Exception: Requirement does not apply.
				□Not Observable □Not Applicable	;
7.4.2 [ME36] ²	Service water heating equipment meets efficiency requirements.			□Complies □Does Not	
				□Not Observable □Not Applicable	

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: Astoria HVDC Converter Station

Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck

Report date: 12/07/22 Page 13 of 19 ISSUED FOR PERMIT

Engineering and Land Surveying, P.C.

370 7th Avenue **SUITE 1604** New York, NY 10001



25 Mohawk Avenue **Sparta, NJ 07871**

CONFIDENTIAL

THESE DRAWINGS ARE CONFIDENTIAL IN NATURE. ANY MISUSE OR UNAUTHORIZED DISTRIBUTION OF THE DRAWINGS CONTAINED HEREIN WILL BE A VIOLATION OF THIS CONFIDENTIALITY REQUIREMENT AND SUBJECT THE VIOLATOR TO LIABILITY. REVIEW OF THESE MATERIALS BY RECEIPT SHALL CONSTITUTE ACCEPTANCE OF THESE TERMS AND THE TERMS OF ANY UNDERLYING CONFIDENTIALITY AGREEMENT WE MAY HAVE EXCLUDED IN OBTAINING THIS INFORMATION FROM A THIRD PARTY. IF THE RECIPIENT IS NOT IN AGREEMENT WITH THE OBLIGATION OF CONFIDENTIALITY THEN THE DRAWINGS SHALL BE RETURNED TO THE ORIGINATOR.

В	FINAL SUBMISSION	RAC	ZH	12/12/2022
Α	INTERIM SUBMISSION	RAC	ZH	09/13/2022
REV	DESCRIPTION	DRW BY	CHK BY	DATE



901 Main Campus Drive

Raleigh, North Carolina 27606



Astoria HVDC Converter Station

31-45 20th Avenue, Astoria, Queens NY 11105 Block #850 - Lot #310 - BIN #4624437

ENERGY COMPLIANCE MECHANICAL-3

> PROJECT NO CHECKED BY DRAWING NO

Section #	Final Inspection	Complies?	Comments/Assumptions
& Req.ID		·	
6.4.3.1.2	Thermostatic controls have a 5 °F	Complies	Requirement will be met.
[FI3] ³	deadband.	□Does Not	
		□Not Observable □Not Applicable	
6.4.3.2 [FI20] ³	Temperature controls have setpoint overlap restrictions.	□Complies □Does Not	Requirement will be met.
		□Not Observable □Not Applicable	
6.4.3.3.1 [FI21] ³	HVAC systems equipped with at least one automatic shutdown control.	□Complies □Does Not	Requirement will be met.
		□Not Observable □Not Applicable	
6.4.3.3.2	Setback controls allow automatic	☐Complies	Requirement will be met.
[FI22] ³	restart and temporary operation as required for maintenance.	□Does Not	
	required for maintenance.	□Not Observable □Not Applicable	
6.4.3.3.3 [FI4] ³	Systems with setback controls and DDC include optimum start controls.	□Complies □Does Not	Exception: Systems designed for continuous operation.
[114]	Optimum start algorithm considers		
	mass radiant slab floor temperature.	□Not Observable □Not Applicable	
6.4.3.5 [FI5] ³	Heat pump controls prevent supplemental electric resistance heat	□Complies	Requirement will be met.
[[13]-	from coming on when not needed.	□Does Not	
	-	□Not Observable □Not Applicable	
6.4.3.5 [FI5] ³	Heat pump controls prevent supplemental electric resistance heat	□Complies □Does Not	Requirement will be met.
,	from coming on when not needed.	□Not Observable	
		□Not Applicable	
6.4.3.5 [FI5] ³	Heat pump controls prevent supplemental electric resistance heat	□Complies □Does Not	Requirement will be met.
	from coming on when not needed.	□Not Observable	
		□Not Applicable	
6.4.3.5 [FI5] ³	Heat pump controls prevent supplemental electric resistance heat	□Complies □Does Not	Requirement will be met.
	from coming on when not needed.	□Not Observable	
		□Not Observable □Not Applicable	
6.4.3.6 [FI6] ³	When humidification and dehumidification are provided to a	□Complies □Does Not	Exception: Zones served by desiccant systems.
[, 10]	zone, simultaneous operation is		
	prohibited. Humidity control prohibits	□Not Observable □Not Applicable	
	the use of fossil fuel or electricity to produce RH > 30% in the warmest		
	zone humidified and RH < 60% in the coldest zone dehumidified.		
6.7.2.1 [FI7] ³	Furnished HVAC as-built drawings submitted within 90 days of system	□Complies □Does Not	Requirement will be met.
]	acceptance.	□Not Observable	
		□Not Applicable	
6.7.2.2 [FI8] ³	Furnished O&M manuals for HVAC systems within 90 days of system	☐Complies ☐Does Not	Requirement will be met.
	acceptance.	□Not Observable	
		□Not Applicable	

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3) Project Title: Astoria HVDC Converter Station

Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck

Report date: 12/07/22 Page 16 of 19

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions	
6.7.2.3 [FI9] ¹	An air and/or hydronic system balancing report is provided for HVAC systems serving zones >5,000 ft2 of conditioned area.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.	
6.7.2.4 [FI10] ¹	HVAC control systems have been tested to ensure proper operation, calibration and adjustment of controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.	
7.4.4.3 [FI11] ³	Public lavatory faucet water temperature <=110°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.	
10.4.3 [FI24] ²	Elevators are designed with the proper lighting, ventilation power, and standby mode.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.	
7.4.3 [FI45] ²	First 8 ft of outlet piping in nonrecirculating storage system, or branch piping connected to recirculated, heat traced, or impredance heated piping is insulated.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.	
6.7.2.3.1 [FI28] ¹	Mechanical systems, Renewable Systems, and SWH Commissioning: Commisioning plan developed by registered design professional or approved agency. See section details.	□Complies □Does Not □Not Observable □Not Applicable		
6.7.2.3.3. 1 [FI31] ¹		□Complies □Does Not □Not Observable □Not Applicable		
6.7.2.3.3. 2 [FI10] ¹	Mechanical systems, Renewable Systems, and SWH Commissioning: HVAC control systems have been tested to ensure proper operation, calibration and adjustment of controls. See section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. e	
6.7.2.3.4 [FI29] ¹		□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.	
6.7.2.3.5. 1 [FI7] ³	Mechanical systems, Renewable Systems, and SWH Commissioning: Furnished HVAC as-built drawings submitted within 90 days of system acceptance. See section details.	□Complies □Does Not □Not Observable □Not Applicable		
6.7.2.3.5. 3 [FI43] ¹	Mechanical systems, Renewable Systems, and SWH Commissioning: An air and/or hydronic system balancing report is provided for HVAC systems. See section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.	
6.7.2.3.5. 4 [FI30] ¹	Mechanical systems, Renewable Systems, and SWH Commissioning: Final commissioning report due to building owner within 90 days of receipt of certificate of occupancy. See section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.	

Report date: 12/07/22

Page 17 of 19

Project Title: Astoria HVDC Converter Station

Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: Astoria HVDC Converter Station Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck Report date: 12/07/22 Page 18 of 19 ISSUED FOR PERMIT

370 7th Avenue **SUITE 1604** New York, NY 10001



25 Mohawk Avenue **Sparta, NJ 07871**

CONFIDENTIAL

THESE DRAWINGS ARE CONFIDENTIAL IN NATURE. ANY MISUSE OR UNAUTHORIZED DISTRIBUTION OF THE DRAWINGS CONTAINED HEREIN WILL BE A VIOLATION OF THIS CONFIDENTIALITY REQUIREMENT AND SUBJECT THE VIOLATOR TO LIABILITY. REVIEW OF THESE MATERIALS BY RECEIPT SHALL CONSTITUTE ACCEPTANCE OF THESE TERMS AND THE TERMS OF ANY UNDERLYING CONFIDENTIALITY AGREEMENT WE MAY HAVE EXCLUDED IN OBTAINING THIS INFORMATION FROM A THIRD PARTY. IF THE RECIPIENT IS NOT IN AGREEMENT WITH THE OBLIGATION OF CONFIDENTIALITY THEN THE DRAWINGS SHALL BE RETURNED TO THE ORIGINATOR.

В	FINAL SUBMISSION	RAC	ZH	12/12/202
Α	INTERIM SUBMISSION	RAC	ZH	09/13/202
RF\/	DESCRIPTION	DRW BY	CHK BY	DATE



901 Main Campus Drive Raleigh, North Carolina 27606

PROJECT



Astoria HVDC Converter Station

31-45 20th Avenue, Astoria, Queens NY 11105 Block #850 - Lot #310 - BIN #4624437

ENERGY COMPLIANCE MECHANICAL-4

1	
DATE	12/12/22
PROJECT NO	105121
DRAWING BY	Author
CHECKED BY	Designer
DRAWING NO	

EN-007.00

Project Title: Astoria HVDC Converter Station

Data filename: C:\Users\Alexander.Zabolotsky\Downloads\Astoria COMcheck.cck

Report date: 12/07/22 Page 19 of 19

Interior Lighting Compliance Certificate

Project Information

Energy Code:

2020 New York City Energy Conservation Code, Appendix CA (modified 90.1-2016)

Designer/Contractor:

Project Title: CHPE Astoria Power Converter Station Project Type: New Construction

Construction Site:

Owner/Agent: Transmission Developers Inc.

Additional Efficiency Package(s) Credits: 1.0 Required 1.0 Proposed Reduced Lighting Power, 1.0 credit

Allowed Interior Lighting Power

Area Category	Floor Area (ft2)	Allowed Watts / ft2	Allowed Watts (B X C)	
1-Converter Halls (Warehouse)	75900	0.37	28007	
2-Service Bldg (Office)	5700	0.62	3540	
		Total Allowed Watts =	= 31547	
Proposed Interior Lighting Power				

A Fixture ID : Description / Lamp / Wattage Per Lamp / Ballast	B Lamps/ Fixture	C # of Fixtures	D Fixture Watt.	(C X D)
1-Converter Halls (Warehouse)				
LED 4: P1: LED Other Fixture Unit 103W:	1	57	100	5700
2-Service Bldg (Office)				
LED 5: S16: LED Linear 33W:	1	71	37	2627
LED 6: HEM4: LED Linear 33W:	1	12	59	708
LED 7: G22: LED Linear 33W:	1	5	41	205
LED 8: A4: LED Panel 19W:	1	4	22	88
LED 9: EG4: LED Other Fixture Unit 46W:	1	54	48	2592
LED 10: A1: LED Panel 36W:	1	17	36	612
		Total Propos	ed Watts =	12532

Interior Lighting PASSES: Design 60% better than code

Interior Lighting Compliance Statement

Compliance Statement: The proposed interior lighting design represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed interior lighting systems have been designed to meet the 2020 New York City Energy Conservation Code, Appendix CA (modified 90.1-2016) requirements in COMcheck Version 4.1.5.5 and to comply with any applicable mandatory requirements listed in the Inspection Checklist.

Project Title: CHPE Astoria Power Converter Station Report date: 12/09/22 Data filename: C:\Users\Daniel.Duzan\OneDrive - Kiewit Corporation\Documents\ASTORIA\comcheck\Astoria Page 1 of 7 COMcheck.cck

▲ COM*check* Software Version 4.1.5.5

Project Information

Exterior Lighting Zone

Construction Site:

Energy Code: 2020 New York City Energy Conservation Code, Appendix CA (modified 90.1-2016) Project Title: CHPE Astoria Power Converter Station Project Type: **New Construction**

3 (Other (LZ3))

Owner/Agent:

Designer/Contractor: Transmission Developers Inc.

Allowed Exterior Lighting Power

A	В	C	_ D	E
Area/Surface Category	Quantity	Allowed Watts / Unit	Tradable Wattage	Allowed Watts (B X C)
Guarded facility, entrance/inspection area	241130 ft2	0.5	No	120565
		Total Tradab	ole Watts (a) =	0

Total Allowed Watts = Total Allowed Supplemental Watts (b) =

(a) Wattage tradeoffs are only allowed between tradable areas/surfaces. (b) A supplemental allowance equal to 500 watts may be applied toward compliance of both non-tradable and tradable areas/surfaces.

Proposed Exterior Lighting Power

Lamps/ # of Fixture (C X D) Fixture ID : Description / Lamp / Wattage Per Lamp / Ballast Fixture Fixtures Watt. Guarded facility, entrance/inspection area (241130 ft2): Non-tradable Wattage LED 11: WP1: LED Roadway-Parking Unit 42W: 36 321 11556 LED 12: LED Roadway-Parking Unit 223W: Total Tradable Proposed Watts =

Exterior Lighting PASSES: Design 0.0% better than code

Exterior Lighting Compliance Statement

COMcheck.cck

Compliance Statement: The proposed exterior lighting design represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed exterior lighting systems have been designed to meet the 2020 New York City Energy Conservation Code, Appendix CA (modified 90.1-2016) requirements in COMcheck Version 4.1.5.5 and to comply with any applicable mandatory requirements listed in the Inspection Checklist.

Name - Title Signature

Project Title: CHPE Astoria Power Converter Station Data filename: C:\Users\Daniel.Duzan\OneDrive - Kiewit Corporation\Documents\ASTORIA\comcheck\Astoria Page 2 of 7

Section # & Req.ID	Rough-In Electrical Inspection	Complies?	Comments/Assumptions
8.4.2 [EL10] ²	At least 50% of all 125 volt 15- and 20-Amp receptacles are controlled by	□Complies □Does Not	Exception: Receptacles intended for 24 hour operation of equipment.
	an automatic control device.	□Not Observable □Not Applicable	
8.4.3 [EL11] ²	New buildings have electrical energy use measurement devices installed. Where tenant spaces exist, each	□Complies □Does Not	Exception: Requirement does not apply.
	tenant is monitored separately. In buildings with a digital control system the energy use is transmitted to to control system and displayed graphically.	□Not Observable □Not Applicable	
9.4.1.1 [EL1] ²	Automatic control requirements prescribed in Table 9.6.1, for the	□Complies □Does Not	Requirement will be met.
	appropriate space type, are installed. Mandatory lighting controls (labeled as 'REQ') and optional choice controls (labeled as 'ADD1' and 'ADD2') are implemented.	□Not Observable □Not Applicable	
9.4.1.1 [EL2] ²	Independent lighting controls installed per approved lighting plans and all	□Complies □Does Not	Requirement will be met.
	manual controls readily accessible and visible to occupants.	□Not Observable □Not Applicable	
9.4.1.1f [EL13] ¹	Daylight areas under skylights and roof monitors that have more than	□Complies □Does Not	Exception: Requirement does not apply.
	150 W combined input power for general lighting are controlled by photocontrols.	□Not Observable □Not Applicable	
9.4.1.4 [EL3] ²	Automatic lighting controls for exterior lighting installed.	□Complies □Does Not	Requirement will be met.
		□Not Observable □Not Applicable	
9.4.1.3 [EL4] ¹	Separate lighting control devices for specific uses installed per approved	□Complies □Does Not	Requirement will be met.
	lighting plans.	□Not Observable □Not Applicable	
9.6.2 [EL8] ¹	Additional interior lighting power allowed for special functions per the	□Complies □Does Not	Requirement will be met.
	approved lighting plans and is automatically controlled and separated from general lighting.	□Not Observable □Not Applicable	
9.4.5 [EL6] ¹	Internally illuminated exit signs do not exceed 5 watts per face.	□Complies □Does Not	Requirement will be met.
		□Not Observable □Not Applicable	

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: CHPE Astoria Power Converter Station Data filename: C:\Users\Daniel.Duzan\OneDrive - Kiewit Corporation\Documents\ASTORIA\comcheck\Astoria Page 5 of 7



COM*check* **Software Version 4.1.5.5**

Inspection Checklist

Energy Code: 2020 New York City Energy Conservation Code, Appendix CA

Requirements: 100.0% were addressed directly in the COMcheck software Text in the "Comments/Assumptions" column is provided by the user in the COMcheck Requirements screen. For each requirement, the user certifies that a code requirement will be met and how that is documented, or that an exception is being claimed. Where compliance is itemized in a separate table, a reference to that table is provided.

Section # & Req.ID	Plan Review	Complies?	Comments/Assumptions
4.2.2, 8.4.1.1, 8.4.1.2, 8.7 [PR6] ²	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the electrical systems and equipment and document where exceptions are claimed. Feeder connectors sized in accordance with approved plans and branch circuits sized for maximum drop of 3%.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
4.2.2, 9.4.3, 9.7 [PR4] ¹	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the interior lighting and electrical systems and equipment and document where exceptions to the standard are claimed. Information provided should include interior lighting power calculations, wattage of bulbs and ballasts, transformers and control devices.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
9.7 [PR8] ¹	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the exterior lighting and electrical systems and equipment and document where exceptions to the standard are claimed. Information provided should include exterior lighting power calculations, wattage of bulbs and ballasts, transformers and control devices.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
8.4.5 [PR11] ¹	Electrical meters for tenant spaces in covered buildings. Each covered tenant space in a new building shall be equipped with a separate meter or sub-meter to measure the electrical consumption of such space when let or sublet. See section details and Section 28-311.2 of the Administrative Code. As new covered tenant spaces are created, they shall be equipped with meters or sub-meters as provided in this section	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
11 [PR12] ¹	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the additional energy efficiency package options.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: CHPE Astoria Power Converter Station Data filename: C:\Users\Daniel.Duzan\OneDrive - Kiewit Corporation\Documents\ASTORIA\comcheck\Astoria Page 3 of 7 COMcheck.cck

370 7th Avenue **SUITE 1604** New York, NY 10001



25 Mohawk Avenue **Sparta, NJ 07871**

CONFIDENTIAL

THESE DRAWINGS ARE CONFIDENTIAL IN NATURE. ANY MISUSE OR UNAUTHORIZED DISTRIBUTION OF THE DRAWINGS CONTAINED HEREIN WILL BE A VIOLATION OF THIS CONFIDENTIALITY REQUIREMENT AND SUBJECT THE VIOLATOR TO LIABILITY. REVIEW OF THESE MATERIALS BY RECEIPT SHALL CONSTITUTE ACCEPTANCE OF THESE TERMS AND THE TERMS OF ANY UNDERLYING CONFIDENTIALITY AGREEMENT WE MAY HAVE EXCLUDED IN OBTAINING THIS INFORMATION FROM A THIRD PARTY. IF THE RECIPIENT IS NOT IN AGREEMENT WITH THE OBLIGATION OF CONFIDENTIALITY THEN THE DRAWINGS SHALL BE RETURNED TO THE ORIGINATOR.

ISSUED FOR PERMIT

В	FINAL SUBMISSION	RAC	ZH	12/12/2022
Α	INTERIM SUBMISSION	RAC	ZH	09/13/2022
REV/	DESCRIPTION	DRW BY	CHK BY	DATE



@Hitachi Energy 901 Main Campus Drive Raleigh, North Carolina 27606



Astoria HVDC Converter Station

31-45 20th Avenue, Astoria, Queens NY 11105 Block #850 - Lot #310 - BIN #4624437

ENERGY COMPLIANCE ELECTRICAL-1

1	
DATE	12/12/22
PROJECT NO	105121
DRAWING BY	Author
CHECKED BY	Designer

EN-008.00

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: CHPE Astoria Power Converter Station Data filename: C:\Users\Daniel.Duzan\OneDrive - Kiewit Corporation\Documents\ASTORIA\comcheck\Astoria Page 4 of 7

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
8.7.1 [FI16] ³	Furnished as-built drawings for electric power systems within 30 days of system acceptance.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
8.7.2 [FI17] ³	Furnished O&M instructions for systems and equipment to the building owner or designated representative.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
9.2.2.3 [FI18] ¹	Interior installed lamp and fixture lighting power is consistent with what is shown on the approved lighting plans, demonstrating proposed watts are less than or equal to allowed watts.	□Complies □Does Not □Not Observable □Not Applicable	See the Interior Lighting fixture schedule for values.
9.4.2 [FI19] ¹	Exterior lighting power is consistent with what is shown on the approved lighting plans, demonstrating proposed watts are less than or equal to allowed watts.	□Complies □Does Not □Not Observable □Not Applicable	See the Exterior Lighting fixture schedule for values.
9.4.4 [FI20] ¹	At least 75% of all permanently installed lighting fixtures in dwelling units have >= 55 lm/W efficacy or a >= 45 lm/W total luminaire efficacy.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Report date: 12/09/22 Project Title: CHPE Astoria Power Converter Station Data filename: C:\Users\Daniel.Duzan\OneDrive - Kiewit Corporation\Documents\ASTORIA\comcheck\Astoria Page 6 of 7 COMcheck.cck Project Title: CHPE Astoria Power Converter Station

Data filename: C:\Users\Daniel.Duzan\OneDrive - Kiewit Corporation\Documents\ASTORIA\comcheck\Astoria Page 7 of 7 COMcheck.cck

ISSUED FOR PERMIT



370 7th Avenue SUITE 1604 New York, NY 10001



25 Mohawk Avenue **Sparta, NJ 07871**

CONFIDENTIAL

THESE DRAWINGS ARE CONFIDENTIAL IN NATURE. ANY MISUSE OR UNAUTHORIZED DISTRIBUTION OF THE DRAWINGS CONTAINED HEREIN WILL BE A VIOLATION OF THIS CONFIDENTIALITY REQUIREMENT AND SUBJECT THE VIOLATOR TO LIABILITY. REVIEW OF THESE MATERIALS BY RECEIPT SHALL CONSTITUTE ACCEPTANCE OF THESE TERMS AND THE TERMS OF ANY UNDERLYING CONFIDENTIALITY AGREEMENT WE MAY HAVE EXCLUDED IN OBTAINING THIS INFORMATION FROM A THIRD PARTY. IF THE RECIPIENT IS NOT IN AGREEMENT WITH THE OBLIGATION OF CONFIDENTIALITY THEN THE DRAWINGS SHALL BE RETURNED TO THE ORIGINATOR.

В	FINAL SUBMISSION	RAC	ZH	12/12/2022
Α	INTERIM SUBMISSION	RAC	ZH	09/13/2022
RF\/	DESCRIPTION	DRW BY	CHK BY	DATE



901 Main Campus Drive Raleigh, North Carolina 27606

PROJECT



Astoria HVDC Converter Station

31-45 20th Avenue, Astoria, Queens NY 11105 Block #850 - Lot #310 - BIN #4624437

ENERGY COMPLIANCE ELECTRICAL-2

1	
DATE	12/12/22
PROJECT NO	105121
DRAWING BY	Author
CHECKED BY	Designer
DRAWING NO	
	00000

EN-009.00

CADD FILE NO
Autodesk Docs://CHPE
Astoria/CHA-KIE-111-ZZ-M3-A-001.rvt