

INSTALLATION AND REMOVAL.

TREE PROTECTION

NOT TO SCALE

POST 36" LONG 11/2"x11/2" -HARDWOOD SPACING 10' O.C. (SEE NOTE 2) 36" WIRE FENCING-14 GA. 6" SQ. STAPLED TO POST MIRAFI 100X (OR EQUIVALENT) FABRIC (FILTER CLOTH) 30#/IN. WRAP IN TRENCH AS SHOWN COMPACTED BACKFILL -

**ELEVATION** 

4. SEE EROSION CONTROL PLANS FOR LOCATIONS OF TREE PROTECTION AREAS.

- TIE FABRIC TO WIRE FENCE IN ACCORDANCE WITH MANUFACTURERS RECOMMENDATIONS.
- 2. IF EXTRA STRENGTH FABRIC (GREATER THAN 50#/INCH) IS USED, WIRE CAN BE DELETED IF POST SPACING IS REDUCED TO 6' O.C.
- 3. AT THE ENDS OF THE FENCING THE FIRST 20' SHALL BE TURNED UP THE SLOPE 2'.
- 4. POSTS SHOULD BE INCLINED TOWARD THE DIRECTION FLOW CAME
- 5. OVERLAP FABRIC A MINIMUM OF 6" AND FOLDED AT JOINTS. ATTACH FILTER FABRIC TO STAKES ALLOWING EXTENSION INTO TRENCH AS SHOWN; SECURE TO STAKES AS NOTED.
- 6. THE MAXIMUM AREA OF RUNOFF PER 100LF. OF FENCE SHALL NOT EXCEED 0.25 ACRES.
- MAINTENANCE SHALL BE PERFORMED AS NECESSARY. THE FENCING SHALL BE CHECKED AFTER EVERY STORM TO ENSURE THEY'RE PROPER FUNCTIONING.
- WHEN FENCE IS NO LONGER NEEDED, THE ACCUMULATED SILT, THE POSTS AND FABRIC SHALL BE REMOVED AND TRENCH BACK FILLED WITH TOPSOIL AND SEEDED.
- 9. FENCING SHOULD BE PLACED AS SHOWN ON THE DRAWING OR IF NOT SHOWN, 10' BEYOND THE TOE OF THE SLOPE AND AT A SPACING IN ACCORDANCE WITH THE TABLE.
- 10. EXCAVATE TRENCH AS PER DETAIL AND SET POSTS AT 10' O.C.
- 11. BACKFILL WITH COMPACTED, EXCAVATED SOIL FROM TRENCH.

-NORTH AMERICAN GREEN S75 OR APPROVED EQUAL ON SUBGRADE, TEMP. SEED MIXTURE FILTER SOCK, SIZED TO SUIT CONDITIONS. -HARDWOOD POST 10' O.C. WATER FLOW INLET SIDE

# NOTES:

- 1. ALL MATERIAL TO MEET MANUFACTURER SPECIFICATIONS.
- ALL FILTER SOCKS SHALL BE 12" DIAMETER OR LARGER. THE CONTRACTOR SHALL MAINTAIN THE COMPOST FILTER BERM IN A FUNCTIONAL CONDITION AT ALL TIMES AND IT SHALL BE ROUTINELY INSPECTED.

FILTER COMPOST MATERIAL

AS PER SPECIFICATIONS.

- 4. WHERE THE BERM REQUIRES REPAIR, IT WILL BE ROUTINELY REPAIRED.
- 5. THE CONTRACTOR SHALL REMOVE SEDIMENTS COLLECTED AT THE BASE OF THE BERM WHEN THEY REACH 1/3 OF THE EXPOSED HEIGHT OF THE BERM, OR AS DIRECTED BY THE
- 6. THE COMPOST FILTER BERM WILL BE REMOVED ON SITE WHEN NO LONGER REQUIRED, AS DETERMINED BY THE OWNERS.
- 7. INSTALL PERPENDICULAR TO FLOW.

MAINTENANCE NOTES:

TOP OF CHANNEL/BANK

FILTER SOCK SHALL BE PLACED

ACROSS THE ENTIRE WIDTH OF

PERPENDICULAR TO THE FLOW

THE CHANNEL

**FILTER** 

SOCK

CHANNEL PLACEMENT


FILTER

SOCK

FILTER


SOCK


- 1. TRAFFIC SHALL NOT BE PERMITTED TO CROSS FILTER
- 2. ACCUMULATED SEDIMENT SHALL BE REMOVED WHEN IT REACHES 1 OF THE EXPOSED HEIGHT OF THE PRACTICE AND DISPOSED OF IN ACCORDANCE WITH THE SWPPP.
- SOCKS SHALL BE INSPECTED WEEKLY AND AFTER EACH RUNOFF EVENT. DAMAGED SOCKS SHALL BE REPAIRED IN THE MANNER REQUIRED BY THE MANUFACTURER OR REPLACED WITHIN 24 HOURS OF
- INSPECTION NOTIFICATION. BIODEGRADABLE FILTER SOCKS SHALL BE REPLACED AFTER 6 MONTHS; PHOTO-DEGRADABLE FILTER SOCKS AFTER 1 YEAR. POLY-PROPYLENE SOCKS SHALL BE REPLACED ACCORDING TO THE
- MANUFACTURER'S RECOMMENDATIONS. UPON STABILIZATION OF THE AREA CONTRIBUTORY TO THE SOCK, STAKES SHALL BE REMOVED. THE SOCK SHALL BE REMOVED. FOR REMOVAL THE MESH CAN BE CUT AND COMPOST SPREAD AS AN ADDITIONAL



AT GRADE PLACEMENT

COMPOST FILTER SOCK DETAIL SCALE: N.T.S.






TYPICAL OUTFALL ON SLOPE

TYPICAL CULVERT OUTFALL RIP RAP

EXISTING OR PROPOSED FINISHED GRADE ┌ 1'-0" MIN. 4"-TOPSOIL, SEED SIDE SLOPES AND BOTTOM

TYPICAL GRASS DRAINAGE SWALE



<u> IGHT STONE-LINED DRAINAGE CHANNEL</u> SCALE: N.T.S.

SILT FENCE SCALE: N.T.S.

Champlain Hudson **Power Express** 








IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ALTERED THE ALTERING ENGINEER ARCHITECT LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

					SEGMI	ENT	LAIN HO 3 - PACK ON AND S	AGE	2 - FOF	RT A	NN	TO KII
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	JJE	JPR								
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY:	JJE	DESIGNED BY	': JTM	APPROVED	BY:	JPR F	SCALE REV. NO.

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY **EROSION AND SEDIMENT CONTROL DETAILS** 

**KIEWIT PROJECT NO.** 21162 CHA PROJECT NO. 066076 DRAWING NO.

C-601





6' LONG 13 GAUGE RUST PROOF STEEL FENCE POST WITH STABILIZING ANCHOR PLATES -CONSTRUCTION 3/4" POLYPROPYLENE TWIST ROPE, YELLOW BARRIER ROPE 8' O.C. MAX. -WARNING SIGN (SEE ADJACENT DETAIL) (SIGNS SPACED AT 48' ON CENTER±) EXISTING GRADE ELEVATION

1. CONSTRUCTION BARRIER FENCE SHALL BE INSTALLED IN THE LOCATIONS SHOWN ON THE PLANS PRIOR TO BEGINNING ANY WORK ADJACENT TO THESE AREAS.

2 WETLAND PROTECTION FENCE

2. THE CONTRACTOR SHALL INSTALL AT THE BEGINNING OF THE CONTRACT, AND MAINTAIN THROUGHOUT ITS DURATION.





STAPLE OR STAKE PER-MANUFACTURER'S RECOMMENDATIONS NORTH AMERICAN GREEN -ECB, MIRAFI MIRAMAT OR APPROVED EQUAL TOE TO BE BACKFILLED WITH COMPACTED EARTH

EROSION CONTROL BLANKETS TO BE INSTALLED ON SLOPES 3:1 OR GREATER (TYP.)

3 EROSION CONTROL BANK STABILIZATION DETAIL

INLET PROTECTION

50' MINIMUM FROM WETLANDS/WATERBODIES PUMP -— TIE DOWN **DISCHARGE** SPOUT - WATER

SEDIMENT\_ DEWATERING FILTERED —V -2' WIDE x 1' HIGH #2 STONE BERM (TYP)— #2 STONE BERM AGGREGATE OR STRAW —

SIDE VIEW

NOTE: THE SEDIMENT DEWATERING BAG WILL BE MANUFACTURED IN THE U.S.A. FROM A NONWOVEN POLYPROPYLENE FABRIC THAT MEETS OR EXCEEDS THE FOLLOWING SPECIFICATIONS:

# SEDIMENT DEWATERING BAG SPECIFICATIONS

UNDERLAY


(FOR ADDED FLOW)

		_	
Mechanical Properties	Test Method	Units	MARV
Grab Tensile Strength	ASTM D 4632	kN (lbs)	0.9 (205) × 0.9 (205)
Grab Tensile Elongation	ASTM D 4632	%	50 × 50
Puncture Strength	ASTM D 4833	kN (lbs)	0.58 (130)
Mullen Burst Strength	ASTM D 3786	kPa (psi)	2618 (380)
Trapezoid Tear Strength	ASTM D 4533	kN (lbs)	0.36 (80) X 0.36 (80)
UV Resistence	ASTM D 4355	%	70
Apparent Opening Size	ASTM D 4751	Mm (US Std Sieve)	0.180 (80)
Flow Rate	ASTM D 4491	1/min/m² (gal/min/ft²)	3866 (95)
Permittivity	ASTM D 4491	Sec <sup>-1</sup>	1.2

SEDIMENT DEWATERING BAG



- 1. STONE SIZE-USE AASHTO M43 SIZE 3 COARSE AGGREGATE, OR RECLAIMED OR RECYCLED CONCRETE EQUIVALENT.
- 2. LENGTH NOT LESS THAN 50 FEET (EXCEPT ON A SINGLE RESIDENCE LOT WHERE A 30 FOOT MINIMUM LENGTH WOULD
- 3. THICKNESS NOT LESS THAN 12".
- WIDTH TWELVE (12) FOOT MINIMUM, BUT NOT LESS THAN THE FULL WIDTH AT POINTS WHERE INGRESS OR EGRESS OCCURS. PAVEMENT TWENTY-FOUR (24) FOOT IF SINGLE ACCESS TO SITE.
  - 5. WOVEN GEOTEXTILE FABRIC WILL BE PLACED OVER THE ENTIRE AREA PRIOR TO PLACING OF STONE.
  - 6. EXISTING ROAD SIDE DRAINAGE SHALL BE MAINTAINED.
  - 7. SURFACE WATER ALL SURFACE WATER FLOWING OR DIVERTED TOWARD CONSTRUCTION ENTRANCES SHALL BE PIPED BENEATH THE ENTRANCE. IF PIPING IS IMPRACTICAL, A MOUNTABLE BERM WITH 5:1 SLOPES WILL BE PERMITTED.
  - 8. MAINTENANCE-THE ACCESS SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHTS-OF-WAY. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH ADDITIONAL STONE AS CONDITIONS DEMAND AND REPAIR AND/OR CLEANOUT OF ANY MEASURES USED TO TRAP SEDIMENT. ALL SEDIMENT OR STONE SPILLED, DROPPED, WASHED, OR TRACKED ONTO PUBLIC RIGHTS-OF-WAY MUST BE REMOVED IMMEDIATELY.
  - 9. WHEN WASHING IS REQUIRED, IT SHALL BE DONE ON A AREA STABILIZED WITH STONE AND WHICH DRAINS INTO AN APPROVED SEDIMENT TRAPPING DEVICE.
  - 10. PERIODIC INSPECTION AND NEEDED MAINTENANCE SHALL BE PROVIDED AFTER EACH RAIN.



TYPICAL SECTION

DISPOSED OF OFF SITE. 3. DISPOSAL OF THE HARDENED MATERIAL SHALL BE OFF-SITE IN A CONSTRUCTION/DEMOLITION

A CONTAINMENT VESSEL AND PROPERLY

INSPECTED DAILY. DAMAGED OR LEAKING

FACILITATES SHALL BE DEACTIVATED AND

A STABILIZED AREA SUCH AS A GRASS

REMOVED WHEN 75% OF THE STORAGE

FILTER STRIP.

LANDFILL.

REPAIRED OR REPLACED IMMEDIATELY. EXCESS

RAINWATER THAT HAS ACCUMULATED OVER

HARDENED CONCRETE SHALL BE PUMPED TO

ACCUMULATED HARDENED MATERIAL SHALL BE

CAPACITY OF THE STRUCTURE IS FILLED. ANY

EXCESS WASH WATER SHALL BE PUMPED INTO

4. THE PLASTIC LINER SHALL BE REPLACED WITH EACH CLEANING OF THE WASHOUT FACILITY.

5. INSPECT THE PROJECT SITE FREQUENTLY TO ENSURE THAT NO CONCRETE DISCHARGES ARE TAKING PLACE IN NON-DESIGNATED AREAS.

6. LOCATION(S) TO BE DETERMINED IN THE FIELD BY THE OWNER'S REPRESENTATIVE

7. CONCRETE WASHOUTS SHALL NOT BE LOCATED WITHIN 200' OF ANY KNOWN WELL.

6 CONCRETE WASHOUT AREA SCALE: N.T.S.

6" MIN DEPTH

AGGREGATE

ALL AROUND

5 | STABILIZED CONSTRUCTION ACCESS

PER PLAN OR 50' MIN.

PLAN VIEW

WOVEN GEOTEXTILE

EXISTING GROUND

12' MIN.


Champlain Hudson Power Express







ARE ACTING UNDER THE DIRECTION OF A LICENSED AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY SPECIFIC DESCRIPTION OF THE ALTERATION.



CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY **EROSION AND SEDIMENT CONTROL DETAILS** 

**KIEWIT PROJECT NO.** 21162 CHA PROJECT NO. 066076 DRAWING NO.

C-602

AS NOTED DATE 03/22/2023

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ALTERED THE ALTERING ENGINEER ARCHITECT LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A

- EXISTING

20'

**EXISTING** 

PAVEMEN1

20'

20'

#### DEWATERING PROCEDURES:

TRAPPED WATER WITHIN THE TRENCH SHALL BE DISCHARGED INTO A PORTABLE SEDIMENT TANK OR SEDIMENT FILTER BAGS LOCATED AWAY FROM THE WATERBODY TO PREVENT SILT-LADEN WATER FROM FLOWING INTO THE WATERBODY.

#### DAM AND PUMP CROSSING PROCEDURES:

BEFORE THE INITIATION OF ANY IN-STREAM ACTIVITIES, ALL MATERIAL ASSOCIATED WITH THE DAM AND PUMP SITE SET-UP MUST BE ON-HAND. THESE MATERIALS INCLUDE, BUT ARE NOT LIMITED TO THE FOLLOWING:

#### B)DOWNSTREAM SPLASH PLATE

C)PUMPS (PRIMARY AND SECONDARY) AND HOSES

SEDIMENT INTO THE SUMP INTAKE, HOSE AND PUMP

D)FUEL FOR PUMPS (STORED AT LEAST ONE HUNDRED (100) FEET FROM WATERBODY) E)SPILL PREVENTION AND CONTROL MATERIALS (INCLUDING SECONDARY CONTAINMENT FOR PUMPS LOCATED WITHIN ONE HUNDRED (100) FEET OF WETLAND OR WATERBODY)

ONCE THE NECESSARY MATERIALS ARE ON-LOCATION, SITE SET-UP MAY BEGIN. THE FIRST STEP IS TO SELECT AN APPROPRIATE LOCATION FOR THE PUMP INTAKE HOSE(S) TO BE POSITIONED. DEPENDING UPON THE CHANNEL CHARACTERISTICS, EITHER A NATURALLY OCCURRING DEEP SPOT OR CHANNEL WILL BE SELECTED AS A "SUMP" OR A SUMP MAY NEED TO BE CREATED TO PROVIDE SUFFICIENT WATER DEPTH FOR THE SCREENED HOSE INTAKE(S). IF A NATURAL SUMP IS NOT AVAILABLE FOR THE INTAKE HOSE, AN IN-STREAM SUMP WILL BE CREATED BY EXCAVATING WITHIN THE STREAM CHANNEL AND SURROUNDING THE EXCAVATION USING SANDBAGS.

#### THE FOLLOWING BMPS SHALL BE IMPLEMENTED AT THE INTAKE OR SUMP SITE:

A)ALL EQUIPMENT, MATERIAL, AND CONSTRUCTION PERSONNEL NECESSARY FOR THE CROSSING SHALL BE ON-SITE BEFORE SET-UP BEGIN

SB)UPON COMPLETION OF THE WATERBODY CROSSING ANY SANDBAGS UTILIZED FOR A SUMP SHALL BE REMOVED AND THE STREAM CHANNEL RESTORED TO PRE-CONSTRUCTION CONDITION C)THE SUMP SHALL BE OF SUFFICIENT DEPTH TO PREVENT THE ENTRAINMENT OF EXCESSIVE AMOUNTS OF

DURING THE ASSEMBLY OF THE UPSTREAM AND DOWNSTREAM WATER BARRIERS, THE PUMPING NETWORK SHALL BE SETUP TO BEGIN THE TRANSFER OF WATER AROUND THE CONSTRUCTION WORK AREA.

THE PUMP INTAKE AND DISCHARGE HOSES SHALL BE APPROPRIATELY PLACED AND OF SUFFICIENT LENGTH, BASED UPON SITE-SPECIFIC CONDITIONS. THE INTAKE HOSE SHALL BE SCREENED TO PREVENT THE ENTRAINMENT OF FISH. DISCHARGE HOSES SHALL BE PROVIDED WITH SUPPORT OVER THE DITCH-LINE AS NEEDED TO PREVENT EXCESSIVE SAGGING AND REDUCTION OF PUMPING CAPACITY.

THE NUMBER AND SIZES OF PUMPS TO BE USED AT ANY CROSSING SHALL BE DEPENDENT UPON THE VOLUME OF WATER FLOWING AT THE TIME THE CROSSING IS MADE.

# BMPS TO BE IMPLEMENTED DURING PUMP SET-UP INCLUDE:

A)PUMPS SHALL BE FUELED PRIOR TO PLACING THEM IN POSITION

B)IF IT IS NECESSARY TO REFUEL DURING THE PUMP OPERATION, EXTRA CARE SHALL BE TAKEN TO AVOID SPILLAGE AND SPILL CONTROL MATERIALS WILL BE READILY AVAILABLE ON SITE

C)SECONDARY CONTAINMENT SHALL BE PLACED UNDER THE PUMPS AS AN ADDITIONAL PRECAUTIONARY

MEASURE TO PROTECT AGAINST ACCIDENTAL LEAKAGE OR SPILL D)FUEL FOR FILLING THE PUMPS SHALL NOT BE STORED WITHIN ONE HUNDRED (100) FEET OF THE WATERBODY

E)THE INTAKE HOSE SHALL BE SCREENED TO PREVENT THE ENTRAINMENT OF FISH F)THE END OF THE DISCHARGE HOSE SHALL BE MOUNTED UPON A SPLASH PLATE OR SIMILAR DEVICE OR IN A MANNER THAT WILL DISSIPATE THE ENERGY OF THE DISCHARGING WATER AND REDUCE OR ELIMINATE

STREAMBED SCOUR G)IF HOSES CROSS THE TEMPORARY ACCESS ROAD, THEY SHALL BE PROTECTED FROM TRAVELING EQUIPMENT H)PUMP(S) SHALL BE OF SUFFICIENT CAPACITY TO TRANSFER TWICE THE CAPACITY OF THE ENTIRE

STREAMFLOW AROUND THE CONSTRUCTION WORK AREA I)RESERVE OR BACKUP PUMP(S) SHALL BE KEPT ON SITE AT ALL TIMES.

NECESSARY TO PREVENT OVERTOPPING OF THE DAMS.

# WATER BARRIER INSTALLATION

BETWEEN THE PUMP HOSE INTAKE OR SUMP HOLE AREA AND THE TRENCH, AS WELL AS DOWNSTREAM OF THE TRENCH, DAMS OF RELATIVELY IMPERVIOUS MATERIAL SHALL BE INSTALLED. THE UPSTREAM DAM SHALL BE COMPLETED FIRST. EVERY REASONABLE EFFORT SHALL BE MADE TO CONSTRUCT THE DAMS AS WATER TIGHT AS POSSIBLE.

THE FOLLOWING BMPS WILL BE IMPLEMENTED DURING WATER BARRIER INSTALLATION: A)DAMS SHALL BE CONSTRUCTED OF EITHER SANDBAGS, WATER BLADDERS, STEEL PLATES, PORTA-DAMS OR

EQUIVALENT OR "JERSEY BARRIERS" AND PLASTIC SHEETING OR A COMBINATION THEREOF B)THE DAMS SHALL BE CONSTRUCTED OF SUFFICIENT HEIGHT TO ALLOW ADEQUATE FREEBOARD UNDER REASONABLY EXPECTED WATER LEVELS OR FLOWS AND PROVIDE FOR SOME IMPOUNDMENT OF WATER

C)PRIOR TO COMPLETION OF THE DAMS, THE PUMP(S) MUST BE STARTED IN ORDER TO PROVIDE DOWNSTREAM FLOW OF WATER AROUND THE CONSTRUCTION WORK AREA D)THE RATE OF PUMPING SHALL BE MONITORED TO MINIMIZE DRAINING OF THE INTAKE SUMP AND THE RESULTING CESSATION IN FLOW. ALTERNATIVELY, PUMPING SHALL BE MONITORED AND INCREASED AS

(IF NECESSARY) SPOIL PILE 10' FROM TOP OF BANK - SANDBAG COFFERDAM OPEN PIPELINE TRENCH ---TRENCH PLUG--SPARE PUMP - FILTER SOCK - SPILL CONTAINMENT DEVICE EROSION AND SEDIMENTATION CONTROL TO BE PLACED ACROSS THE EQUIPMENT CROSSING AT KEEP EQUIPMEN THE END OF THE DAY CROSSING FREE OF MUD/SOIL \_ \_ \_ \_ \_ EQUIPMENT CROSSING WOOD MAT BRIDGE \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ STREA BANK STRAW BALES OR SAND BAGS-TO BE PLACED DURING NO CONSTRUCTION ACTIVITY

— INTAKE HOSE

**GENERAL SEQUENCE:** 

WATER AT INTAKE.

1. SCHEDULE CONSTRUCTION DURING LOW FLOW PERIOD, IF POSSIBLE.

CAPACITY OR ANTICIPATED FLOW. HAVE STANDBY PUMP ON SITE.

DEPENDING ON STREAM FLOW, DIG SUMP HOLE TO CONCENTRATE

PLATING OR A COMBINATION OF BOTH. INSTALL DOWNSTREAM DAM,

2. SET UP PUMP AND HOSE AS SHOWN, OR USE PRACTICAL

ALTERNATIVES. PUMP SHOULD HAVE TWICE THE PUMPING

3. INSTALL UPSTREAM DAM COMPOSED OF SANDBAGS, METAL

4. AFTER DAMS ARE IN PLACE, IT MAY BE NECESSARY TO USE

7. RESTORE STREAM BANKS AND APPROACHES FOR A MINIMUM

5. EXCAVATE TRENCH AND LOWER IN PIPE UNDER HOSE. MOVE HOSE

6. DISMANTLE DOWNSTREAM DAM. THEN UPSTREAM DAM. KEEP PUMP

AS REQUIRED OR DISCONNECT, IF TEMPORARY FLOW BLOCKAGE IS

DISTANCE OF AT LEAST 50 FEET FROM THE STREAM EDGES AND

PERMANTENTLY STABLIZE WITHIN 1 DAY OF INITIAL RESTORATION.

IF REQUIRED, TO KEEP STREAM BED DRY.

ACCEPTABLE. BACKFILL TRENCH.

RUNNING TO MAINTAIN STREAM FLOW.

ADDITIONAL PUMPS TO HANDLE STREAM FLOW.


-FILTER SOCK

OR HAY BALES

DAM AND PUMP AROUND STREAM CROSSING SCALE: N.T.S.

- DISCHARGE

HOSE



LSANDBAG COFFERDAM DETAIL SCALE: N.T.S.

**ENERGY DISSIPATER AT** 

THE END OF DISCHARGE

1. SAND BAGS SHALL BE FILTER FABRIC TYPE AND BE DOUBLE BAGGED. 2. PORTADAM, BY PORTADAM, INC. SHALL BE CONSIDERED ACCEPTABLE SUBSTITUTE TO SAND BAGS

Champlain Hudson **Power Express** 





IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ALTERED THE ALTERING ENGINEER ARCHITECT LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THFIR SIGNATURE. THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

					SEGMENT 3 - PACKAGE 2 - FORT ANN TO EROSION AND SEDIMENT CONTROL	KII
					EROSION AND SEDIMENT CONTROL	וט .
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	JJE	JPR		
lo.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: JTM DESIGNED BY: JTM APPROVED BY: JPR REV.	

ROW LIMIT

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY **EROSION AND SEDIMENT CONTROL DETAILS** 

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

C-603

1. TIMBER MATS SHOULD BE INSTALLED IN WETLANDS AND OTHER AREAS IF NECESSARY TO

PREVENT RUTTING. 2. BASED ON ACTUAL SITE CONDITIONS, MULTIPLE LAYERS OF TIMBER MATS MAY BE REQUIRED.

3. TIMBER MAT SURFACE SHOULD BE LEVEL TO PREVENT EQUIPMENT AND VEHICLES FROM SLIDING OFF DURING MUDDY OR ICING CONDITIONS, AND PREVENT TIMBERS FROM BREAKING. 4. SEDIMENT TRACKED ONTO TIMBER MATTING SHOULD BE REMOVED AS NECESSARY TO

PREVENT SEDIMENT FROM ENTERING WETLAND DURING RAIN EVENTS. SEDIMENT SHOULD BE REMOVED TO A STABILIZED SOIL STOCKPILE OR OTHER APPROVED LOCATION. 5. PERIMETER EROSION AND SEDIMENT CONTROLS ARE REQUIRED TO BE INSTALLED PRIOR TO

PLACING TIMBER MATTING. 6. UNLESS PERMITTED FROM REMOVAL, STUMPS WITHIN THE WETLAND SHOULD REMAIN. THIS

MAY REQUIRE ADDITIONAL TIMBERS TO BRIDGE ABOVE.

7. UPON REMOVAL OF TIMBER MATTING ALL SPLINTERED WOOD SHOULD BE REMOVED. IF EXPOSED SOILS ARE PRESENT STRAW MULCH SHOULD BE APPLIED.

NOTE: GEOTEXTILE FABRIC TO BE INSTALLED UNDER MATTING (TYP)

APPROXIMATE WETLAND BOUNDARY - TIMBER MAT WATER BAR (IF NECESSARY) PLAN VIEW 4' 12" SECTION A-A' APPROXIMATE WETLAND - EXISTING GRADE BOUNDARY — TRANSITION TO TIMBER MATS AS NECESSARY SECTION B-B'

1. TIMBER MATS SHOULD BE INSTALLED IN WETLANDS AND OTHER AREAS IF NECESSARY TO

PREVENT RUTTING. BASED ON ACTUAL SITE CONDITIONS, MULTIPLE LAYERS OF TIMBER MATS MAY BE REQUIRED.

3. TIMBER MAT SURFACE SHOULD BE LEVEL TO PREVENT EQUIPMENT AND VEHICLES FROM SLIDING OFF DURING MUDDY OR ICING CONDITIONS, AND PREVENT TIMBERS FROM BREAKING. 4. SEDIMENT TRACKED ONTO TIMBER MATTING SHOULD BE REMOVED AS NECESSARY TO PREVENT SEDIMENT FROM ENTERING WETLAND DURING RAIN EVENTS. SEDIMENT SHOULD BE

REMOVED TO A STABILIZED SOIL STOCKPILE OR OTHER APPROVED LOCATION. 5. PERIMETER EROSION AND SEDIMENT CONTROLS ARE REQUIRED TO BE INSTALLED PRIOR TO

PLACING TIMBER MATTING. 6. UNLESS PERMITTED FROM REMOVAL, STUMPS WITHIN THE WETLAND SHOULD REMAIN. THIS

MAY REQUIRE ADDITIONAL TIMBERS TO BRIDGE ABOVE. 7. UPON REMOVAL OF TIMBER MATTING ALL SPLINTERED WOOD SHOULD BE REMOVED. IF

EXPOSED SOILS ARE PRESENT STRAW MULCH SHOULD BE APPLIED.

NOTE: GEOTEXTILE FABRIC TO BE INSTALLED UNDER MATTING (TYP)

- NYSDOT #703-0202 -#4 STONE — TIMBER MATS WATERWAY

TIMBER MAT SECTIONS USED FOR SUPPORTS IN CHANNEL TIMBER MATS 4% MAXIMUM 4% MAXIMUM - WATERWAY GEOTEXTILE FABRIC (MIRAFIT EXISTING GRADE 500X OR APPROVED EQUAL) — - DIVERSION SWALE OR WATERBAR ADDITIONAL MATS FOR STREAM BANK PROTECTION AS NEEDED -SECTION A-A'

1. IN-STREAM EXCAVATION SHOULD BE COMPLETED IN ACCORDANCE WITH "TEMPORARY ACCESS WATERWAY CROSSING" ON PAGE 2.32 OF THE 2016 NYSDEC STANDARDS AND SPECIFICATIONS FOR EROSION AND SEDIMENT CONTROL (OR NEWEST VERSION) AND THE CERTIFICATE.

THE CONSTRUCTION OF ANY CROSSING SHOULD NOT CAUSE A SIGNIFICANT WATER LEVEL DIFFERENCE BETWEEN THE UPSTREAM AND DOWNSTREAM WATER SURFACE ELEVATIONS. IN-STREAM WORK WILL BE PROHIBITED WITHIN COLD WATER TROUT FISHERIES FROM

OCTOBER 1 TO MAY 31. 3. ALL FILL MATERIALS ASSOCIATED WITH THE ROADWAY APPROACH SHOULD BE LIMITED TO A MAXIMUM HEIGHT OF 2 FEET ABOVE THE EXISTING FLOOD PLAIN ELEVATION.

4. A WATER DIVERTING STRUCTURE SUCH AS A SWALE OR WATER BAR SHOULD BE CONSTRUCTED (ACROSS THE ROADWAY ON BOTH ROADWAY APPROACHES) 50 FEET (MAXIMUM) ON EITHER SIDE OF THE WATERWAY CROSSING. THIS WILL PREVENT ROADWAY SURFACE RUNOFF FROM DIRECTLY ENTERING THE WATERWAY. THE 50 FEET MEASURED IS MEASURED FROM THE TOP OF THE WATERWAY BANK. IF THE ROADWAY APPROACH IS CONSTRUCTED WITH A REVERSE GRADE AWAY FROM THE WATERWAY, A SEPARATE DIVERTING STRUCTURE IS NOT REQUIRED.

5. ALL CROSSINGS SHOULD HAVE ONE TRAFFIC LANE. THE MINIMUM WIDTH SHOULD BE 12 FEET WITH A MAXIMUM WIDTH OF 20 FEET.

TIMBER MATTING
SCALE: N.T.S.









IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ACHITECT, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	JJE	JPR		LAIN HU [3-PACKA0 WETLAND	GE	2 - FOR	TAN	N TO K	
										SCALE	—
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: JJE	DESIGNED BY:	JTM	APPROVED	BY: JP	REV. NO.	

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY WETLAND CROSSING DETAILS

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

C-611


WATER SHALL BE DIVERTED OFF THE DISTURBED RIGHT-OF-WAY AT AN OUTSLOPE OF THREE TO FIVE PERCENT BY CONSTRUCTING DIVERSION DITCH ACCORDING TO THE FOLLOWING


- 1. AT THE PROPOSED INTERCEPTOR DITCH LOCATION ESTABLISH A HORIZONTAL CONTOUR LINE (USING A POCKET TRANSIT OR HAND LEVEL) WHICH EXTENDS COMPLETELY ACROSS THE DISTURBED RIGHT-OF-WAY. THIS LINE WILL ALWAYS BE PERPENDICULAR TO THE DIRECTION OF WATER FLOW AND SHOULD BE PARALLEL TO THE MAP CONTOURS SHOWN ON THE PLAN DRAWINGS.
- 2. DETERMINE WHICH SIDE OF THE RIGHT-OF-WAY IS BEST SUITED FOR THE DITCH OUTLET (EVALUATE VEGETATION DENSITY, LOCAL TOPOGRAPHY, ETC.) AND DEVIATE DIKE AWAY FROM THE HORIZONTAL CONTOUR LINE SLIGHTLY DOWNWARD TOWARD THE SELECTED OUTLET SIDE MAINTAINING A THREE TO FIVE PERCENT SLOPE. AS AN EXAMPLE, THE CHART AT THE RIGHT SHOWS DIMENSIONS ASSUMING A FOUR PERCENT
- 3. WHEN OUTLETTING NEAR WATER BODIES, STREAMS, DITCHES, & CROP FIELDS, A FILTER FENCE OR STRAW BALE FENCE SHOULD BE PLACED ON OUTLET END OF THE DIVERSION

#### TEMPORARY DRAINAGE DITCH


- 1. TEMPORARY DIVERSION DITCH SHOULD BE BUILT SIMILAR TO THE PERMANENT DITCH
- CONFIGURATION BUT THE DIMENSION CAN BE SCALED BACK. 2. MAXIMUM HEIGHT SHOULD BE 12" AND SHOULD BE COMPACTED.
- 3. SPACING BETWEEN DIVERSION DITCHES AND SKEW OF THE DIVERSION DITCHES CAN VARY FROM THE PERMANENT DIVERSION DITCHES.
- 4. WHEN CONSTRUCTING TEMPORARY DIVERSION DITCHES THEY SHOULD BE FUNCTIONAL, WHILE MAINLINE CONSTRUCTION IS PROCEEDING, UNTIL RESTORATION BEGINS AND PERMANENT DIVERSION DITCHES ARE THEN CONSTRUCTED.

4% FLOV	V CHART
HORIZONTAL DISTANCE BETWEEN WATERBAR INLET & OUTLET (FEET)	ELEVATION DISTANCE BETWEEN WATERBAR INLET AND OUTLET (FEET)
75	3
100	4
125	5
150	6
175	7





# PERMANENT DIVERSION DITCH DETAIL SCALE: N.T.S.



2 MINIMAL HEIGHT & WIDTH DIMENSIONS FOR WATERBAR CONSTRUCTION SCALE: N.T.S.

**Power Express** 







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

						PLAIN HU T3-PACKA WAT	GE		ORT /	ANN	TO KII
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	JJE	JPR	-						
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: JTM	DESIGNED BY:	JTM	APPRO'	VED BY:	JPR	SCALE REV. NO.


CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY WATERBAR DETAILS

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. DRAWING NO.

C-612

NO. 3 STONE, NO. 4 STONE OR

WETLAND WORKING SURFACE PLAN - OPTION B




**SECTION** NOT TO SCALE

# NOTES:

- 1. UNDERCUT AND REMOVE TOP SOIL PRIOR TO PLACING GEOTEXTILE FABRIC.
- 2. A LAYER OF CLEAN CRUSHED STONE SHALL BE LAID ON TOP OF THE GEOTEXTILE FABRIC.
- 3. GEOTEXTILE FABRIC SHALL EXTEND AT LEAST 3 FT TO 5 FT BEYOND THE EDGE OF STONE PLACEMENT TO MINIMIZE STONE ENTERING THE WETLAND AND FACILITATE REMOVAL OF THE ROAD.
- 4. SUITABLE CROSS DRAINING SHALL BE PROVIDED ACROSS THE ROAD
- FOR STREAM CHANNELS AND SURFACE FLOW. 5. AREA TO BE RESTORED IN ACCORDANCE WITH THE EM&CP SECTION 14

# **GENERAL NOTES:**

- 1. TIMBER:
- A. TIMBER SHALL BE SELECT STRUCTURAL MIXED OAK WITH A MINIMUM BENDING STRESS OF 1250 PSI OR BETTER.
- 2. CONTRACTOR TO VERIFY ALL DIMENSIONS AND SITE CONDITIONS PRIOR TO COMMENCING WORK. ANY ERRORS, OMISSIONS, OR UNUSUAL CONDITIONS ARE TO BE REPORTED TO THE TEMPORARY STRUCTURES AND CONSTRUCTION DEVICES ENGINEER IMMEDIATELY.



# NOTES:

- TIMBER MATS SHOULD BE INSTALLED IN WETLANDS AND OTHER AREAS IF NECESSARY TO
- PREVENT RUTTING. 2. BASED ON ACTUAL SITE CONDITIONS, NUMBER OF TIMBER MAT LAYERS TO BE
- DETERMINED ON SITE. 3. TIMBER MAT SURFACE SHOULD BE LEVEL TO PREVENT EQUIPMENT AND VEHICLES FROM SLIDING OFF DURING MUDDY OR ICING CONDITIONS, AND PREVENT TIMBERS FROM BREAKING.
- 4. SEDIMENT TRACKED ONTO TIMBER MATTING SHOULD BE REMOVED AS NECESSARY TO PREVENT SEDIMENT FROM ENTERING WETLAND DURING RAIN EVENTS. SEDIMENT SHOULD BE REMOVED TO A STABILIZED SOIL STOCKPILE OR OTHER APPROVED LOCATION.
- 5. PERIMETER EROSION AND SEDIMENT CONTROLS ARE REQUIRED TO BE INSTALLED PRIOR TO PLACING TIMBER MATTING.
- 6. UNLESS PERMITTED FROM REMOVAL, STUMPS WITHIN THE WETLAND SHOULD REMAIN. THIS
- MAY REQUIRE ADDITIONAL TIMBERS TO BRIDGE ABOVE. UPON REMOVAL OF TIMBER MATTING ALL SPLINTERED WOOD SHOULD BE REMOVED. IF
- EXPOSED SOILS ARE PRESENT STRAW MULCH SHOULD BE APPLIED.
- 8. IF DEEMED NECESSARY BY CONSTRUCTION IN THE FIELD, GEOTEXTILE FABRIC TO BE
- INSTALLED UNDER MATTING. (TYP) 9. AREA TO BE RESTORED IN ACCORDANCE WITH THE EM&CP SECTION 14.









IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ALTERED. THE ALTERING ENGINEER. ARCHITECT. LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

1	04/06/2023	REVISED PER DPS COMMENTS	JTM	JPR
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	JJE	JPR
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY WETLAND WORKING SURFACE PLAN


DRAWN BY: XXX DESIGNED BY: XXX APPROVED BY: XXX REV. NO.


GRADED AGGREGATE BASE


KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

C-613

AS NOTED DATE XXX









**DUCTBANK IN ROADWAY** 

- 1. SLOPING, BENCHING, OR SHORING SHALL BE IN ACCORDANCE WITH OSHA EXCAVATION STANDARDS, 29 CFR PART 1926, SUBPART P. AT LOCATIONS WHERE THE TRENCH IS NOT SHORED, SLOPING AND/OR BENCHING WILL DEPEND ON TYPE OF SOILS ENCOUNTERED ON SITE. SLOPE FROM EDGE OF ROADWAY TO BOTTOM OF EXCAVATIONS MAY BE FLATTER THAN 2:1 (H: V) FOR AASHTO HS-20 LOADING. THE CONTRACTOR SHALL BE
- RESPONSIBLE FOR EVALUATING SLOPE STABILITY BASED ON ACTUAL EQUIPMENT FOR SITE OPERATIONS AS DETERMINED BY A GEOTECHNICAL ENGINEER.
- 2. SEE DETAIL 4 ON DETAIL SHEET C-631 FOR PAVEMENT TRANSITION DETAIL. 3. SEE SHEET C-631 FOR SURFACE RESTORATION DETAILS.
- 4. SEE PLAN AND PROFILE SHEETS FOR CONDUIT & TO & AND DUCTBANK SIZE TRENCH WIDTH (NOTE ABOVE PROFILE VIEW).

1 TYPICAL TRENCHING DETAILS
NOT TO SCALE














IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ACHITECT, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A
SPECIFIC DESCRIPTION OF THE ALTERATION.

0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	JJE	JPR	SEGMENT 3 - PACKAGE 2 - FORT ANN TO KILL  TRENCH CROSS SECTION DETAIL
				4.00	SCALE
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	P DRAWN BY: JJE DESIGNED BY: JTM APPROVED BY: JPR REV. NO.


CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY TRENCH CROSS SECTION DETAILS


KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

C-621




EXISTING, MINOR REFURBISHMENT






NOTE: CLEARING WIDTH DEPICTED ARE APPROXIMATE AND ASSUME THERE ARE NO ENVIRONMENTAL OR PROPERTY CONSTRAINTS. THE PROPOSED LIMITS OF WORK, CLEARING AND DISTURBANCE BASED ON FIELD CONDITIONS ARE DEPICTED ON THE EROSION AND SEDIMENT CONTROL PLANS.



TYPE 2 EXISTING, MAJOR REFURBISHMENT



TYPE 4A WETLAND









IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.


	03/22/2023		JJE	IDD	CHAMPLAIN HUDSON POWER EX SEGMENT 3 - PACKAGE 2 - FORT ANN TO KIN TYPICAL ACCESS ROAD CROSS SECT
	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	JJE	JPR	
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: JJE DESIGNED BY: JTM APPROVED BY: JPR SCALE REV. NO.

HAMPLAIN HUDSON POWER EXPRESS EGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY TYPICAL ACCESS ROAD CROSS SECTIONS

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

C-622

TYPE 4 REFURBISH ACCESS NEXT TO RAIL. BUILD TEMP ACCESS AT TOE OF SLOPE



TYPE 5 BUILD TEMP ACCESS AT TOE OF SLOPE

NOTE: CLEARING WIDTHS DEPICTED ARE APPROXIMATE AND ASSUME THERE ARE NO ENVIRONMENTAL OR PROPERTY CONSTRAINTS. THE PROPOSED LIMITS OF WORK, CLEARING AND DISTURBANCE BASED ON FIELD CONDITIONS ARE DEPICTED ON THE EROSION AND SEDIMENT CONTROL PLANS.









IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

					SEGMENT	LAIN HU [3-PACKA CAL ACCES	GE	2 - FOF	RT ANN	TO KI
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	JJE	JPR						
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: JJE	DESIGNED BY:	JTM	APPROVED	BY: JPR	SCALE REV. NO.
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: JJE	DESIGNED BY:	JTM	APPROVED	BY: JPR	RE

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY TYPICAL ACCESS ROAD CROSS SECTIONS

KIEWIT PROJECT NO.	
21162	
CHA PROJECT NO.	
066076	
DRAWING NO.	

C-623

TYPICAL DUCTBANK SECTION OVER EXISTING CP RAIL CULVERT OUTLET
NOT TO SCALE


NOTES:
1. DUCT BANK TO BE 2.0' MIN ABOVE OR BELOW EXISTING CULVERTS.

Package	Sheet Number	CP Rail Mile Post	Station	Utility	Size "d"	Exist. Ground Elev. (ft.)*	Invert (ft.)*	D (ft.)*	h (ft.)	L (ft.)
Package 2	C-115	68.39	20217+20	Storm Drainage Pipe/Culvert	24"	137.6	121.5	16.1	6.53	10
Package 2	C-116	68.22	20225+96	Storm Drainage Pipe/Culvert	36" x 30"	135.3	124.7	10.6	2.76	11
Package 2	C-124	65.98	20345+93	Storm Drainage Pipe/Culvert	20"	137.4	125.8	11.6	6.3	20
Package 2	C-124	65.87	20351+16	Storm Drainage Pipe/Culvert	18"	137.8	128.1	9.7	4.4	5.5

Champlain Hudson **Power Express** 







					CHAMPLAIN HUDS SEGMENT 3 - PACKAGE TYPICAL CULVE
0 03/22/	2023	ISSUED FOR CONSTRUCTION SUBMISSION	JJE	JPR	

CHAMPLAIN HUDSON POWER EXPRESS KIEWIT PROJECT NO. E 2 - FORT ANN TO KINGSBURY VERT SECTION (1 OF 3)

21162 CHA PROJECT NO. 066076 DRAWING NO.

C-624

AS NOTED DATE

DB APP DRAWN BY: JJE DESIGNED BY: JTM APPROVED BY: JPR REV. NO. DATE SUBMITTAL / REVISION DESCRIPTION

TYPICAL DUCTBANK SECTION UNDER EXISTING CP RAIL CULVERT OUTLET
NOT TO SCALE


1. DUCT BANK TO BE 2.0' MIN ABOVE OR BELOW EXISTING CULVERTS.

Package	Sheet Number	CP Rail Mile Post	Station	Utility	Size "d"	Exist. Ground Elev. (ft.)*	Invert (ft.)*	D (ft.)*	h (ft.)*	L (ft.)
Package 2	C-305/C-305.1/C-305A/C-305A.1	68.66	20203+20	Storm Drainage Pipe/Culvert	60"	140.6	126.1	14.7	22.3	25
Package 2	C-308/C-308A	66.92	20296+00	Storm Sewer	18"	136.8	137.2	-0.3	27.5	21.5
Package 2	C-127	65.1	20390+96	Storm Drainage Pipe/Culvert	48"	126.4	127.4	1.7	22.1	24
Package 2	C-311A	63	20501+97	Storm Drainage Pipe/Culvert	36"	142.4	133.9	13.8	20.6	34.5
Package 2	C-312/C-312A	62.11	20548+88-20549+00	Storm Drainage Pipe/Culvert	48"	136.2	137.7	8.4	17	34
Package 2	C-313A	60.15	20651+66	Storm Drainage Pipe/Culvert	UNKNOWN	142.1	140.5	1.6	22	30.5

Champlain Hudson **Power Express** 








0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	JJE	JPR	SEGME	NT	3 - PA	CKA	GE	2 - F	ORT	ANN	
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: J.	JJE <b>[</b>	ESIGNE	D BY:	JTM	APPRO\	/ED BY	: JPR	SCALE REV. NO.


CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY TYPICAL CULVERT SECTION (2 OF 3)

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

C-625







				11.44*	g. 4111	5 1 5 15 15 15 15	. //. 19	1 75.3		
Package	Sheet Number	CP Rail Mile Post	Station	Utility	Size "d"	Exist. Ground Elev. (ft.)*	Invert (ft.)*	h (ft.)	L (ft.)	x (ft.)
Package 2	C-306/C-306.1/C-306A/C-306A.1	67.66	20255+75	Storm Drainage Pipe/Culvert	12.5' x 10.4'	125.8	121.6	20.2	38.5	32.5
Package 2	C-121	66.8	20301+77	Storm Drainage Pipe/Culvert	18"	124.5	122.8	3.1	21.5	7.2
Package 2	C-122	66.52	20316+90	Storm Drainage Pipe/Culvert	12"	126.5	126.6	2	24.7	4.5
Package 2	C-310/C-310A	64.57	20421+25	Storm Drainage Pipe/Culvert	96"	127.9	120.7	5.2	28	5.2
Package 2	C-129	64.48	20425+91	Storm Drainage Pipe/Culvert	42"	130.5	128.8	8.5	23.5	10
Package 2	C-130	64.28	20436+53	Storm Drainage Pipe/Culvert	24"	130.3	129.7	3.2	22	10
Package 2	C-130	64.08	20446+84	Storm Drainage Pipe/Culvert	24"	129.9	128.5	3	22	8.3
Package 2	C-131	63.97	20451+81	Storm Drainage Pipe/Culvert	18"	132	130.9	2	21.5	14.1
Package 2	C-132	63.54	20473+68	Storm Drainage Pipe/Culvert	UNKNOWN SIZE	132.7	133	4.4	22	7,7
Package 2	C-133	63.23	20490+00	Arch Concrete Creek Crossing - North of Route 149	UNKNOWN SIZE	133.1	133.1	3.5	22	9.5
Package 2	C-135	62.63	20520+78	Storm Drainage Pipe/Culvert	36"	136.7	134.9	2.6	23	28.9
Package 2	C-136	62.38	20534+63	Storm Drainage Pipe/Culvert	36"	142.9	139.8	0.89	23	29.9
Package 2	C-139	61.54	20579+46	Storm Drainage Pipe/Culvert	48"	141.6	140.6	3.3	24	30
Package 2	C-140	61.37	20588+67-20588+30	Storm Drainage Pipe/Culvert	30", 36"	140.3	137.4	0.5	25.5	34.9
Package 2	C-141	60.89	20614+48	Storm Drainage Pipe/Culvert	24"	146.6	141	2.2	22	16.1
Package 2	C-314A	59.27	20700+03	Storm Drainage Pipe/Culvert	48"	140.1	137.7	23.3	24	12.8
Package 2	C-148	58.96	20716+83	Storm Drainage Pipe/Culvert	24"	142.6	141.1	3	22	30.5
Package 2	C-151	58.15	20760+68	Storm Drainage Pipe/Culvert	30"	134.6	132.7	22.3	22.5	197.8
Package 2	Not Available	57.75	20773+89	Storm Drainage Pipe/Culvert	36"	135.5	132.8	19.5	23	482.7

3 TYPICAL DUCTBANK SECTION NEAR EXISTING CP RAIL CULVERT OUTLET NOT TO SCALE

1. DUCT BANK TO BE 2.0' MIN ABOVE OR BELOW EXISTING CULVERTS.

Champlain Hudson **Power Express** 







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

					SEGMENT 3 - PACKAGE 2 - FORT ANN TO KII  TYPICAL CULVERT SECTION (3 OF
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	JJE	JPR	
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: JJE DESIGNED BY: JTM APPROVED BY: JPR REV. NO.
		•	·		

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY TYPICAL CULVERT SECTION (3 OF 3)

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

C-626

SCALE: N.T.S.

1. ABOVE SECTION IS THE MINIMUM FOR INSTALLATION. MATCH EXISTING SECTION IF EXISTING

- THICKNESS IS GREATER ALL MATERIALS TO MEET NYSDOT STANDARD SPECIFICATIONS.
- APPLY STRAIGHT TACK COAT BETWEEN PAVEMENT SECTIONS NYSDOT ITEM NO.407.0103 4. PRIVATE COMMERCIAL DRIVEWAYS TO UTILIZE COMMERCIAL DRIVEWAY SPECIFICATIONS AS
- SHOWN ON THE NYSDOT STANDARD SHEETS.

ASPHALT CONCRETE PAVEMENT DETAIL (PRIVATE DRIVEWAY)

2" ASPHALT CONCRETE TOP COURSE (NYSDOT ITEM NO. 404.096201) 2.5" ASPHALT CONCRETE BINDER COURSE (NYSDOT ITEM NO. 404.198901) -8" ASPHALT CONCRETE BASE COURSE (NYSDOT ITEM NO. 404.378901) -12" SUBBASE MATERIAL, MATCH EXISTING THICKNESS NYSDOT TYPE 2 (ITEM NO. 304.12) -COMPACTED SUBGRADE

1. ABOVE SECTION IS THE MINIMUM FOR INSTALLATION. MATCH EXISTING SECTION IF EXISTING THICKNESS IS GREATER

TENSAR BX1200 GEOGRID<sup>6</sup>

12 INCH AGGREGATE

9 INCH AGGREGATE

6 INCH AGGREGATE

6 INCH AGGREGATE

2. ALL MATERIALS TO MEET NYSDOT STANDARD SPECIFICATIONS 3. APPLY STRAIGHT TACK COAT TO BETWEEN PAVEMENT SECTIONS NYSDOT ITEM NO.407.0103

ASPHALT CONCRETE PAVEMENT (WITHIN NYSDOT ROADWAYS)

TEMPORARY ACCESS ROAD SECTION<sup>1,2,3,4</sup>

MIRAFI 180N GEOTEXTILE<sup>6</sup>

20 INCH RIP RAP

+ 6 INCH AGGREGATE

18 INCH AGGREGATE

12 INCH AGGREGATE

11 INCH AGGREGATE

8 INCH AGGREGATE

SCALE: N.T.S.

-2" ASPHALT CONCRETE TOP COURSE (NYSDOT ITEM NO. 404.096201) 2-1/2" ASPHALT CONCRETE BINDER COURSE (NYSDOT ITEM NO. 404.198901) - 3" ASPHALT CONCRETE BASE COURSE (NYSDOT ITEM NO. 404.378901) -12" SUBBASE MATERIAL. MATCH EXISTING THICKNESS NYSDOT (ITEM NO. 304.12) - COMPACTED SUBGRADE

1. ABOVE SECTION IS THE MINIMUM FOR INSTALLATION. MATCH EXISTING SECTION IF EXISTING

THICKNESS IS GREATER 2. ALL MATERIALS TO MEET NYSDOT STANDARD SPECIFICATIONS

3. SEE DETAIL 10 ON SHEET C-631 4. APPLY STRAIGHT TACK COAT TO BETWEEN PAVEMENT SECTIONS NYSDOT ITEM407.0103

ASPHALT CONCRETE PAVEMENT

<u>(WITHIN COUNTY OR TOWN ROADWAYS)</u>

MIRAFI RSI SERIES

GEOTEXTILE<sup>6</sup> 20 INCH RIP RAP<sup>7</sup>


+ 4 INCH AGGREGATE (RS580I)

15 INCH AGGREGATE (RS280I)

9 INCH AGGREGATE (RS280I)

9 INCH AGGREGATE (RS280I)

9 INCH AGGREGATE (RS280I)



1. ALL MATERIALS TO MEET NYSDOT STANDARD SPECIFICATIONS

PAVEMENT TRANSITION DETAIL

SLOPE AS INDICATED ON PLAN -LAYER THICKNESS PER TABLE - COMPACTED SUBGRADE -GEOTEXTILE FABRIC AND/OR

5 TEMPORARY ACCESS ROAD

SCALE: N.T.S.

GEOGRID, AS REQUIRED<sup>6</sup>

<sup>2</sup> AGGREGATE SHALL BE NYSDOT TYPE 2 CRUSHED AGGREGATE OR APPROVED ALTERNATIVE.

TEMPORARY ACCESS ROAD SECTIONS PER KIEWIT ENGINEERING (NY) CORP.

UNSTABILIZED

18 INCH AGGREGATE

15 INCH AGGREGATE

<sup>3</sup> DESIGN CONSIDERS 1,000 PASSES OF MAXIMUM 22—KIP AXLE LOAD AND A DESIGN RUT DEPTH OF 3 INCHES. ADDITIONAL AXLE PASSES, HEAVIER AXLE LOADS, AND DETERIORATED SUBGRADE CONDITIONS MAY REQUIRE THICKER AGGREGATE SECTIONS OR ADDITIONAL MAINTENANCE. <sup>4</sup> ALTERNATE TEMPORARY ACCESS ROAD DESIGNS MAY BE PROVIDED BY KIEWIT ENGINEERING, AS REQUIRED, BASED ON FIELD CONDITIONS AND TRAFFIC LOADING.

<sup>5</sup> ESTIMATE CBR IN THE FIELD USING A DYNAMIC CONE PENETROMETER OR ALTERNATIVE METHOD APPROVED BY GEOTECHNICAL ENGINEER OF RECORD (EOR). CBR OF IN-SITU SOIL MAY VARY SEASONALLY DUE TO FREEZE/THAW AND BASED ON MOISTURE CONDITIONS.

GEOGRID AND GEOTEXTILE A GEOGRID AND GEOTEXTILES SHALL BE INSTALLED PER MANUFACTURER'S SPECIFICATION INCLUDING OVERLAP AND EDGE DETAILS.

B SPECIFIED GEOTEXTILE OR GEOGRID MAY BE REPLACED BY EQUIVALENT MATERIAL APPROVED BY EOR.


<sup>C</sup> GEOTEXTILE IS REQUIRED IN REGULATED WETLANDS AND AGRICULTURAL LANDS. D GEOTEXTILE SEPARATOR FABRIC IS REQUIRED BENEATH GEOGRID ON COHESIVE SUBGRADE

RIP RAP

A RIP RAP SHALL BE NYSDOT LIGHT STONE FILL OR APPROVED ALTERNATIVE. B A LAYER OF #57 STONE IS RECOMMENDED ON TOP OF GEOTEXTILE TO PREVENT DAMAGING OR PUNCHING OF THE GEOTEXTILE FABRIC WHERE RIP RAP IS USED.


-SLOPE AS INDICATED ON PLAN -8" SUBBASE - COMPACTED SUBGRADE — STABILIZATION FABRIC

6 GRAVEL PAVEMENT SCALE: N.T.S.



CONCRETE TOP COURSE. 2. ALL MATERIALS TO MEET NYSDOT STANDARD SPECIFICATIONS

MILL AND OVERLAY ASPHALT CONCRETE PAVEMENT DETAIL SCALE: N.T.S.



NOTES: 1. WHERE IDENTIFIED ON PLANS, CULVERT REPLACEMENTS AND/OR REPAIR TO BE COMPLETED IN ACCORDANCE WITH NYSDOT STANDARD SHEETS (NYSDOT STANDARD SHEET GROUP 603 CULVERTS AND STORM DRAINS AND NYSDOT BRIDGE DETAIL SHEETS BD-CB1 THRU BD-CB13)

8 CULVERT REPLACEMENT


CBR<sup>5</sup>

0.5

1.5

2.0

3.0+



1. ALL MATERIALS TO MEET NYSDOT STANDARD SPECIFICATIONS

9 WING WEDGE CURB DETAIL









IT IS A VIOLATION OF LAW FOR ANY PERSON. UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ALTERED THE ALTERING ENGINEER ARCHITECT LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.


0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	JJE	JPR	CHAMPLAIN HUDSON POWER EX SEGMENT 3 - PACKAGE 2 - FORT ANN TO KILL SURFACE RESTORATION DETAIL
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	SCALE SCALE
INO.	DATE	SUDIVITITAL/ REVISION DESCRIPTION	DB	AFF	DRAWN BY: JJE DESIGNED BY: JTM APPROVED BY: JPR REV. NO.

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY SURFACE RESTORATION DETAILS

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

AS NOTED DATE

C-631



BORING LOG STRIP LEGEND Blow Counts per 6" = 10-10-10 Recovery %/RQD % = 95%/90% 11000psi =UCS 2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

Legend

ASPHALT Bedrock Bedrock Boulder Boulder Fat CLAY CH SILTY Fat CLAY CH-MH Lean CLAY SILTY CLAY CL-ML CONCRETE Concrete Fill Fill CLAYEY GRAVEL GC-GM SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL Poorly Graded Gravel with CLAY GP-GC Poorly Graded GRAVEL with SILT GP-GM Well Graded GRAVEL Well Graded GRAVEL with CLAY GW-GM Well Graded GRAVEL with SILT Limestone Elastic SILT ORGANIC Fat CLAY ORGANIC Lean CLAY OL/OH ORGANIC SOIL PEAT Rock Rock Sandstone Sandstone CLAYEY SAND SILT, CLAYEY SAND 2C-2M SHALE Shale SILTSTONE Siltstone SILTY SAND SP Poorly Graded SAND SP-SC Poorly Graded SAND with CLAY SP-SM Poorly Graded SAND with SILT SW Well graded SAND SM-SC Well Graded SAND with CLAY Well Graded SAND with SILT SW-SMTopsoil Topsoil Gravel or Conglomerate 1 USGS 601 USGS 654 Subgraywacke USGS 670 nterbedded Sandstone and Shale USGS 702 USGS 705 Schist USGS 705 Schist USGS 708 Gneiss USGS 708 Gneiss USGS 718 Granite 1 Void Void Water Undefined Weathered Rock ▼ Water Table Water Table during drilling Water Table after drilling









ALTERED. THE ALTERING ENGINEER. ARCHITECT. LANDSCAPE ACHITECT, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.


0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP


CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY HDD 12 RAILROAD CROSS SECTION CUT

DRAWN BY: SK DESIGNED BY: SK APPROVED BY: JEO REV. NO.


KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

C-641






CP RAIL CANADIAN MAINLINE MP: 68.53



HDD #12A CONDUIT 1 EXIT PIT CUT SECTION; STA. 20193+20
CP RAIL CANADIAN MAINLINE MP: 68.80



SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY

HDD 12A RAILROAD CROSS SECTION CUT


KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

**C-642** 

Champlain Hudson Power Express







0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP

AS NOTED DATE DRAWN BY: JAS DESIGNED BY: JAS APPROVED BY: JEO REV. NO.

BORING LOG STRIP LEGEND

2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

Legend

Bedrock

Boulder

Fat CLAY

SILTY Fat CLAY

Lean CLAY

SILTY CLAY

Concrete

Fill

CLAYEY GRAVEL

SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL Poorly Graded Gravel with CLAY

Poorly Graded GRAVEL with SILT

Well Graded GRAVEL

Well Graded GRAVEL with CLAY

Well Graded GRAVEL with SILT

Limestone

ORGANIC Fat CLAY ORGANIC Lean CLAY

ORGANIC SOIL

PEAT

Rock Sandstone

CLAYEY SAND SILT, CLAYEY SAND

Shale

SILTY SAND

Poorly Graded SAND

Poorly Graded SAND with CLAY

Poorly Graded SAND with SILT

Well graded SAND

Well Graded SAND with CLAY

Well Graded SAND with SILT

Topsoil

Gravel or Conglomerate 1

Subgraywacke nterbedded Sandstone and Shale

Schist

Schist

Gneiss

Gneiss

Granite 1 Void

Water

Undefined

Water Table during drilling

Water Table after drilling

Recovery %/RQD % = 95%/90% 11000psi =UCS

Blow Counts per 6" = 10-10-10

ASPHALT Bedrock

Boulder

CH

CH-MH

CL-ML CONCRETE

Fill

GC-GM

GP-GC

GP-GM

GW-GM

OL/OH

Rock

Sandstone

2C-2M

SHALE

SILTSTONE

SP

SP-SC

SP-SM

SW

SM-SC

SW-SM

Topsoil

USGS 601 USGS 654

USGS 702


USGS 705


USGS 705

USGS 708

USGS 708

USGS 718





Poorly Graded GRAVEL Poorly Graded Gravel with CLAY GP-GC GP-GM Poorly Graded GRAVEL with SILT Well Graded GRAVEL Well Graded GRAVEL with CLAY GW-GM Well Graded GRAVEL with SILT Limestone ORGANIC Fat CLAY ORGANIC Lean CLAY OL/OH ORGANIC SOIL PEAT Rock Rock Sandstone Sandstone CLAYEY SAND SILT, CLAYEY SAND 2C-2M SHALE Shale SILTSTONE SILTY SAND SP Poorly Graded SAND SP-SC Poorly Graded SAND with CLAY SP-SM Poorly Graded SAND with SILT Well graded SAND SW SM-SC Well Graded SAND with CLAY Well Graded SAND with SILT SW-SMTopsoil Topsoil Gravel or Conglomerate 1 USGS 601 USGS 654 Subgraywacke

BORING LOG STRIP LEGEND

2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

Legend

Bedrock

Boulder

Fat CLAY

SILTY Fat CLAY

Lean CLAY

SILTY CLAY

Concrete

Fill

CLAYEY GRAVEL

SILTY CLAYEY GRAVEL SILTY GRAVEL

Recovery %/RQD % = 95%/90% 11000psi =UCS

Blow Counts per 6" = 10-10-10

ASPHALT

Bedrock

Boulder

CH

CH-MH

CL-ML CONCRETE


Fill

GC-GM

Champlain Hudson **Power Express** 







CP RAIL CANADIAN MAINLINE MP: 68.53

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ALTERED. THE ALTERING ENGINEER. ARCHITECT. LANDSCAPE ACHITECT, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

					SEGMEN HDE	IT 3 -	PACK	(AGE		ORT A	ANN	TO KII
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO								
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: JA	s DES	IGNED B	Y: JAS	APPROV	/ED BY:		SCALE REV. NO.

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY HDD 12A RAILROAD CROSS SECTION CUT

Scale in feet

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

nterbedded Sandstone and Shale

Schist

Schist

Gneiss

Gneiss

Granite 1

Void

Water

Undefined

Water Table during drilling

Water Table after drilling

C-642.1

AS NOTED DATE

USGS 702 USGS 705

USGS 705

USGS 708

USGS 708


USGS 718


Void

Weathered Rock

Delayed Water Table

▼ Water Table





HDD #13 CONDUIT 1 EXIT PIT CUT SECTION; STA 20248+70
CP RAIL CANADIAN MAINLINE MP: 67.80

**Power Express** 







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ALTERED. THE ALTERING ENGINEER. ARCHITECT, LANDSCAPE ACHITECT, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	D
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO	L

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY HDD 13 RAILROAD CROSS SECTION CUT

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

BORING LOG STRIP LEGEND

2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

Legend

Bedrock

Boulder

Fat CLAY

SILTY Fat CLAY

Lean CLAY

SILTY CLAY

Concrete

Fill CLAYEY GRAVEL

SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL Poorly Graded Gravel with CLAY

Poorly Graded GRAVEL with SILT

Well Graded GRAVEL

Well Graded GRAVEL with CLAY

Well Graded GRAVEL with SILT

Limestone

Elastic SILT

ORGANIC Fat CLAY

ORGANIC Lean CLAY

ORGANIC SOIL

PEAT

Rock Sandstone

CLAYEY SAND

SILT, CLAYEY SAND

Shale

SILTY SAND

Poorly Graded SAND

Poorly Graded SAND with CLAY

Poorly Graded SAND with SILT Well graded SAND

Well Graded SAND with CLAY Well Graded SAND with SILT

Topsoil Gravel or Conglomerate 1

Subgraywacke nterbedded Sandstone and Shale

Schist

Schist

Gneiss

Gneiss

Granite 1

Void

Water

Undefined

Water Table during drilling Water Table after drilling

Recovery %/RQD % = 95%/90% - 11000psi =UCS

Blow Counts per 6" = 10-10-10

ASPHALT Bedrock

Boulder

СН

CH-MH

CL-ML CONCRETE

Fill

GC-GM

GP-GC GP-GM

GW-GM

OL/OH

Rock

Sandstone

2C-2M

SHALE

SILTSTONE

SP

SP-SC

SP-SM

SW

SM-SC

SW-SM

Topsoil

USGS 601

USGS 654

USGS 702

USGS 705

USGS 705

USGS 708

USGS 708

USGS 718


Void

Weathered Rock

▼ Water Table

**C-643** 

AS NOTED DATE DRAWN BY: MAR DESIGNED BY: MAR APPROVED BY: JEO REV. NO.




15.0° ACCESS Rd OFFSET = 33.3 \_WORKZONE OFFSET = 33.8 ACCESS Rd Elev. = 136.3 WORKZONE Elev. = 135.9 R.R. ROW OFFSET = 40.2 R.R. ROW Elev. = 132.1CONDUIT 2 OFFSET = 41.0CP RAIL OFFSET = 0.0\_ 140 140 CP RAIL Elev. = 138.2CONDUIT 1 OFFSET = 56.2CONDUIT 1 Elev. = 132.9WORKZONE OFFSET = 64.3 6.6' WORKZONE Elev. = 134.8 4.5% \_\_\_\_ OFFSET Elev. = 14-6-5-5 6-6-4-3 -5.1% 3-3-4-2 130 4-4-4-5 60 50 EXISTING GROUND -**APPROXIMATE** 3-7-7-7 HDD EXIT ACCESS Rd OFFSET = 12.5\_ ACCESS Rd Elev. = 135.8 1.5H PROPOSED 5'X10'X5' -0.3% PROPOSED ACCESS ROAD -WET OFFSET = 37.55-3-5-6 WET Elev. = 132.8 120 *APPROXIMATE* DEPTH AT INV: 82.8' 5-8-5-7 -40 -90 -60 -30 -20


HDD #13 CONDUIT 2 EXIT PIT CUT SECTION; STA. 20248+70
CP RAIL CANADIAN MAINLINE MP: 67.80

**Power Express** 









No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	C
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO	

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY HDD 13 RAILROAD CROSS SECTION CUT

Scale in feet

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

BORING LOG STRIP LEGEND

2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

Legend

Bedrock

Boulder

Fat CLAY

SILTY Fat CLAY

Lean CLAY SILTY CLAY

Concrete

Fill CLAYEY GRAVEL

SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL Poorly Graded Gravel with CLAY

Poorly Graded GRAVEL with SILT Well Graded GRAVEL Well Graded GRAVEL with CLAY

Well Graded GRAVEL with SILT Limestone

ORGANIC Fat CLAY

ORGANIC Lean CLAY

ORGANIC SOIL

PEAT

Rock

Sandstone

CLAYEY SAND

SILT, CLAYEY SAND

Shale

SILTY SAND

Poorly Graded SAND

Poorly Graded SAND with CLAY

Poorly Graded SAND with SILT

Well graded SAND

Well Graded SAND with CLAY

Well Graded SAND with SILT

Topsoil

Gravel or Conglomerate 1

Subgraywacke

nterbedded Sandstone and Shale

Schist

Schist

Gneiss

Gneiss

Granite 1

Void

Water

Undefined

Water Table during drilling

Water Table after drilling

Recovery %/RQD % = 95%/90% 11000psi =UCS

Blow Counts per 6" = 10-10-10

ASPHALT Bedrock

Boulder

CH

CH-MH

CL-ML

CONCRETE

Fill

GC-GM

GP-GC GP-GM

GW-GM

OL/OH

Rock

Sandstone

2C-2M

SHALE

SILTSTONE

SP

SP-SC

SP-SM

SW

SM-SC

SW-SM

Topsoil

USGS 601

USGS 654

USGS 702

USGS 705

USGS 705

USGS 708

USGS 708

USGS 718

Void


Weathered Rock


▼ Water Table

□ Delayed Water Table

C-643.1

PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED. THE ALTERING ENGINEER. ARCHITECT. LANDSCAPE ACHITECT, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION. AS NOTED DATE DRAWN BY: MAR DESIGNED BY: MAR APPROVED BY: JEO REV. NO.





1 HDD #13A CONDUIT 1 ENTRY PIT CUT SECTION; STA. 20281+11
CP RAIL CANADIAN MAINLINE MP: 67.18

Blow Counts per 6" = 10-10-10
Recovery %/RQD % = 95%/90%

2D strip logs shown at 10x exaggeration
3D strip logs have no exaggeration

Legend ASPHALT Bedrock Bedrock Boulder Boulder СН Fat CLAY SILTY Fat CLAY CH-MH Lean CLAY CL-ML SILTY CLAY CONCRETE Concrete Fill Fill CLAYEY GRAVEL GC-GM SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL Poorly Graded Gravel with CLAY GP-GC Poorly Graded GRAVEL with SILT GP-GM Well Graded GRAVEL Well Graded GRAVEL with CLAY GW-GM Well Graded GRAVEL with SILT Limestone Elastic SILT ORGANIC Fat CLAY ORGANIC Lean CLAY OL/OH ORGANIC SOIL PEAT Rock Rock Sandstone Sandstone CLAYEY SAND SILT, CLAYEY SAND 2C-2M SHALE Shale SILTSTONE SILTY SAND Poorly Graded SAND SP SP-SC Poorly Graded SAND with CLAY Poorly Graded SAND with SILT SP-SM SW Well graded SAND SM-SC Well Graded SAND with CLAY Well Graded SAND with SILT SW-SMTopsoil Topsoil Gravel or Conglomerate 1 USGS 601 USGS 654 Subgraywacke USGS 670 Interbedded Sandstone and Shale USGS 702 USGS 705 Schist USGS 705 Schist USGS 708 Gneiss USGS 708 Gneiss USGS 718 Granite 1 Void Void Water Weathered Rock Undefined ▼ Water Table Water Table during drilling □ Delayed Water Table Water Table after drilling

CHAMPLAIN HUDSON POWER EXPRESS
SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY
HDD 13A RAILROAD CROSS SECTION CUT

KIEWIT PROJECT NO.
21162
CHA PROJECT NO.
066076
DRAWING NO.

CHPE

Champlain Hudson

Power Express





IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP


C-644


DRAWN BY: MAR DESIGNED BY: MAR APPROVED BY: JEO REV. NO.

C ORAWN BY: MAR DESIGNED BY: MAR APPROVED BY: JEO REV. NO.

C ORAWN BY: MAR DESIGNED BY: MAR APPROVED BY: JEO REV. NO.

C ORAWN BY: MAR DESIGNED BY: MAR APPROVED BY: JEO REV. NO.





Rock Rock Sandstone Sandstone CLAYEY SAND SILT, CLAYEY SAND 2C-2M SHALE Shale SILTSTONE SILTY SAND Poorly Graded SAND Poorly Graded SAND with CLAY SP-SC SP-SM Poorly Graded SAND with SILT Well graded SAND SW SM-SC Well Graded SAND with CLAY Well Graded SAND with SILT SW-SMTopsoil Topsoil Gravel or Conglomerate 1 USGS 601 USGS 654 Subgraywacke Interbedded Sandstone and Shale USGS 702 USGS 705 Schist USGS 705 Schist USGS 708 Gneiss USGS 708 Gneiss USGS 718 Granite 1 Void Void Water Undefined Weathered Rock ▼ Water Table Water Table during drilling







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED. THE ALTERING ENGINEER. ARCHITECT. LANDSCAPE ACHIERD, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

					SEGMENT 3 - PACKAGE 2 - FORT ANN TO KI HDD 13A RAILROAD CROSS SECTION
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO	
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: MAR DESIGNED BY: MAR APPROVED BY: JEO REV. NO.

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY HDD 13A RAILROAD CROSS SECTION CUT

KIEWIT PROJECT NO.	
21162	
CHA PROJECT NO.	
066076	
DRAWING NO.	

C-644.1

AS NOTED DATE

Water Table after drilling

BORING LOG STRIP LEGEND

2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

Legend

Bedrock

Boulder

Fat CLAY

SILTY Fat CLAY

Lean CLAY

SILTY CLAY

Concrete

Fill CLAYEY GRAVEL

SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL Poorly Graded Gravel with CLAY

Poorly Graded GRAVEL with SILT Well Graded GRAVEL Well Graded GRAVEL with CLAY

Well Graded GRAVEL with SILT

Limestone

ORGANIC Fat CLAY

ORGANIC Lean CLAY

ORGANIC SOIL

PEAT

Recovery %/RQD % = 95%/90% 11000psi =UCS

Blow Counts per 6" = 10-10-10

ASPHALT

Bedrock

Boulder

CH

CH-MH

CL-ML CONCRETE

Fill


GC-GM

GP-GC GP-GM

GW-GM

OL/OH

Delayed Water Table



HDD #14 CONDUIT 1 EXIT PIT CUT SECTION; STA. 20293+17 CP RAIL CANADIAN MAINLINE MP: 66.97

2 HDD #14 CONDUIT 1 ENTRY PIT CUT SECTION; STA. 20300+09
CP RAIL CANADIAN MAINLINE MP: 66.85

BORING LOG STRIP LEGEND Blow Counts per 6" = 10-10-10 Recovery %/RQD % = 95%/90% 11000psi =UCS 2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

Legend ASPHALT Bedrock Bedrock Boulder Boulder Fat CLAY CH SILTY Fat CLAY CH-MH Lean CLAY SILTY CLAY CL-ML CONCRETE Concrete Fill Fill CLAYEY GRAVEL GC-GM SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL Poorly Graded Gravel with CLAY GP-GC Poorly Graded GRAVEL with SILT GP-GM Well Graded GRAVEL Well Graded GRAVEL with CLAY GW-GM Well Graded GRAVEL with SILT Limestone Elastic SILT ORGANIC Fat CLAY ORGANIC Lean CLAY OL/OH ORGANIC SOIL PEAT Rock Rock Sandstone Sandstone CLAYEY SAND SILT, CLAYEY SAND 2C-2M SHALE Shale SILTSTONE SILTY SAND SP Poorly Graded SAND SP-SC Poorly Graded SAND with CLAY Poorly Graded SAND with SILT SP-SM Well graded SAND SW SM-SC Well Graded SAND with CLAY Well Graded SAND with SILT SW-SMTopsoil Topsoil Gravel or Conglomerate 1 USGS 601 USGS 654 Subgraywacke Interbedded Sandstone and Shale USGS 702 USGS 705 Schist USGS 705 Schist USGS 708 Gneiss Gneiss USGS 708 USGS 718 Granite 1 Void Void Water Weathered Rock Undefined ▼ Water Table Water Table during drilling Delayed Water Table Water Table after drilling









IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A
SPECIFIC DESCRIPTION OF THE ALTERATION.


				SEGMENT 3 - PACKAGE 2 - FORT ANN TO KI HDD 14 RAILROAD CROSSING SECTIO
03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO	-
DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: MAR DESIGNED BY: MAR APPROVED BY: JEO REV. NO.

CHAMPLAIN HUDSON POWER EXPRESS ORT ANN TO KINGSBURY SSING SECTION CUT

Scale in feet

KIEW	/IT PROJECT NO.
	21162
CH	A PROJECT NO.
	066076
	RAWING NO.

**C-645** 



Delayed Water Table CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY HDD 14 RAILROAD CROSSING SECTION CUT

DB APP DRAWN BY: MAR DESIGNED BY: MAR APPROVED BY: JEO REV. NO.

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. DRAWING NO.

BORING LOG STRIP LEGEND

2D strip logs shown at 10x exaggeration

3D strip logs have no exaggeration

Legend

Bedrock

Boulder

Fat CLAY

SILTY Fat CLAY

Lean CLAY

SILTY CLAY

Concrete

Fill CLAYEY GRAVEL

SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL Poorly Graded Gravel with CLAY

Poorly Graded GRAVEL with SILT Well Graded GRAVEL Well Graded GRAVEL with CLAY

Well Graded GRAVEL with SILT

Limestone

Elastic SILT

ORGANIC Lean CLAY

ORGANIC SOIL

PEAT

Rock

Sandstone

CLAYEY SAND

SILT, CLAYEY SAND

Shale

SILTY SAND

Poorly Graded SAND

Poorly Graded SAND with CLAY

Poorly Graded SAND with SILT

Well graded SAND

Well Graded SAND with CLAY

Well Graded SAND with SILT

Topsoil

Gravel or Conglomerate 1

Subgraywacke nterbedded Sandstone and Shale

Schist

Schist

Gneiss

Gneiss

Granite 1 Void

Water Undefined

Water Table during drilling

Water Table after drilling

Recovery %/RQD % = 95%/90% 11000psi =UCS

Blow Counts per 6" = 10-10-10

ASPHALT

Bedrock

Boulder

CH

CH-MH

CL-ML CONCRETE

Fill

GC-GM

GP-GC GP-GM

GW-GM

OL/OH

Rock

Sandstone

2C-2M SHALE

SILTSTONE

SP-SC

SP-SM

SW

SM-SC

SW-SM

Topsoil

USGS 601 USGS 654

USGS 702 USGS 705

USGS 705

USGS 708

USGS 708

USGS 718

Void

Weathered Rock

▼ Water Table

C-645.1

AS NOTED DATE


03/22/2023 ISSUED FOR CONSTRUCTION SUBMISSION

MCS JEO

DATE SUBMITTAL / REVISION DESCRIPTION

**Power Express** 






IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

HDD #14 CONDUIT 2 ENTRY PIT CUT SECTION; STA. 20300+17
CP RAIL CANADIAN MAINLINE MP: 66.85

HDD #14A CONDUIT 1 EXIT PIT CUT SECTION; STA. 20337+37 CP RAIL CANADIAN MAINLINE MP: 66.14



HDD #14A CONDUIT 1 ENTRY PIT CUT SECTION; STA. 20331+52
CP RAIL CANADIAN MAINLINE MP: 66.25

**Power Express** 





AF PROFES OR LAN ITEM B ALTERIA ARCHITE AND I	VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY E ACTING UNDER THE DIRECTION OF A LICENSED SIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT ID SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN EARING THE STAMP OF A LICENSED PROFESSIONAL IS D., THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE CT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT NCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.
---	---

0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO	SEGMENT 3 - PACKAGE 2 - FORT ANN TO KI HDD 14A RAILROAD CROSS SECTION
Na	DATE	OURMITTAL / DEVICION DECORIDATION	DB	ADD	SCALE
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: MAR DESIGNED BY: MAR APPROVED BY: JEO REV. NO.

CHAMPLAIN HUDSON POWER EXPRESS
SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY
HDD 14A RAILROAD CROSS SECTION CUT

KIEWIT PROJECT NO.
21162
CHA PROJECT NO.
066076
DRAWING NO.

**C-646** 

AS NOTED DATE

CLAYEY GRAVEL GC-GM SILTY CLAYEY GRAVEL GM SILTY GRAVEL Poorly Graded GRAVEL GP-GC Poorly Graded Gravel with CLAY Poorly Graded GRAVEL with SILT GP-GMWell Graded GRAVEL GW GW-GC Well Graded GRAVEL with CLAY GW-GM Well Graded GRAVEL with SILT Limestone

BORING LOG STRIP LEGEND

2D strip logs shown at 10x exaggeration

Legend

Bedrock

Boulder

Fat CLAY SILTY Fat CLAY

Lean CLAY

SILTY CLAY

Concrete

Fill

3D strip logs have no exaggeration

Recovery %/RQD % = 95%/90% - 11000psi =UCS

Blow Counts per 6" = 10-10-10

ASPHALT

Bedrock

Boulder

CH

CH-MH

CL-ML

CONCRETE

Fill

ORGANIC Fat CLAY ORGANIC Lean CLAY OL/OH ORGANIC SOIL PEAT Rock Rock Sandstone Sandstone CLAYEY SAND

SILT, CLAYEY SAND SC-SM SHALE Shale SILTSTONE Siltstone SILTY SAND


Poorly Graded SAND SP-SC Poorly Graded SAND with CLAY SP-SM Poorly Graded SAND with SILT SW Well graded SAND SW-SC Well Graded SAND with CLAY

Well Graded SAND with SILT SW-SMTopsoil Topsoil Gravel or Conglomerate 1 USGS 601


USGS 654 Subgraywacke USGS 670 Interbedded Sandstone and Shale USGS 702 USGS 705 Schist USGS 705 Schist

USGS 708 Gneiss USGS 708 Gneiss USGS 718 Granite 1 Void Void

Water Weathered Rock Undefined ▼ Water Table Water Table during drilling □ Delayed Water Table Water Table after drilling



HDD #14A CONDUIT 2 EXIT PIT CUT SECTION; STA. 20338+28
CP RAIL CANADIAN MAINLINE MP: 66.14



HDD #14A CONDUIT 2 ENTRY PIT CUT SECTION; STA. 20332+37
CP RAIL CANADIAN MAINLINE MP: 66.23







CONFER PLANT	IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS T ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHIT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF ITEM BEARING THE STAMP OF A LICENSED PROFESSIONA ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSC, ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUL AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND SPECIFIC DESCRIPTION OF THE ALTERATION.
· //	

0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO	SEGMENT 3 - PACKAGE 2 - FORT ANN TO KIN HDD 14A RAILROAD CROSS SECTION
				<b></b>	SCALE
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: MAR DESIGNED BY: MAR APPROVED BY: JEO REV. NO.

CHAMPLAIN HUDSON POWER EXPRESS
SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY
HDD 14A RAILROAD CROSS SECTION CUT

KIEWIT PROJECT NO.
21162
CHA PROJECT NO.
066076
DRAWING NO.

Water Table after drilling

C-646.1

SILTY Fat CLAY CH-MH Lean CLAY CL-ML SILTY CLAY CONCRETE Concrete Fill Fill CLAYEY GRAVEL GC-GM SILTY CLAYEY GRAVEL GM SILTY GRAVEL

Bedrock

Boulder

Fat CLAY

Poorly Graded GRAVEL GP-GC Poorly Graded Gravel with CLAY Poorly Graded GRAVEL with SILT GP-GMWell Graded GRAVEL GW

BORING LOG STRIP LEGEND

2D strip logs shown at 10x exaggeration

Legend

3D strip logs have no exaggeration

Recovery %/RQD % = 95%/90% - 11000psi =UCS

Blow Counts per 6" = 10-10-10

ASPHALT

Bedrock

Boulder

CH

Well Graded GRAVEL with CLAY GW-GC Well Graded GRAVEL with SILT GW-GM Limestone Elastic SILT

ORGANIC Fat CLAY ORGANIC Lean CLAY

OL/OH ORGANIC SOIL PEAT Rock Rock

Sandstone Sandstone CLAYEY SAND

SILT, CLAYEY SAND SC-SM SHALE Shale

SILTSTONE Siltstone SILTY SAND

Poorly Graded SAND SP-SC Poorly Graded SAND with CLAY SP-SM Poorly Graded SAND with SILT


SW Well graded SAND SW-SC Well Graded SAND with CLAY Well Graded SAND with SILT SW-SM


Topsoil Gravel or Conglomerate 1 USGS 601 USGS 654 Subgraywacke Interbedded Sandstone and Shale

USGS 702 USGS 705 Schist USGS 705 Schist

USGS 708 Gneiss USGS 708 Gneiss USGS 718 Granite 1

Void Void Water Undefined Weathered Rock ▼ Water Table Water Table during drilling Delayed Water Table





HDD #15 CONDUIT 1 ENTRY PIT CUT SECTION; STA. 20418+18
CP RAIL CANADIAN MAINLINE MP: 64.60

BORING LOG STRIP LEGEND Blow Counts per 6" = 10-10-10 Recovery %/RQD % = 95%/90% - 11000psi =UCS 2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

Legend ASPHALT Asphalt Bedrock Bedrock Boulder Boulder CH Fat CLAY SILTY Fat CLAY CH-MH Lean CLAY CL-ML SILTY CLAY CONCRETE Concrete Fill Fill CLAYEY GRAVEL GC-GM SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL Poorly Graded Gravel with CLAY GP-GC Poorly Graded GRAVEL with SILT GP-GM GW Well Graded GRAVEL Well Graded GRAVEL with CLAY GW-GM Well Graded GRAVEL with SILT Limestone Limestone Elastic SILT ORGANIC Fat CLAY ORGANIC Lean CLAY OL/OH ORGANIC SOIL PEAT Rock Rock Sandstone Sandstone CLAYEY SAND SILT, CLAYEY SAND 2C-2M SHALE Shale SILTSTONE Siltstone SILTY SAND Poorly Graded SAND SP SP-SC Poorly Graded SAND with CLAY Poorly Graded SAND with SILT SP-SM SW Well graded SAND SM-SC Well Graded SAND with CLAY Well Graded SAND with SILT SW-SMTopsoil Topsoil Gravel or Conglomerate 1 USGS 601 USGS 654 Subgraywacke Interbedded Sandstone and Shale USGS 702 USGS 705 Schist USGS 705 Schist USGS 708 Gneiss USGS 708 Gneiss USGS 718 Granite 1 Void Void Water Undefined Weathered Rock ▼ Water Table Water Table during drilling □ Delayed Water Table Water Table after drilling







No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO	


	CHAMPLAIN HUDSON POWER EXPRESS
	SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY
	HDD 15 RAILROAD CROSS SECTION CUT
1	

Scale in feet


KIEWIT PROJECT NO.
21162
CHA PROJECT NO.
066076
DRAWING NO.

**C-647** 

DRAWN BY: MAR DESIGNED BY: MAR APPROVED BY: JEO REV. NO.



HDD #15 CONDUIT 2 EXIT PIT CUT SECTION; STA. 20424+29 CP RAIL CANADIAN MAINLINE MP: 64.51




BORING LOG STRIP LEGEND Blow Counts per 6" = 10-10-10 Recovery %/RQD % = 95%/90% - 11000psi =UCS 2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

	ACDLIAL T	Legend
	ASPHALT	Asphalt
	Bedrock	Bedrock
).	Boulder	Boulder
	СН	Fat CLAY
	CH-MH	SILTY Fat CLAY
/////	CL	Lean CLAY
(///	CL-ML	SILTY CLAY
	CONCRETE	Concrete
XX X	Fill	Fill
	GC	CLAYEY GRAVEL
	GC-GM	SILTY CLAYEY GRAVEL
	GM	SILTY GRAVEL
	GP	Poorly Graded GRAVEL
	GP-GC	Poorly Graded Gravel with CLAY
	GP-GM	Poorly Graded GRAVEL with SILT
	GW	Well Graded GRAVEL
	GW-GC	Well Graded GRAVEL with CLAY
, <b>25</b> ,	GW-GM	Well Graded GRAVEL with SILT
	Limestone	Limestone
	MH	Elastic SILT
	ML	SILT
~~~	ПΗ	ORGANIC Fat CLAY
555		ORGANIC Lean CLAY
1888		ORGANIC SOIL
\ / <sub>/</sub>	PT	PEAT
	Rock	Rock
	Sandstone	Sandstone
/. ·/· ·	SC	CLAYEY SAND
]	SC-SM	SILT, CLAYEY SAND
- 71- "	SHALE	Shale
	SILTSTONE	Siltstone
1.1.	SM	SILTY SAND
	SP	Poorly Graded SAND
	SP-SC	Poorly Graded SAND with CLAY
	SP-SM	Poorly Graded SAND with SILT
	SW	Well graded SAND
	SM-SC	Well Graded SAND with CLAY
	SW-SM	Well Graded SAND with SILT
	Topsoil	Topsoil
$\sim$	USGS 601	Gravel or Conglomerate 1
	USGS 654	Subgraywacke
	USGS 670	Interbedded Sandstone and Shale
3.639076	USGS 702	
77117		Quartzite
	USGS 705	Schist
	USGS 705	Schist
	USGS 708	Gneiss
$\langle \dot{\gamma} \dot{\gamma} \dot{\gamma}$	USGS 708	Gneiss
- `	USGS 718	Granite 1
	Void	Void
	Water	Water
	Weathered Rock	Undefined
<b>▼</b>	Water Table	Water Table during drilling
$\nabla$	Delayed Water	Water Table after drilling









IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.


0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY HDD 15 RAILROAD CROSS SECTION CUT


KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

C-647.1

DRAWN BY: MAR DESIGNED BY: MAR APPROVED BY: JEO REV. NO.



Legend ASPHALT Asphalt Bedrock Bedrock Boulder Boulder Fat CLAY SILTY Fat CLAY CH-MH Lean CLAY SILTY CLAY CL-ML CONCRETE Concrete Fill Fill CLAYEY GRAVEL GC-GM SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL GP-GC Poorly Graded Gravel with CLAY Poorly Graded GRAVEL with SILT Well Graded GRAVEL Well Graded GRAVEL with CLAY Well Graded GRAVEL with SILT GW-GM Limestone Limestone Elastic SILT SILT ORGANIC Fat CLAY ORGANIC Lean CLAY OL/OH ORGANIC SOIL PEAT Rock Rock Sandstone Sandstone CLAYEY SAND SC-SM SILT, CLAYEY SAND SHALE Shale SILTSTONE Siltstone SILTY SAND Poorly Graded SAND SP-SC Poorly Graded SAND with CLAY SP-SM Poorly Graded SAND with SILT Well graded SAND Well Graded SAND with CLAY SM-SC Well Graded SAND with SILT SW-SMUSGS 601 Gravel or Conglomerate 1 USGS 654 Subgraywacke USGS 670 Interbedded Sandstone and Shale USGS 702 USGS 705 Schist USGS 705 Schist USGS 708 Gneiss USGS 708 Gneiss USGS 718 Granite 1 Void Void Water Water



1 HDD #16 CONDUIT 1 ENTRY PIT CUT SECTION; STA. 20499+04
CP RAIL CANADIAN MAINLINE MP: 63.06

HDD #16 CONDUIT 1 EXIT PIT CUT SECTION; STA. 20505+08

CP RAIL CANADIAN MAINLINE MP: 62.94

CHPE

Champlain Hudson

Power Express







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY
ARE ACTING UNDER THE DIRECTION OF A LICENSED
PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT
OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN
ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS
ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A
SPECIFIC DESCRIPTION OF THE ALTERATION.

0 No.	ISSUED FOR CONSTRUCTION SUBMISSION SUBMITTAL / REVISION DESCRIPTION	MCS DB	JEO APP	_
				1
				1
				1

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY HDD 16 RAILROAD CROSS SECTION CUT

KIEWIT PROJECT NO.	
21162	
CHA PROJECT NO.	
066076	
DRAWING NO.	

Undefined

Water Table during drilling


Water Table after drilling

C-648

DRAWN BY: ES DESIGNED BY: ES APPROVED BY: JEO REV. NO. C


Weathered Rock

▼ | Water Table



CP RAIL CANADIAN MAINLINE MP: 62.94

HDD #16 CONDUIT 2 ENTRY PIT CUT SECTION; STA. 20498+99 CP RAIL CANADIAN MAINLINE MP: 63.06



		Legend
	ASPHALT	Asphalt
	Bedrock	Bedrock
	Boulder	Boulder
	СН	Fat CLAY
///////	CH-MH	SILTY Fat CLAY
777	CL	Lean CLAY
	CL-ML	SILTY CLAY
/ /	CONCRETE	Concrete
	Fill	Fill
1273	GC	CLAYEY GRAVEL
	GC-GM	SILTY CLAYEY GRAVEL
	GM	SILTY GRAVEL
	GP	Poorly Graded GRAVEL
90	GP-GC	Poorly Graded Gravel with CLAY
	GP-GM	Poorly Graded GRAVEL with SILT
	GW	Well Graded GRAVEL
	GW-GC	Well Graded GRAVEL with CLAY
	GW-GM	Well Graded GRAVEL with SILT
	Limestone	Limestone
	MH	Elastic SILT
	ML	SILT
$\mathbb{S}$	DΗ	ORGANIC Fat CLAY
	ΠL	ORGANIC Lean CLAY
886	OL/OH	ORGANIC SOIL
<u>\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ </u>	PT	PEAT
	Rock	Rock
	Sandstone	Sandstone
· · /· :	SC	CLAYEY SAND
	SC-SM	SILT, CLAYEY SAND
7 -	SHALE	Shale
	SILTSTONE	Siltstone
1.	MS	SILTY SAND
	SP	Poorly Graded SAND
	SP-SC	Poorly Graded SAND with CLAY
	SP-SM	Poorly Graded SAND with SILT
	SW	Well graded SAND
		<u> </u>
<u>^</u>	SW-SC	Well Graded SAND with CLAY
	SW-SM	Well Graded SAND with SILT
$\sim$	Topsoil	Topsoil
	USGS 601	Gravel or Conglomerate 1
	USGS 654	Subgraywacke
	USGS 670	Interbedded Sandstone and Shale
學學	USGS 702	Quartzite
	USGS 705	Schist
	USGS 705	Schist
	USGS 708	Gneiss
	USGS 708	Gneiss
- 7	USGS 718	Granite 1
	Void	Void
	Water	Water
	Weathered Rock	Undefined
▼	\/a + a va Ta la la	Water Table during drilling
	Water Table	water rable daring and









IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

					1
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO	L
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	[


CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY HDD 16 RAILROAD CROSS SECTION CUT


Scale in feet

KIEWIT PROJECT NO.
21162
CHA PROJECT NO.
066076
DRAWING NO.

C-648.1

AS NOTED DATE DRAWN BY: ES DESIGNED BY: ES APPROVED BY: JEO REV. NO.





HDD #17 CONDUIT 1 ENTRY PIT CUT SECTION; STA. 20545+66 CP RAIL CANADIAN MAINLINE MP: 62.17

HDD #17 CONDUIT 1 EXIT PIT CUT SECTION; STA. 20552+15

BORING LOG STRIP LEGEND Blow Counts per 6" = 10-10-10 / Recovery %/RQD % = 95%/90% - 11000psi =UCS 2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

		Legend	
	ASPHALT	Asphalt	
	Bedrock	Bedrock	
🔷 .	Boulder	Boulder	
	СН	Fat CLAY	
/ // //	CH-MH	SILTY Fat CLAY	
777	CL	Lean CLAY	
////	CL-ML	SILTY CLAY	
/ /	CONCRETE	Concrete	
	Fill	FILL	
12 Y 3	GC	CLAYEY GRAVEL	
	GC-GM	SILTY CLAYEY GRAVEL	
	GM	SILTY GRAVEL	
, E	GP	Poorly Graded GRAVEL	
	GP-GC	Poorly Graded Gravel with CLAY	
PP		Poorly Graded GRAVEL with SILT	
00	GP-GM	•	
	GW	Well Graded GRAVEL	
	GW-GC	Well Graded GRAVEL with CLAY	
	GW-GM	Well Graded GRAVEL with SILT	
	Limestone	Limestone	
	MH	Elastic SILT	
	ML	SILT	
<u>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</u>	ОН	ORGANIC Fat CLAY	
	OL	ORGANIC Lean CLAY	
	OL/OH	ORGANIC SOIL	
1/	PT	PEAT Rock	
	Rock		
	Sandstone	Sandstone	
(: /: :/	SC	CLAYEY SAND	
	SC-SM	SILT, CLAYEY SAND	
	SHALE	Shale	
X	SILTSTONE	Siltstone	
	MZ	SILTY SAND	
	SP	Poorly Graded SAND	
- /: :	SP-SC	Poorly Graded SAND with CLAY	
	SP-SM	Poorly Graded SAND with SILT	
	SW	Well graded SAND	
4 / A	SM-SC	Well Graded SAND with CLAY	
	M2-W2	Well Graded SAND with SILT	
	Topsoil	Topsoil	
X X	USGS 601	Gravel or Conglomerate 1	
	USGS 654	Subgraywacke	
	USGS 670	Interbedded Sandstone and Shale	
	USGS 702	Quartzite	
7777	USGS 705	Schist	
	USGS 705	Schist	
	USGS 708	Gneiss	
	USGS 708	Gneiss	
<del>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</del>		Granite 1	
	USGS 718		
	Void	Void	
<u> </u>	Water	Water	
<u> </u>	Weathered Rock	Undefined	
<b>■</b>	Water Table	Water Table during drilling	









IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO

SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY HDD 17 RAILROAD CROSS SECTION CUT


AS NOTED DATE


CP RAIL CANADIAN MAINLINE MP: 62.05

CHAMPLAIN HUDSON POWER EXPRESS

**C-649** 

DRAWN BY: ES DESIGNED BY: ES APPROVED BY: JEO REV. NO.





3 HDD #17 CONDUIT 2 ENTRY PIT CUT SECTION; STA. 20545+97
CP RAIL CANADIAN MAINLINE MP: 62.16

Blow Counts per 6" = 10-10-10

Recovery %/RQD % = 95%/90% — 11000psi =UCS

2D strip logs shown at 10x exaggeration
3D strip logs have no exaggeration

			Legend
		ASPHALT	Asphalt
	_	Bedrock	Bedrock
	<b>♦</b> "	Boulder	Boulder
7/		СН	Fat CLAY
/	7/1	CH-MH	SILTY Fat CLAY
7	77	CL	Lean CLAY
/	11	CL-ML	SILTY CLAY
/	<i>/</i>	CONCRETE	Concrete
		Fill	Fill
50	<del>Y</del>	GC	CLAYEY GRAVEL
100		GC-GM	SILTY CLAYEY GRAVEL
2			
20		GM	SILTY GRAVEL Poorly Graded GRAVEL
50	) }	GP GP	·
50		GP-GC	Poorly Graded Gravel with CLAY
5		GP-GM	Poorly Graded GRAVEL with SILT
		GW	Well Graded GRAVEL
		GW-GC	Well Graded GRAVEL with CLAY
K		GW-GM	Well Graded GRAVEL with SILT
		Limestone	Limestone
	Щ	MH	Elastic SILT
	$\perp_{\mu}$	ML	SILT
<u>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</u>		ОН	ORGANIC Fat CLAY
	<u>کہ</u>	OL OL	ORGANIC Lean CLAY
A.	1 1	OL/OH	ORGANIC SOIL
7/	1,	PT	PEAT
		Rock	Rock
	,	Sandstone	Sandstone
:	/ /	SC	CLAYEY SAND
	7: :	SC-SM	SILT, CLAYEY SAND
		SHALE	Shale
	$\times$	SILTSTONE	Siltstone
		MZ	SILTY SAND
:		SP	Poorly Graded SAND
	/	SP-SC	Poorly Graded SAND with CLAY
		SP-SM	Poorly Graded SAND with SILT
- -	^	SW	Well graded SAND
-	<b>/</b> •	SM-SC	Well Graded SAND with CLAY
	_ ^	M2-W2	Well Graded SAND with SILT
K	XX	Topsoil	Topsoil
		USGS 601	Gravel or Conglomerate 1
		USGS 654	Subgraywacke
		USGS 670	Interbedded Sandstone and Shale
		USGS 702	Quartzite
//		USGS 705	Schist
		USGS 705	Schist
		USGS 708	Gneiss
X		USGS 708	Gneiss
	<del>-/-//</del>	USGS 718	Granite 1
	1	Void	Void
-		Water	Vater
-	·	Weathered Rock	Undefined
	<u>···</u> ▼	Water Table	Water Table during drilling







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO	L


CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY HDD 17 RAILROAD CROSS SECTION CUT

KIEWIT PROJECT NO	Э.
21162	
CHA PROJECT NO	
066076	
DRAWING NO.	

C-649.1

DRAWN BY: ES DESIGNED BY: ES APPROVED BY: JEO REV. NO. C

\_\_BORING\_WFE-18 \_\_ELEVATION: 143.6 BORING K-129.9B\_ ELEVATION: 143.8 WORKZONE OFFSET = 24.5 FO = 10.2LOW OFFSET = 16.3FO Elev. = UNKNOWN LOW Elev. + 144.3 CP RAIL OFFSET = 0.0 BORING K-129.9A \ ELEVATION: \ 143.4 CP RAIL Elev. = 146.4 DEL WET OFFSET = 37.2 DEL WET Elev. = 141.7 = 79.715.0' R.R. ROW OFFSET = 45.5-12. 3.4 R.R. ROW Elev. = 141.4 150 150 OFFSET Elev. = WET (WET L EXISTING GROUND --2.8% 8.4% -15.3% 2.1% 5.1% -8.0% 21.3% 19.5% -5.4% 17.6% -9.3% 2.9% 4-3-5-6 5-4-3-3 2-2-2-2 2-2-2-2 — APPROXIMATE 2-3-3-2 6-3-4 2-2-1-1 HDD EXIT 0-0-1-1 Q-0-0-0 -PROPOSED 5'X10'X5' 3-3-3 ENTRY PIT 3-3-4 130 130 0-0-0-0 - APPROXIMATE DEPTH 0-1-2 AT INV: 118.9' -60 -50 -30 -20 -10



HDD #18 CONDUIT 1 ENTRY PIT CUT SECTION; STA. 20649+00 CP RAIL CANADIAN MAINLINE MP: 60.20

2 HDD #18 CONDUIT 1 EXIT PIT CUT SECTION; STA. 20655+05

CP RAIL CANADIAN MAINLINE MP: 60.08

BORING LOG STRIP LEGEND Blow Counts per 6" = 10-10-10 / Recovery %/RQD % = 95%/90% - 11000psi =UCS 2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

		Legend
	ASPHALT	Asphalt
	Bedrock	Bedrock
	Boulder	Boulder
	СН	Fat CLAY
	CH-MH	SILTY Fat CLAY
	CL	Lean CLAY
	CL-ML	SILTY CLAY
	CONCRETE	Concrete
X	Fill	Fill
Ó	GC	CLAYEY GRAVEL
	GC-GM	SILTY CLAYEY GRAVEL
	GM	SILTY GRAVEL
00	GP	Poorly Graded GRAVEL
OO	GP-GC	Poorly Graded Gravel with CLAY
2003	GP-GM	Poorly Graded GRAVEL with SILT
	GW	Well Graded GRAVEL
7	GW-GC	Well Graded GRAVEL with CLAY
	GW-GM	Well Graded GRAVEL with SILT
	Limestone	Limestone
	MH	Elastic SILT
	ML	SILT
(( ((	DΗ	DRGANIC Fat CLAY
)) ))	DL	ORGANIC Lean CLAY
	OL/OH	ORGANIC SOIL
	PT	PEAT
	Rock	Rock
<u> </u>	Sandstone	Sandstone
/ <b>.</b> • / <b>.</b> •	SC SC	CLAYEY SAND
. •/• •/	SC-SM	SILT, CLAYEY SAND
. /	SHALE	Shale
	SILTSTONE	Siltstone
	ZIL I Z I DIVE	
		SILTY SAND Poorly Graded SAND
	SP	,
. /	SP-SC	Poorly Graded SAND with CLAY
	SP-SM	Poorly Graded SAND with SILT
<u> </u>	SW	Well graded SAND
<u> </u>	SW-SC	Well Graded SAND with CLAY
	SW-SM	Well Graded SAND with SILT
XX	Topsoil	Topsoil
	USGS 601	Gravel or Conglomerate 1
	USGS 654	Subgraywacke
	USGS 670	Interbedded Sandstone and Shale
	USGS 702	Quartzite
	USGS 705	Schist
	USGS 705	Schist
	USGS 708	Gneiss
(///	USGS 708	Gneiss
-	USGS 718	Granite 1
	Void	Void
	Water	Water
	Weathered Rock	Undefined
•	Water Table	Water Table during drilling
$\nabla$	Delayed Water Table	Water Table after drilling

Champlain Hudson **Power Express** 







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

					CHAN SEGME
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO	
No	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	ДРР	DDAMN DV


MPLAIN HUDSON POWER EXPRESS MENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY HDD 18 RAILROAD CROSS SECTION CUT


Scale in feet

KIEWIT PROJECT NO.
21162
CHA PROJECT NO.
066076
DRAWING NO.


**C-650** 

DB | APP | DRAWN BY: MAR | DESIGNED BY: MAR | APPROVED BY: JEO | REV. NO.





3 HDD #18 CONDUIT 2 ENTRY PIT CUT SECTION; STA. 20649+00 CP RAIL CANADIAN MAINLINE MP: 60.20




		Legend
	ASPHALT	Asphalt
	Bedrock	Bedrock
	Boulder	Boulder
	СН	Fat CLAY
	CH-MH	SILTY Fat CLAY
	CL	Lean CLAY
	CL-ML	SILTY CLAY
	CONCRETE	Concrete
X	Fill	Fill
Ó	GC	CLAYEY GRAVEL
	GC-GM	SILTY CLAYEY GRAVEL
	GM	SILTY GRAVEL
00	GP	Poorly Graded GRAVEL
OO	GP-GC	Poorly Graded Gravel with CLAY
2003	GP-GM	Poorly Graded GRAVEL with SILT
	GW	Well Graded GRAVEL
7	GW-GC	Well Graded GRAVEL with CLAY
	GW-GM	Well Graded GRAVEL with SILT
	Limestone	Limestone
	MH	Elastic SILT
	ML	SILT
(( ((	DΗ	DRGANIC Fat CLAY
)) ))	DL	ORGANIC Lean CLAY
	OL/OH	ORGANIC SOIL
	PT	PEAT
	Rock	Rock
<u> </u>	Sandstone	Sandstone
/ <b>.</b> • / <b>.</b> •	SC SC	CLAYEY SAND
. •/• •/	SC-SM	SILT, CLAYEY SAND
. /	SHALE	Shale
	SILTSTONE	Siltstone
	ZIL I Z I DIVE	
		SILTY SAND Poorly Graded SAND
	SP	,
. /	SP-SC	Poorly Graded SAND with CLAY
	SP-SM	Poorly Graded SAND with SILT
<u> </u>	SW	Well graded SAND
<u> </u>	SW-SC	Well Graded SAND with CLAY
	SW-SM	Well Graded SAND with SILT
XX	Topsoil	Topsoil
	USGS 601	Gravel or Conglomerate 1
	USGS 654	Subgraywacke
	USGS 670	Interbedded Sandstone and Shale
	USGS 702	Quartzite
	USGS 705	Schist
	USGS 705	Schist
	USGS 708	Gneiss
(///	USGS 708	Gneiss
-	USGS 718	Granite 1
	Void	Void
	Water	Water
	Weathered Rock	Undefined
•	Water Table	Water Table during drilling
$\nabla$	Delayed Water Table	Water Table after drilling









IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A
SPECIFIC DESCRIPTION OF THE ALTERATION.

					SEGMENT HDD	3 - P
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO		

DATE SUBMITTAL / REVISION DESCRIPTION


CHAMPLAIN HUDSON POWER EXPRESS
SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY
HDD 18 RAILROAD CROSS SECTION CUT

KIEWIT PROJECT NO.
21162
CHA PROJECT NO.
066076
DRAWING NO.

C-650.1

MCS JEO

DB APP DRAWN BY: MAR DESIGNED BY: MAR APPROVED BY: JEO SCALE AS NOTED DATE 03/25



HDD #19 CONDUIT 1 ENTRY PIT CUT SECTION; STA. 20696+90 CP RAIL CANADIAN MAINLINE MP: 59.32

HDD #19 CONDUIT 1 EXIT PIT CUT SECTION; STA. 20702+69
CP RAIL CANADIAN MAINLINE MP: 59.22

BORING LOG STRIP LEGEND Blow Counts per 6" = 10-10-10 Recovery %/RQD % = 95%/90% - 11000psi =UCS 2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

Legend

ASPHALT Bedrock Bedrock Boulder Boulder Fat CLAY CH SILTY Fat CLAY CH-MH Lean CLAY SILTY CLAY CL-ML CONCRETE Concrete Fill Fill CLAYEY GRAVEL GC-GM SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL Poorly Graded Gravel with CLAY GP-GC GP-GM Poorly Graded GRAVEL with SILT Well Graded GRAVEL GW-GC Well Graded GRAVEL with CLAY GW-GM Well Graded GRAVEL with SILT Limestone ORGANIC Fat CLAY ORGANIC Lean CLAY OL/OH ORGANIC SOIL PEAT Rock Rock Sandstone Sandstone CLAYEY SAND SILT, CLAYEY SAND 2C-2M SHALE Shale SILTSTONE SILTY SAND SP Poorly Graded SAND SP-SC Poorly Graded SAND with CLAY SP-SM Poorly Graded SAND with SILT Well graded SAND SW SM-SC Well Graded SAND with CLAY Well Graded SAND with SILT SW-SMTopsoil Topsoil Gravel or Conglomerate 1 USGS 601 USGS 654 Subgraywacke Interbedded Sandstone and Shale USGS 702 USGS 705 Schist USGS 705 Schist USGS 708 Gneiss USGS 708 Gneiss USGS 718 Granite 1 Void Void Water Weathered Rock Undefined ▼ Water Table Water Table during drilling Delayed Water Table Water Table after drilling

**Power Express** 





IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ALTERED. THE ALTERING ENGINEER. ARCHITECT. LANDSCAPE ACHITECT, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

	No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	ם
	0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO	L
L						

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY HDD 19 RAILROAD CROSSING SECTION CUT


Scale in feet


KIEWIT PROJECT NO	Э.
21162	
CHA PROJECT NO	
066076	
DRAWING NO.	

C-651

AS NOTED DATE DB APP DRAWN BY: CZ DESIGNED BY: CZ APPROVED BY: JEO REV. NO.







3 HDD #19 CONDUIT 2 ENTRY PIT CUT SECTION; STA. 20696+99
CP RAIL CANADIAN MAINLINE MP: 59.32

Blow Counts per 6" = 10-10-10

Recovery %/RQD % = 95%/90%

2D strip logs shown at 10x exaggeration
3D strip logs have no exaggeration

Legend ASPHALT Bedrock Bedrock Boulder Boulder Fat CLAY CH SILTY Fat CLAY CH-MH Lean CLAY SILTY CLAY CL-ML CONCRETE Concrete Fill Fill CLAYEY GRAVEL GC-GM SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL Poorly Graded Gravel with CLAY GP-GC Poorly Graded GRAVEL with SILT GP-GM Well Graded GRAVEL Well Graded GRAVEL with CLAY GW-GM Well Graded GRAVEL with SILT Limestone ORGANIC Fat CLAY ORGANIC Lean CLAY OL/OH ORGANIC SOIL PEAT Rock Rock Sandstone Sandstone CLAYEY SAND SILT, CLAYEY SAND 2C-2M SHALE Shale SILTSTONE SILTY SAND SP Poorly Graded SAND SP-SC Poorly Graded SAND with CLAY SP-SM Poorly Graded SAND with SILT SW Well graded SAND SM-SC Well Graded SAND with CLAY Well Graded SAND with SILT SW-SMTopsoil Topsoil Gravel or Conglomerate 1 USGS 601 USGS 654 Subgraywacke nterbedded Sandstone and Shale USGS 702 USGS 705 Schist USGS 705 Schist USGS 708 Gneiss USGS 708 Gneiss USGS 718 Granite 1 Void Void Water Undefined Weathered Rock ▼ Water Table Water Table during drilling Water Table after drilling







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.


0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP

CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY HDD 19 RAILROAD CROSSING SECTION CUT KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.


C-651.1

MCS JEO

DB APP DRAWN BY: CZ DESIGNED BY: CZ APPROVED BY: JEO REV. NO. C



2 HDD #20 CONDUIT 1 ENTRY PIT CUT SECTION; STA. 20749+32
CP RAIL CANADIAN MAINLINE MP: 58.37



HDD #20 CONDUIT 1 EXIT PIT CUT SECTION; STA. 20737+42

CP RAIL CANADIAN MAINLINE MP: 58.60

SILTY Fat CLAY CH-MH Lean CLAY SILTY CLAY CL-ML CONCRETE Concrete Fill Fill CLAYEY GRAVEL GC-GM SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL GP-GC Poorly Graded Gravel with CLAY Poorly Graded GRAVEL with SILT Well Graded GRAVEL GW GW-GC Well Graded GRAVEL with CLAY GW-GM Well Graded GRAVEL with SILT Limestone Limestone Elastic SILT SILT DRGANIC Fat CLAY ORGANIC Lean CLAY OL/OH ORGANIC SOIL PEAT Rock Rock Sandstone Sandstone CLAYEY SAND SC-SM SILT, CLAYEY SAND SHALE Shale SILTSTONE Siltstone

BORING LOG STRIP LEGEND

2D strip logs shown at 10x exaggeration

Legend

Asphalt

Bedrock

Boulder

Fat CLAY

SILTY SAND

Poorly Graded SAND

Poorly Graded SAND with CLAY

Poorly Graded SAND with SILT

Well Graded SAND with CLAY

Well Graded SAND with SILT

Gravel or Conglomerate 1

Subgraywacke

Interbedded Sandstone and Shale

3D strip logs have no exaggeration

Recovery %/RQD % = 95%/90% - 11000psi =UCS

Blow Counts per 6" = 10-10-10 /

ASPHALT

Bedrock

Boulder

USGS 702 USGS 705 Schist USGS 705 Schist USGS 708 Gneiss USGS 708 Gneiss USGS 718 Granite 1 Void Void Water Water Weathered Rock Undefined Water Table Water Table during drilling Water Table after drilling

SP-SC

ZM-ZC

SW-SM

USGS 601

USGS 654

USGS 670

**Power Express** 





OF NEW O'DON OP THE OF NEW O'DON OP THE OF NEW O'DON OP THE OF TH	

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY	
ARE ACTING UNDER THE DIRECTION OF A LICENSED	
PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT	
OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN	
ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS	
ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE	
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT	
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY	
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A	
SPECIFIC DESCRIPTION OF THE ALTERATION.	


				SEGMENT 3 - PACKAGE 2 - FORT ANN TO KILL HDD 20 RAILROAD CROSS SECTION
03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO	
DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	SCALE SCALE
DAIL	SUBMITTAL/ REVISION DESCRIPTION		\	DRAWN BY: CJL DESIGNED BY: CJL APPROVED BY: JEO REV. NO.

CHAMPLAIN HUDSO	N POWER EXPRESS
SEGMENT 3 - PACKAGE 2 -	FORT ANN TO KINGSBURY
HDD 20 RAILROAD C	ROSS SECTION CUT

KIEWIT PROJECT NO.
21162
CHA PROJECT NO.
066076
DRAWING NO.

**C-652** 

AS NOTED DATE



FO = -8.4— PROPOSED ACCESS ROAD FO Elev. = UNKNOWN BORING K-131.7B = 96.8 = 147.4 = 101.0 ELE VA TION: 143.5 FO Elev. = UNKNOWN = 146.BORING K-131.7A ELEVATION: 144.6 --- EXISTING GROUND 150 \_5.2% 16-49-30-6 0.8 29-30-13-4 - APPROXIMATE HDD EXIT 17-20-20-10 8-10-7-6 3-2-2-2 - PROPOSED 5'X10'X5' EXIT PIT 8-5-6-5 6-5-6-4 1-1-1-1 4-3-3-1 0-0-0-0 - APPROXIMATE DEPTH AT INV: 106.9' 0-0-0-0 -20

HDD #20 CONDUIT 2 EXIT PIT CUT SECTION; STA. 20737+43

CP RAIL CANADIAN MAINLINE MP: 58.60


BORING LOG STRIP LEGEND Blow Counts per 6" = 10-10-10 Recovery %/RQD % = 95%/90% - 11000psi =UCS 2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

			Legend
		ASPHALT	Asphalt
		Bedrock	Bedrock
		Boulder	Boulder
		СН	Fat CLAY
	////	CH-MH	SILTY Fat CLAY
	////	CL	Lean CLAY
	////	CL-ML	SILTY CLAY
	/ /	CONCRETE	Concrete
		Fill	FILL
	15 Y 3	GC	CLAYEY GRAVEL
		GC-GM	SILTY CLAYEY GRAVEL
		GM	SILTY GRAVEL
	2	GP	Poorly Graded GRAVEL
		GP-GC	Poorly Graded Gravel with CLAY
		GP-GM	Poorly Graded GRAVEL with SILT
		GW	Well Graded GRAVEL
		GW-GC	Well Graded GRAVEL with CLAY
		GW-GM	Well Graded GRAVEL with SILT
		Limestone	Limestone
		MH	Elastic SILT
		ML	SILT
		DH DH	DRGANIC Fat CLAY
	<u>}}</u>	DL DL	DRGANIC FUT CLAY
		OL/OH	DRGANIC SDIL
		PT	PEAT
	<u> </u>	Rock Sandstone	Rock Sandstone
	/. · /. ·		
	. //	SC SM	CLAYEY SAND SILT, CLAYEY SAND
	. /	SC-SM SHALE	
		SILTSTONE	Shale Siltstone
		SM	SILTY SAND
			Poorly Graded SAND
		SP	•
	. /	SP-SC	Poorly Graded SAND with CLAY
		SP-SM	Poorly Graded SAND with SILT
	<u> </u>	SW	Well graded SAND
	A /. ·	SM-SC	Well Graded SAND with CLAY
		SM-SW	Well Graded SAND with SILT
		Topsoil	Topsoil
		USGS 601	Gravel or Conglomerate 1
		USGS 654	Subgraywacke
		USGS 670	Interbedded Sandstone and Shale
	7777	USGS 702	Quartzite
		USGS 705	Schist
		USGS 705	Schist
		USGS 708	Gneiss
		USGS 708	Gneiss
	- `	USGS 718	Granite 1
		Void	Void
		Water	Water
		Weathered Rock	Undefined
	<b>T</b>	Water Table	Water Table during drilling
-	$\nabla$	Delayed Water	Water Table after drilling









IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY
ARE ACTING UNDER THE DIRECTION OF A LICENSED
PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT
OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN
ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS
ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A
SPECIFIC DESCRIPTION OF THE ALTERATION.


					SEGMENT 3 - PACKAGE 2 - FORT ANN TO K HDD 20 RAILROAD CROSS SECTION
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO	
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: CJL DESIGNED BY: CJL APPROVED BY: JEO REV. NO.


CHAMPLAIN HUDSON POWER EXPRES	S
SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBUI	R'
HDD 20 RAILROAD CROSS SECTION CUT	


KIEWIT PROJECT NO.
21162
CHA PROJECT NO.
066076
DRAWING NO.


C-652.1

AS NOTED DATE










BORING LOG STRIP LEGEND | Blow Counts per 6" = 10-10-10 | Recovery %/RQD % = 95%/90% - 11000psi =UCS 2D strip logs shown at 10x exaggeration 3D strip logs have no exaggeration

Legend ASPHALT Bedrock Bedrock Boulder Boulder CH Fat CLAY SILTY Fat CLAY CH-MH Lean CLAY CL-ML SILTY CLAY CONCRETE Concrete Fill Fill CLAYEY GRAVEL GC-GM SILTY CLAYEY GRAVEL SILTY GRAVEL Poorly Graded GRAVEL Poorly Graded Gravel with CLAY GP-GC Poorly Graded GRAVEL with SILT GP-GM Well Graded GRAVEL Well Graded GRAVEL with CLAY GW-GM Well Graded GRAVEL with SILT Limestone Elastic SILT ORGANIC Fat CLAY ORGANIC Lean CLAY OL/OH ORGANIC SOIL PEAT Rock Rock Sandstone Sandstone CLAYEY SAND SILT, CLAYEY SAND 2C-2M SHALE Shale SILTSTONE SILTY SAND SP Poorly Graded SAND SP-SC Poorly Graded SAND with CLAY SP-SM Poorly Graded SAND with SILT SW Well graded SAND SM-SC Well Graded SAND with CLAY Well Graded SAND with SILT SW-SM Topsoil Gravel or Conglomerate 1 USGS 601 USGS 654 Subgraywacke USGS 670 nterbedded Sandstone and Shale USGS 702 USGS 705 Schist USGS 705 Schist USGS 708 Gneiss USGS 708 Gneiss USGS 718 Granite 1 Void Void Water Weathered Rock Undefined ▼ Water Table Water Table during drilling Water Table after drilling

**Power Express** 







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE
ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT
AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY
THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A
SPECIFIC DESCRIPTION OF THE ALTERATION.


					CHAMPLAIN HUDSON POWER EX SEGMENT 3 - PACKAGE 2 - FORT ANN TO KI HDD 21A RAILROAD CROSS SECTION
0	03/22/2023	ISSUED FOR CONSTRUCTION SUBMISSION	MCS	JEO	
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DRAWN BY: ES DESIGNED BY: ES APPROVED BY: JEO REV. NO.
				l	1.321.000


CHAMPLAIN HUDSON POWER EXPRESS SEGMENT 3 - PACKAGE 2 - FORT ANN TO KINGSBURY HDD 21A RAILROAD CROSS SECTION CUT


KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.


C-654.1

AS NOTED DATE
















IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

					CHAMP	LAIN HUD	SON POWE	R EX		
					SPLICE VAULT ANCHOR AND EMBED DE					
0	03/17/2023	FINAL SUBMITTAL	JNK	00						
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DDAMALDY DDI	DEGIONED DV INIK	ADDDOVED DV	SCALE		
140.	DATE	SOBINITIAL/ NEVISION DESCRIPTION		ALI	DRAWN BY: DRH	DESIGNED BY: JNK	APPROVED BY: 00	REV. NO.		

SPLICE VAULT ANCHOR AND EMBED DETAILS

21162 DRAWING NO. S-702

AS SHOWN DATE



NOTES:

1. FOR ALL SPLICE VAULT MANHOLES IN PACKAGES 1A AND 1B: AFTER CABLE COMMISSIONING, RISERS TO BE REMOVED, MANHOLE FRAMES AND COVERS TO BE LOWERED TO FINAL POSITION. MANHOLE FRAMES AND COVERS TO BE COVERED WITH 8'X 8' MIRAFI 140N GEOTEXTILE FABRIC OR EQUIVALENT. FULL DEPTH PAVEMENT WILL BE RESTORED PRIOR TO MILL AND OVERLAY AFTER CABLE COMMISSIONING.

KIEWIT PROJECT NO. CHAMPLAIN HUDSON POWER EXPRESS 21162 DRAWING NO.


S-703

SPLICE VAULT DETAILS

JNK OO AS SHOWN DATE SH.NO. DB APP DRAWN BY: DRH DESIGNED BY: JNK APPROVED BY: OO REV. NO.

CHPE								
Champlain Hudson								
Power Express								





0 03/17/2023 FINAL SUBMITTAL

DATE SUBMITTAL / REVISION DESCRIPTION

```
DESIGN SPECIFICATIONS
1. AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, 9TH EDITION, 2020
2. NYSDOT LRFD BRIDGE DESIGN SPECIFICATIONS, 2021
 3. NYSDOT LRFD BLUE PAGES, 2021
4. AREMA MANUAL FOR RAILWAY ENGINEERING, VOLUME 2 STRUCTURES, 2016
5. ASCE 7-16 MINIMUM DESIGN LOADS AND ASSOCIATED CRITERIA FOR BUILDINGS AND
    OTHER STRUCTURES
<u>DESIGN LOADS</u>
1. DEAD LOADS
 1.1. CONCRETE UNIT WEIGHT = 150 PCF
 1.2. STEEL UNIT WEIGHT = 490 PCF
 2. SUPERIMPOSED DEAD LOADS
 2.1. WEIGHT OF TWO HVDC CABLES + ONE FIBER OPTIC CABLE AND ASSOCIATED
        CONDUIT = 47.53 PLF
  2.2. WEIGHT OF CABLE TRAY = 20.57 PLF
  2.3. PULLING IRON, TROLLEY BEAM, ANCHORAGE, EMBED FORCES NOTED ON DRAWINGS
        WHERE APPLICABLE.
 3. EARTH LOADS
 3.1. SOIL BACKFILL UNIT WEIGHT = 125 PCF
 4. LIVE LOAD SURCHARGE
 4.1. 100 PSF MINIMUM
 5. LIVE LOADS
  5.1. 300 PSF MINIMUM AT GROUND SURFACE OF TRENCH SECTIONS AND VAULTS.
 5.2. HL-93
 5.3. COOPER E-80
 6. WIND LOADS
 6.1. 50 PSF TRANSVERSE
 6.2. 10 PSF LONGITUDINAL
 7. SNOW LOADS
 7.1. 50 PSF
 8. WATER
 8.1. STRUCTURES ARE ASSUMED TO BE SUBMERGED.
 9. THERMAL LOADS
  9.1. STRUCTURES ARE SUBJECT TO THERMOMECHANICAL LOADING FROM HVDC CABLES.
  9.2. TEMPERATURE GRADIENT.
 10. SEISMIC LOADING
  10.1. BURIED STRUCTURES ARE NOT SUBJECT TO SEISMIC PROVISIONS.
MATERIALS:
 1. REINFORCED CONCRETE
  1.1. f'c = 5,000 \text{ PSI AT 28 DAYS, UNO}
```

1.2. F3 FREEZE-THAW CATEGORY WHERE NOTED 2. REINFORCING STEEL 2.1. ASTM A706, GRADE 60, UNO 3. STRUCTURAL STEEL 3.1. ASTM A36, UNO

4. BOLTS 4.1. ASTM A325, UNO 5. NUTS 5.1. ASTM A563, UNO 6. WASHERS

6.1. ASTM F436, UNO 7. POLYMER CONCRETE 7.1. ANSI/SCTE 77 2013

9.1. SCH 40

8. REINFORCED THERMOSETTING RESIN CONDUIT 8.1. NEC 355 9. PVC

CHPE **Power Express** 





IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

					CHAMP	LAIN HUE	SON F	POWE	EREX	
					STRUCTURAL GENERAL NOTES AND ABI					
					-					
0	03/17/2023	FINAL SUBMITTAL	JNK	00						
No.	DATE	CLIDMITTAL / DEVICION DECODIDATION	DB	A DD					SCALE	
INO.	DATE	SUBMITTAL / REVISION DESCRIPTION	סט	APP	DRAWN BY: DRH	DESIGNED BY: JN	<   APPROVE	D BY: 00	REV. NO.	

## CHAMPLAIN HUDSON POWER EXPRESS STRUCTURAL GENERAL NOTES AND ABBREVIATIONS

KIEWIT PROJECT NO. 21162 DRAWING NO.

S-705 AS SHOWN DATE

BEARING CAST IN PLACE CENTERLINE CLR CLEAR COVER DIAMETER **ELEVATION** GIRDER HIGH STRENGTH INTERMEDIATE CONDUIT SUPPORT **INSIDE DIAMETER** IRON PIPE SIZE

KIPS PER SQUARE INCH

LONG LEG VERTICAL

OUTSIDE DIAMETER

APPROACH

ABBREVIATIONS:

NOM


PLATE PROTECTIVE POLYVINYL CHLORIDE ROUTE


NOMINAL

PRECAST

STANDARD WALL THICKNESS UNLESS NOTED OTHERWISE

STATION





NOTES:

- 1. TYPICAL SECTION AND FOLLOWING NOTES PROVIDED PROPOSED DESIGN CRITERIA TO BE APPLIED FOR DRAINS LOCATED BELOW THE DUCT BANK WITHIN THE NYSDOT RIGHT OF WAY, PENDING APPROVAL.
- 2. EXCAVATION FOR / CONSTRUCTION OF FUTURE DRAIN REPAIRS/REPLACEMENTS, AND RELATED SHORING CALCULATIONS BY OTHERS.
- 3. D = DISTANCE FROM EXISTING GROUND LEVEL TO DRAIN INVERT.
- 4. h = DISTANCE FROM BOTTOM OF TRENCH PROTECTIVE CONCRETE/BOTTOM OF BRIDGING SUPPORT, TO TOP OF EXISTING DRAINAGE PIPE.
- 5. FOR SINGLE PIPE, OD = OUTSIDE DIAMETER OF PIPE; FOR MULTIPLE PIPES IN PARALLEL, OD = DISTANCE BETWEEN OUTSIDE EDGES OF EXTERIOR PIPES.
- 6. REFER TO CIVIL PLAN & PROFILE DRAWINGS FOR VALUE OF "h". 7. FOR D<14FT, ALL FUTURE EXCAVATIONS TO REPAIR / REPLACE EXISTING DRAINAGE
- PIPES WILL BE SHORED EXCAVATION, WITH MAXIMUM EXCAVATION WIDTH OF w=2FT+OD+2FT (DESIGN/CONSTRUCTION BY OTHERS). 8. FOR D>14FT, TRENCH-LESS METHOD WILL BE USED TO REPAIR/REPLACE EXISTING
- DRAINAGE PIPES (DESIGN/CONSTRUCTION BY OTHERS).
- 9. BRIDGING SUPPORT IS PROVIDED OVER LENGTH L = w+2a.
- 10. BRIDGING SUPPORT IS NOT PROVIDED WHEN D>14FT. 11. BRIDGING SUPPORT IS DESIGNED TO CARRY DUCT BANK WEIGHT, ONLY. SOIL
- ABOVE THE DUCT BANK IS REMOVED BEFORE EXCAVATING UNDER THE DUCT BANK.
- 12. "a" DIMENSION IS 2'-0" MINIMUM.







IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

1	12/05/2022	REVISED NYSDOT HWP SUBMISSION	JNK	oc
0	09/21/2022	FINAL EM&CP SUBMISSION	JNK	oc
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APF

CHAMPLAIN HUDSON POWER EXPRESS


REINFORCING TRAY OVER UTILITIES


KIEWIT PROJECT NO. 21162


S-720


DRAWING NO.

P DRAWN BY: DRH DESIGNED BY: JNK APPROVED BY: OO REV. NO. AS SHOWN DATE XX OF XXX
















IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR TO ALTER AN ITEM IN ANY WAY. IF AN ITEM BEARING THE STAMP OF A LICENSED PROFESSIONAL IS ALTERED, THE ALTERING ENGINEER, ARCHITECT, LANDSCAPE ARCHITECT OR LAND SURVEYOR SHALL STAMP THE DOCUMENT AND INCLUDE THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE, THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

					TYDICAL YALII T								
					TYPICAL VAULT								
					DETAILS								
0	03/15/2023	ISSUED FOR CONSTRUCTION	DLM	ASM									
No.	DATE	SUBMITTAL / REVISION DESCRIPTION	DB	APP	DD AVA(ALD) ( DIA	A DEGIGNED BY	0.0	A DDD OVED DV		SCALE			
INO.	DAIL	SUBMITTAL / REVISION DESCRIPTION		AFF	DRAWN BY: DLM	M   DESIGNED BY:	SD	APPROVED BY:	ASM	REV. NO.			

CHAMPLAIN HUDSON POWER EXPRESS

KIEWIT PROJECT NO. 21162 CHA PROJECT NO. 066076 DRAWING NO.

**C-802** 

03/15/2023 0 SH.NO.